WATER WELL REPORT

State Permit No. ...

STATE OF OREGON

 3	F	N	
Ø	1	0	_
U	1	<u>~</u>	<u> </u>
	8	- 200	810

State Well No.

16/4W	٠	2	2	H	(2)

(1) OWNER:	(11) WELL TESTS: Drawdown is amount water level is lowered below static level					
Name Elmer Lehman and Ethel M Lehman	Was a pump test made? X Yes No If yes, by whom?					
Address 401 Tone Pine Drive	Yield: 90 gal.	/min. with 10	ft. drawdown af	ter hrs.		
Degree, Oregon function city	**	***	,, <u> </u>	"		
(2) LOCATION OF WELL:	**	,,	"			
County Tane Owner's number, if any—	Bailer test gal./	min. with	ft. drawdown aft	er hrs.		
S.E. 4 N.E. 4 Section 22 T. 16S R. 4 W.M.	Artesian flow	g.p.m.	Date			
Bearing and distance from section or subdivision corner	Temperature of water	Was a chemica	al analysis made?	☐ Yes ☐ No		
N15° 30'W 1345' from the southeast corner of	(12) WELL LOG:	Diamet	ter of well	inches.		
the E.D. Judkins Donation I and Claim No. 17.	Depth drilled		completed well			
Township 16 South, Range 4 West of the	Formation: Describe by	color, character, s	ize of material an	d structure, and		
Willamette Meridian	show thickness of aquife stratum penetrated, with	ers and the kind a h at least one enti	nd nature of the 1 ry for each chang	naterial in each se of formation.		
	M	ATERIAL	FI	ROM TO		
TYPE OF WORK (check):	8 ft top soi	7				
New Well X Deepening ☐ Reconditioning ☐ Abandon ☐	8 ft sand an					
If abandonment, describe material and procedure in Item 11.	2 ft sand	W. W. Ling				
	3 ft sand an	d gravel				
(4) PROPOSED USE (check): (5) TYPE OF WELL:	2 ft sand gr		ulders			
Domestic Industrial Municipal Rotary Driven Cable Jetted		<u></u>				
gation Test Well Other Dug Bored						
(A) CACING INCOMALIAND	· · · · · · · · · · · · · · · · · · ·					
(6) CASING INSTALLED: Threaded Welded						
.3						
"Diam, from ft. to ft. Gage ft						
"Diam, from ft. Gage						
(7) PERFORATIONS: Perforated? ☐ Yes ☐ No						
Type of perforator used v slots				-		
SIZE of perforations 3/16 in. by 10 in.						
perforations from pgift ft. to3 ft.						
perforations from ft. to ft.						
perforations fromft. toft.						
perforations from						
perforations from ft. to ft.						
(8) SCREENS: Well screen installed ☐ Yes ▼No						
nufacturer's Name						
Type Model No						
Diam. Slot size Set from ft. to ft.		n.o				
Diam,	Work started June	19 , 1957. c	ompleted	19		
(4) CONSTRUCTION:	(13) PUMP:					
as well gravel packed? Yes No Size of gravel:	Manufacturer's Name .	-				
Gravel placed from ft. to ft.	Type: H.P.					
Was a surface seal provided? $\ \square$ Yes $\ \square$ No $\ $ To what depth? ft.						
Material used in seal—	Well Driller's Statem	ent:				
Did any strata contain unusable water? Yes No	This well was dri true to the best of my			this report is		
Type of water? Depth of strata		•				
Method of sealing strata off		er-Jensen C				
(10) WATER LEVELS:		n, firm, or corporati Florina Roa		or print)		
Static level 10 ft. below land surface Date Juny 19.57	Address 2880 Elwira Road, Fugene, Oregon					
Artesian pressure lbs. per square inch Date	Driller's well number 23x456x none					
Log Accepted by:	Is million	1/2. to	(1/n	en Glis		
8 90	[Signed]	(Well Dri	iller)	794,000		
[Signed] C. Clerk and Date (1957), 195/	License No93-4	56D:	ate	19		