RECEIVED
AUG 13 1962
STATE ENGINEER
SALEM, OREGON

LANE
8218

16/4W-28

NOTICE TO WATER WELL CONTRACTOR
The original and first copy of this report are to be filed with the STATE ENGINEER, SALEM 10, OREGON within 30 days from the date of well completion.

WATER WELL REPORT
STATE OF OREGON
(Please type or print)

State Well No.
State Permit No.

(1) OWNER:
Name C C Keith
Address 4730 Parkric Rd
Eugene Oregon

(2) LOCATION OF WELL:
County Lane Driller's well number 86
¼ ¼ Section 28 T. 16S R. 4W W.M.
Bearing and distance from section or subdivision corner

(3) TYPE OF WORK (check):
New Well ☑ Deepening ☐ Reconditioning ☐ Abandon ☐
If abandonment, describe material and procedure in Item 12.

(4) PROPOSED USE (check):
Domestic ☐ Industrial ☐ Municipal ☐
Irrigation ☐ Test Well ☐ Other ☐

(5) TYPE OF WELL:
Rotary ☐ Driven ☐
Cable ☑ Jetted ☐
Dug ☐ Bored ☐

(6) CASING INSTALLED: Threaded ☐ Welded ☑
..... " Diam. from ft. to ft. Gage
..... " Diam. from ft. to ft. Gage
..... " Diam. from ft. to ft. Gage

(7) PERFORATIONS: Perforated? ☑ Yes ☐ No
Type of perforator used Torch
Size of perforations ¼ in. by 10 in.
50 perforations from 21 ft. to 50 ft.
..... perforations from ft. to ft.
..... perforations from ft. to ft.
..... perforations from ft. to ft.
..... perforations from ft. to ft.

(8) SCREENS: Well screen installed ☐ Yes ☑ No
Manufacturer's Name
Type Model No.
Diam. Slot size Set from ft. to ft.
Diam. Slot size Set from ft. to ft.

(9) CONSTRUCTION:
Well seal—Material used in seal Bentonite
Depth of seal 18 ft. Was a packer used? Sand
Diameter of well bore to bottom of seal 10 in.
Were any loose strata cemented off? ☐ Yes ☑ No Depth
Was a drive shoe used? ☑ Yes ☐ No
Was well gravel packed? ☐ Yes ☑ No Size of gravel:
Gravel placed from ft. to ft.
Did any strata contain unusable water? ☐ Yes ☐ No
Type of water? Depth of strata
Method of sealing strata off

(10) WATER LEVELS:
Static level 13' 6" ft. below land surface Date 7-19-62
Artesian pressure lbs. per square inch Date

(11) WELL TESTS: Drawdown is amount water level is lowered below static level
Was a pump test made? ☑ Yes ☐ No If yes, by whom? Driller
Yield: 50 gal./min. with 13 ft. drawdown after 2 hrs.
" " " "
" " " "
Bailer test gal./min. with ft. drawdown after hrs.
Artesian flow g.p.m. Date
Temperature of water Was a chemical analysis made? ☐ Yes ☐ No

(12) WELL LOG: Diameter of well below casing 8"
Depth drilled 53 ft. Depth of completed well 51 ft.
Formation: *Describe by color, character, size of material and structure, and show thickness of aquifers and the kind and nature of the material in each stratum penetrated, with at least one entry for each change of formation.*

MATERIAL	FROM	TO
Clay	0	18
Sand & gravel clay	18	24
Black Sand & (water Bearing	24	35
Sand & gravel clay	35	45
Sand & Small gravel	45	50

Work started 7-16 1962 Completed 7-18 1962
Date well drilling machine moved off of well 7-19 1962

(13) PUMP:
Manufacturer's Name
Type: H.P.

Water Well Contractor's Certification:
This well was drilled under my jurisdiction and this report is true to the best of my knowledge and belief.
NAME Bonnie Brae Well Drilling
(Person, firm or corporation) (Type or print)
Address RH 2 Box 198 SPfld Oregon
Drilling Machine Operator's License No. 24
[Signed] P D Zehner
(Water Well Contractor)
Contractor's License No. 207 Date 7-19, 1962

(USE ADDITIONAL SHEETS IF NECESSARY)