## OCT 10 1961 DBSERVATION WELL

LANE 6-2091

This is a DUPLICATE log-the original having already been filled out and state Well No. File Original and First Copy with the STATE ENGINEER, SALEM, OREGON STATE OF OREGON State Permit No. 16/4W -29 J(2)

(1) OWNER:	(11) WELL TESTS: Drawdown is amount water level is lowered below static level
Name Calvin Banton (BOSTICK CONST. Co.)	Was a pump test made? XYes  \( \sigma\) No If yes, by whom Well Dri
Address	Yield: 45 gal./min. with 18 ft. drawdown after 1 hr
	" " " " " "
(2) LOCATION OF WELL:	33 29 29
County Lane Owner's number, if any—	Bailer test gal./min. with ft. drawdown after hr
1/4 1/4 Section T. R. W.M	Artesian flow g.p.m. Date
Bearing and distance from section or subdivision corner	Temperature of water Was a chemical analysis made?   Yes   N
	(19) WELL LOC
	(12) WELL LOG: Diameter of well
	Depth drilled 715 ft. Depth of completed well 66 f
	Formation: Describe by color, character, size of material and structure, an show thickness of aquifers and the kind and nature of the material in each stratum penetrated, with at least one entry for each change of formation
	MATERIAL FROM TO
(3) TYPE OF WORK (check):	Dirt 0 7
New Well   Deepening □ Reconditioning □ Abandon □	
If abandonment, describe material and procedure in Item 11.	narrow strip of loose mater-
PROPOSED TIGHT ( I I I )	ial at about 23 ft.
PROPOSED USE (check): (5) TYPE OF WELL:	Sand & gravel (mostly sand) 29 50
Domestic   Industrial   Municipal   Rotary   Driven   Cable   Jetted	(Water bearing but poor)
Irrigation 🗹 Test Well 🗌 Other 🔲 Dug 🗎 Bored 🗍	Sand & gravel (water bearing 50 65
(C) CACING INCHALLED	better than above with a
(6) CASING INSTALLED: Threaded Welded X 5/8 ODDiam. from	narrow strip of good water
•	bearing gravel at 65 ft.
" Diam. from	Sand - Poor water producer 65 713
" Diam. from ft. to ft. Gage	
(7) PERFORATIONS: Perforated? N Yes No	
Type of perforator used Mills	
SIZE of perforations approx. 3/11 6y 1 3/4 in.	
pprox 750 perforations from 23 ft. to 68 ft.	
perforations from ft. to ft.	
perforations fromft. toft.	
perforations from ft. to ft.	
perforations from ft. to ft.	
'(0) CODERIO	
(8) SCREENS: Well screen installed □ Yes ▼ No	
Manufacturer's Name	
Type Model No.	
Slot size Set from ft. to ft.	
Slot size Set from ft, to ft,	Work started 8-18 19 60 Completed 8-27 19 60
(9) CONSTRUCTION:	(13) PUMP:
Was well gravel packed? ☐ Yes ♠ No Size of gravel:	
Gravel placed fromft. toft.	Manufacturer's Name
Was a surface seal provided? ☐ Yes ☐ No To what depth?	Type: H.P.
Did any strata contain unusable water?  Yes No	Well Driller's Statement:
Type of water? Depth of strata	This well was drilled under my jurisdiction and this report is true to the best of my knowledge and belief.
Method of sealing strata off	
	NAME Wayne Hayes Well Drilling (Person, firm, or corporation) (Type or print)
(10) WATER LEVELS:	EZE Coheren Da Thomas O
Static level 10 ft. below land surface Date 8-27-60	Address 333 Coburg Rd., Eugene, Ure.
Artesian pressure lbs. per square inch Date	Driller's well number
Log Accepted by:	
/s/ Calvin Banton	[Signed] /s/ Wayne Hayes (Well Driller)
[Signed] Date19	
This is a duplicate log. The original	License No. 91 Date Sept 1 19 60
(USE ADDITIONAL SI	105 Was Asigned Sept. 1, 1960