NOTICE TO WATER WELL CONTRACTOR The original and first copy of this report are to be filed with the

State Well No.

state engineer, salem, oregon 97310
within 30 days from the date 51 A TE ENGINEER bype or print)
of well completion.

State Permit No. ...

Nome Name of Market	lowered below static level
Name Is Miss Sumile	Was a pump test made? ☐ Yes ☐ No If yes, by whom?
Address 4225 Shian Bull House	Yield: 275 gal./min. with 50 ft. drawdown after / hrs.
Junellan (uly anigon	" " "
(2) LOCATION OF WELL:	" " " "
County Driller's well number	Bailer test gal./min. with ft. drawdown after hrs.
1/4 1/4 Section 29 T. 165 R. 441) W.M.	Artesian flow g.p.m. Date
Bearing and distance from section or subdivision corner	Temperature of water Was a chemical analysis made? Yes No
	(12) WELL LOG: Diameter of well below casing
	Depth drilled 85 6 ft. Depth of completed well 85 6" ft.
	Formation: Describe by color, character, size of material and structure, and show thickness of aquifers and the kind and nature of the material in each stratum penetrated, with at least one entry for each change of formation.
(3) TYPE OF WORK (check):	MATERIAL FROM TO
	sail 09
	senda grando 9 13
andonment, describe material and procedure in Item 12.	sansy Clay 13 17
(4) PROPOSED USE (check): (5) TYPE OF WELL:	Sand smell grand - some Clay 17 24
Domestic Industrial Municipal Rotary Driven	send & med graved 24 27
Irrigation Test Well Other Cable Jetted	sand larger gracel 27 31
Dug Bored	sand & gracel un/Clay 31 43
(6) CASING INSTALLED: Threaded Welded	Mandy Clay 1 43 56
"Diam. fromft. Gage	Clay 56 62
8 "Diam. from + 18 ft. to & 4 6 ft. Gage 1250	Allee sandy Clay 62 696
" Diam. from ft. to ft. Gage	grands - small 696" 73
(7) DEDEODATIONS.	Mungaly Sandy Clay 73 73-
7	gravel & band to Clay 75-856
Type of perforator used Mills Enife	
Size of perforations /4 in. by 2/2 in.	
perforations fromft. toft.	
perforations from ft. to ft.	
perforations from ft. to ft.	
perforations from ft. to ft.	
perforations fromft. toft.	
(8) SCREENS: Well screen installed? Yes Yes	
Manufacturer's Name	-
Model No.	
ft Slot size Set from ft. to ft.	TT 10-9/ 11/1 10-9/
Diam ft. to ft.	Work started 10-26 1966 Completed 10-3/ 19
(9) CONSTRUCTION:	Date well drilling machine moved off of well 10-31 1966
(b) Constitution,	(13) PUMP:
Well seal—Material used in seal	Manufacturer's Name
Depth of seal ft. Was a packer used?	Type:
Diameter of well bore to bottom of seal in.	
Were any loose strata cemented off? Yes No Depth	Water Well Contractor's Certification:
Was a drive shoe used? ✓ Yes □ No	This well was drilled under my jurisdiction and this report is
Was well gravel packed? Tes No Size of gravel:	true to the best of my knowledge and belief.
Gravel placed from ft. to ft.	CHRISTENSEN DRILLING & IRRIGATION
Did any strata contain unusable water? Yes DNo	NAME 350n West of Standard Pa. 344-4205 Type or print)
Type of water? depth of strata	Address Eugene, Oregon 97402
Method of sealing strata off	~ ~ <i>-</i> /
(10) WATER LEVELS:	Drilling Machine Operator's License No.
The state of the s	[Signed] Mark II Musique
Static level 7 ft. below land surface Date 10-31-66	[Signed] (Water Well Contractor)
Artesian pressure lbs. per square inch Date	Contractor's License No. 97 Date 11/4 1966