## WATER WELL REPORT STATE OF OREGON

## RECEIVED SEP 10 1980

WATER RESOURCES DEPT SALEM, OREGON

SALEM, OREGON 97310
within 30 days from the date of well completion:

State Permit No.

Well ID #: L 32148

(1) OWNER:	(10) LOCATION OF WELL:
Name Mr. L. B. Craytor	County Lane Driller's well number
Address 215 Hileman Lane, Eugene, Oregon	4. 4 Section 36 T. 16 R. 4W W.M.
City Eugene State Oregon	Tax Lot # 40 Lot Blk Subdivision
(2) TYPE OF WORK (check):	Address at well location: Same
· · · · · · · · · · · · · · · · · · ·	
New Well ☐ Deepening ☐ Reconditioning ☐ Abandon ☐ If abandonment, describe material and procedure in Item 12.	(11) WATER LEVEL: Completed well.
(3) TYPE OF WELL: (4) PROPOSED USE (check):	Depth at which water was first found 11 ft.
	Static level 4 ft. below land surface. Date $8/5/80$
y Air	Artesian pressure lbs. per square inch. Date
Cable 🗵 Bored 🗆 Thermal: Withdrawal 🗆 Reinjection 🗆	(12) WELL LOG: Diameter of well below casing
(5) CASING INSTALLED: Steel K Plastic	Depth drilled 32 ft. Depth of completed well 32 ft.
Threaded □ Welded 🔀	Formation: Describe color, texture, grain size and structure of materials; and show thickness and nature of each stratum and aquifer penetrated, with at least one entry
10" Diam. from†1 ft. to32 ft. Gauge	for each change of formation. Report each change in position of Static Water Level
"Diam. from	and indicate principal water-bearing strata.
LINER INSTALLED:	MATERIAL From To SWL
"Diam. from	Soil & sand 0 8
(6) PERFORATIONS: Perforated?   ✓ Yes □ No	Sand, gravel & clay 8 20
Type of perforator used Torch	Sand, gravel, loose 20 25 4'
Size of perforations $3/8$ in. by 6 in.	sand, gravel, clay 25 28
90 perforations from 31 ft. to 18 ft.	Sand, gravel, little clay 28 31
perforations from	Sand, gravel, clay 31 32 4'
perforations fromft. toft.	
(F) CODEENC.	
(7) SCREENS: Well screen installed?   Yes.   No	
Manufacturer's Name  Type Model No.	
Diam. Slot Size Set from ft. to ft.	
Diam. Slot Size Set from ft. to ft.	
Drawdown is amount water level is lowered	
(8) WELL TESTS: below static level	
was a pump test made? ☐ Yes 돈 No If yes, by whom?	
Yield: gal./min. with ft. drawdown after hrs.	
<i>II</i>	
Air test 300 gal./min. with drill stem at 10 ft. 1 hrs.	
er test gal./min. with ft. drawdown after hrs.	,
Artesian flow g.p.m.	
Temperature of water Depth artesian flow encounteredft.	Work started $8/1$ 1980 Completed $8/5$ 1880
(9) CONSTRUCTION: Special standards: Yes □ No 🕏	Date well drilling machine moved off of well 19 80
Well seal—Material used <u>Cement grout</u>	Drilling Machine Operator's Certification!
Well sealed from land surface toft.	This well was constructed under my direct supervision. Materials used
Diameter of well bore to bottom of seal14 in.	and information reported above are true to my best knowledge and belief.
Diameter of well bore below seal10in.	[Signed] Drilling Magnine Operator) Date 8/11, 1980.
Number of sacks of cement used in well seal	Drilling Machine Operator's License No
How was cement grout placed? Pressure grouted.	Water Wall Contractor's Contification
,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,	Water Well Contractor's Certification:  This well was drilled under my jurisdiction and this report is true to
Was pump installed?	the best of my knowledge and belief
Was a drive shoe used?     Yes □ No   Plugs   Size: location   ft.   Size: location   ft.	Name Pitcher Pump & Drilling Company
Did any strata contain unusable water?   Yes No	(Person, firm or corporation) Address 87829 Greenhill Rd, Hugene Or 97402
Type of Water? depth of strata	Address Steel Hill Hugerie FOT 97402
Method of sealing strata off	[Signed] (Water Well Contractor)
Was well gravel packed? ☐ Yes XNo Size of gravel:	Contractor's License No. Date 80
Gravel placed from ft. to ft.	, 10
NOTICE TO WATER WELL CONTRACTOR	WATER RESOURCES DEPARTMENT, SP*12658-690

The original and first copy of this report are to be filed with the