

NOTICE TO WATER WELL CONTRACTOR
The original and first copy
of this report are to be
filed with the

STATE ENGINEER, SALEM, OREGON 97308
within 30 days from the date
of well completion.

WATER WELL REPORT

STATE OF OREGON NOV 19 1973

(Please type or print) STATE ENGINEER
SALEM, OREGON

RECEIVED

State Well No. 16S/5W-25

State Permit No. SE/ANE/4

LANE
8727

26
16S/5W-25
SE/ANE/4
1-8061

(1) OWNER:

Name EUGENE HILL
Address Rt 1 Box 42
Eugene, Oregon

(2) TYPE OF WORK (check):

New Well Deepening Reconditioning Abandon
If abandonment, describe material and procedure in Item 12.

(3) TYPE OF WELL:

Rotary Driven
Cable Jetted
Dug Bored

(4) PROPOSED USE (check):

Domestic Industrial Municipal
Irrigation Test Well Other

(5) CASING INSTALLED:

10" Diam. from 0 ft. to 86 ft. Gage 250
" Diam. from ft. to ft. Gage
" Diam. from ft. to ft. Gage

(6) PERFORATIONS:

Perforated? Yes No.
Type of perforator used torch
Size of perforations 1/2 in. by 6 in.
120 perforations from 43 ft. to 80 ft.
perforations from ft. to ft.
perforations from ft. to ft.

(7) SCREENS:

Well screen installed? Yes No
Manufacturer's Name
Type Model No.
Diam. Slot size Set from ft. to ft.
Diam. Slot size Set from ft. to ft.

(8) WELL TESTS:

Drawdown is amount water level is lowered below static level
Was a pump test made? Yes No If yes, by whom?
Yield: gal./min. with ft. drawdown after hrs.
Ballor test 90 gal./min. with 70 ft. drawdown after 1 hrs.
Artesian flow g.p.m.
Temperature of water Depth artesian flow encountered ft.

(9) CONSTRUCTION:

Well seal—Material used undisturbed
Well sealed from land surface to ft.
Diameter of well bore to bottom of seal in.
Diameter of well bore below seal 10 1/8 in.
Number of sacks of cement used in well seal sacks
Number of sacks of bentonite used in well seal sacks
Brand name of bentonite
Number of pounds of bentonite per 100 gallons
of water lbs./100 gals.
Was a drive shoe used? Yes No Plugs Size: location ft.
Did any strata contain unusable water? Yes No
Type of water? depth of strata
Method of sealing strata off
Was well gravel packed? Yes No Size of gravel:
Gravel placed from ft. to ft.

(10) LOCATION OF WELL:

County LANE Driller's well number
1/4 1/4 Section 25 T. 16S R. 5W W.M.
Bearing and distance from section or subdivision corner

(11) WATER LEVEL: Completed well.

Depth at which water was first found 41 ft.
Static level 12 ft. below land surface. Date 10/4/73
Artesian pressure lbs. per square inch. Date

(12) WELL LOG:

Diameter of well below casing EX 10"
Depth drilled 52 ft. Depth of completed well EX 86 ft.

Formation: Describe color, texture, grain size and structure of materials; and show thickness and nature of each stratum and aquifer penetrated, with at least one entry for each change of formation. Report each change in position of Static Water Level and indicate principal water-bearing strata.

Table with columns MATERIAL, From, To, SWL. Rows include: existing well, brown sandy clay, sand & gravel, yellow sand-course, multicolor gravel, blue clay, blue clay & gravel.

Work started 9/27/73 19 Completed 10/4/73 19
Date well drilling machine moved off of well 10/4/73 19

Drilling Machine Operator's Certification:

This well was constructed under my direct supervision. Materials used and information reported above are true to my best knowledge and belief.

[Signed] Date 10/15/73
(Drilling Machine Operator)

Drilling Machine Operator's License No. 310

Water Well Contractor's Certification:

This well was drilled under my jurisdiction and this report is true to the best of my knowledge and belief.

Name CORVALLIS DRILLING CO INC
(Person, firm or corporation) (Type or print)

Address 3440 sw 3rd; Corvallis, Ore

[Signed] (Water Well Contractor)

Contractor's License No. 560 Date 10/15/73, 19