State Well No.

NOTICE TO WATER WELL CONTRACTOR The original and first copy of this report are to be filed with the AUG 2 C 1972state of oregon

STATE ENGINEER, SALEM, OREGON 230 E ENGINEER type or print)
within 30 days from the date of well completion.

SALEM. OF Do not write above this line)

State Permit No.

(1) OWNER'n House	(10) LOCATION OF WELL:
Name Legen Heuse-Hudelan-Anne M. Heilsern	County Lane Driller's well number#397A
NameOregen Heuse-Rudelph-Anne M.Heilbern Address Star Rte 1: Bex 35e, Yachats, Oregen 97498	4 4 Section 10&3T.16S R. 12W W.M.
(2) TYPE OF WORK (check):	Bearing and distance from section or subdivision cornerLots, 1&6. Tie:N.25 W.101 feet from N.W.corner of (
New Well ☐ Deepening ☐ Reconditioning ☐ Abandon ☐	cement water tank te well.
If abandonment, describe material and procedure in Item 12.	
(3) TYPE OF WELL: (4) PROPOSED USE (check):	(11) WATER LEVEL: Completed well.
	Depth at which water was first found 25 ft.
Rotary Driven Domestic I Industrial Municipal Domestic I Industrial Domestic I	Static level 82 ft. below land surface. Date 8-24-72
Dur Bored I Irrigation Test Well Other I	Artesian pressure lbs. per square inch. Date
CASING INSTALLED: Threaded Welded	(12) WELL LOG: Diameter of well below casing 811
"Diam. from he ft. to here ft. Gage	Depth drilled 42 ft. Depth of completed well 174 ft.
did" Diam. from net disturbed catilise	Formation: Describe color, texture, grain size and structure of materials;
" Diam. from ft. to ft. Gage	and show thickness and nature of each stratum and aquifer penetrated,
) PERFORATIONS: Perforated? Tyes X No.	with at least one entry for each change of formation. Report each change in position of Static Water Level and indicate principal water-bearing strata.
Type of perforator used	MATERIAL From To SWL
Size of perforations in. by in.	
	hard blue grey lave reck 122 149 red lava reck
perforations from	hnerm Terro mania
perforations from	Drewn Lava reck 154 174 101
perforations from ft. to ft.	
(7) SCREENS: Well screen installed? Tyes TX No	
Manufacturer's Name	
Type Model No.	
Diam Slot size Set from ft. to ft.	
Diam. Slot size Set from ft. to ft.	
(8) WELL TESTS: Drawdown is amount water level is lowered below static level	
Was a pump test made? Yes □ No If yes, by whom? driller	
d: 7 gal./min. with 67 ft. drawdown after /4 hrs.	
" " "	
" " "	
Bailer test gal./min. with ft. drawdown after hrs.	
estesian flow g.p.m.	9 21 72 0 01 70
mperature of water 50 Depth artesian flow encountered ft.	Work started 8-21 1973 Completed 8-24 1973
(9) CONSTRUCTION:	Date well drilling machine moved off of well 8-24 1972
Well seal—Material used ne mere	Drilling Machine Operator's Certification:
Well sealed from land surface toft.	This well was constructed under my direct supervision. Materials used and information reported above are true to my
Diameter of well bore to bottom of seal in.	Materials used and information reported above are true to my best knowledge and belief.
Diameter of well bore below seal 8 in.	[Signed] Charles Janschow Date 8-25, 1972
Number of sacks of cement used in well seal sacks	(Drilling Machine Operator)
Number of sacks of bentonite used in well seal sacks	Drilling Machine Operator's License No. 163
Brand name of bentonite	Water Wall Contractor's Contification
Number of pounds of bentonite per 100 gallons	Water Well Contractor's Certification:
of water lbs./100 gals.	This well was drilled under my jurisdiction and this report is true to the best of my knowledge and belief.
Was a drive shoe used? ₩ Yes No Plugs Size: location ft.	
Did any strata contain unusable water? Yes No	Name Charles Panschew, Rte., 1, Bex 192. (Person, firm or corporation) (Type or print)
Type of water? depth of strata	AddressFlerence, Oregon 97439
Method of sealing strata off	Esimos Makel Panachary
Was well gravel packed? ☐ Yes ☐ No Size of gravel: No Mere	[Signed] // QUEL (Water Well Contractor)
Gravel placed from ft. to ft.	Contractor's License No. 87 Date 8-25 , 1972