NOTICE TO WATER WELL:CONTRACTOR The original and first copy of this report are to be filed with the

STATE ENGINEER, SALEM, OREGON 97310 within 30 days from the date of well completion.

Tes

## DECEMBER 1 MATER WELL REPORT

STATE OF OREGON

O (Please type or print) ATER RESOURCES CEPT No. 165/22 28

(Do not write above this line) SALEM, OREGON

(1) OWNER:	(10) LOCATION OF WELL:
Name Don Furtick	County Lane Driller's well number
Address P.O. Box 5453	12 12 12 12 12 12 12 12 12 12 12 12 12 1
Eugene, Oregon	
(2) TYPE OF WORK (check):	Bearing and distance from section or subdivision corner
New Well   ■ Deepening □ Reconditioning □ Abandon □	
If abandonment, describe material and procedure in Item 12.	
	(11) WATER LEVEL: Completed well.
(0.1001).	Depth at which water was first found 46 ft.
Rotary	Static level 34 ft. below land surface. Date 6-4-76
Dug 🗌 Bored 🗋 Irrigation 🗎 Test Well 🗌 Other 🗎	Artesian pressure lbs. per square inch. Date
CASING INSTALLED: Threaded C Welded W	and per aquate men. Date
- I TOTAL I	(12) WELL LOG: Diameter of well below casing 6"
6 "Diam from 0 ft. to 51 ft. Gage .250	Depth drilled 58 ft. Depth of completed well 51 ft.
" Diam. from	Formation: Describe color, texture, grain size and structure of materials;
" Diam. fromft. toft. Gage	and show thickness and nature of each stratum and aquifer penetrated
PERFORATIONS:  Perforated 2   Von   Fil No.	with at least one entry for each change of formation. Report each change in position of Static Water Level and indicate principal water-bearing strata.
Type of perforator used	position of State Water Level and marcale principal water-bearing strata.
	MATERIAL From To SWL
Size of perforations in, by in.	Top soil 0 2'
perforations fromft. toft.	Brown clay & boulders 2' 34'
perforations from ft. to ft.	Cemented sand & gravel 34' 45'
perforations from ft. to ft.	Sand & medium gravel 45, 58,
(7) SCREENS: Well screen installed? I Very 57 No.	
(1) SCREENS: Well screen installed?  Yes No Manufacturer's Name	
Type Model No.	
Diam. Slot size Set from ft. to ft.	1007
Diam. Slot size Set from ft. to ft.	
The state of the s	
(8) WELL TESTS: Drawdown is amount water level is lowered below static level	
Was a pump test made? ☐ Yes 🛣 No If yes, by whom?	
Yield: gal./min. with ft. drawdown after hrs.	
The second secon	10 4 4 4 10 11 4 1 1 1 1 1 1 1 1 1 1 1 1
ated by sin	10 to 1 to
Batter lest 20 gal./min. with 17 ft. drawdown after 1 hrs.	
Artesian flow g.p.m.	,
perature of water Depth artesian flow encountered ft.	67 7
(9) CONSTRUCTION:	Date well drilling machine moved off of well 6-4 1976
Well seal—Material used Cement	Drilling Machine Operator's Certification:
Well sealed from land surface toft.	This well was constructed under my direct supervision.
Diameter of well bore to bottom of seal 10 in.	Materials used and information reported above are true to my best knowledge and belief.
Diameter of well bore below seal6in.	
Number of sacks of cement used in well sealsacks	(Drilling Machine Operator)
Number of sacks of bentonite used in well seal sacks	Drilling Machine Operator's License No. 979
Brand name of bentonite	West will be a second of the s
Number of pounds of bentonite per 100 gallons	Water Well Contractor's Certification:
of water lbs./100 gals.	This well was drilled under my jurisdiction and this report is true to the best of my knowledge and belief.
Was a drive shoe used? X Yes No Plugs Size: location ft.	Name Casey Jones Wall Dwilliam G. T.
Did any strata contain unusable water?   Yes X No	Name Casey Jones Well Drilling Co. Inc. (Person, firm or corporation) (Type or print)
Type of water? depth of strata	Address 37115 Immigrant Rd. Pleasant Hill, Ore.
Method of sealing strata off	
Was well gravel packed? ☐ Yes ☑ No Size of gravel:	[Signed] (Water Worl Contractor)
Gravel placed from ft. to ft.	(water went contractor)
It. 10 ft.	Contractor's License No. <u>559</u> Date <u>6-4-76</u> , 19