NOTICE TO WATER WELL CONTRACTOR The original and first copy of the poor to be filed with the po

WATER RESOURCES DEPARTMENT C '7 1978
SALEM, OREGON 97310 DEC '7 within 30 days from the date

STATE OF OREGON

(Please type or print)

of well complettwATER RESOURCES DEPART write above this line)

LANE State Well No. 165/35-20C 95/8 State Permit No.

SALEM, UNEGUN	(10) TOCAMION ON THE	
(1) OWNER: Name Nat Giustina (RW)	(10) LOCATION OF WELL: County Lane Driller's well number 1123/71	
Name Nat Giustina (RW) Address 880 Crest Drive	Dimer's well flumber	
Eugene, Oregon	3 SW 14 Section 20 T. 16 R. 3E	W.M.
(2) TYPE OF WORK (check):	Bearing and distance from section or subdivision corner	
New Well Deepening Reconditioning Abandon		
If abandonment, describe material and procedure in Item 12.	CHAN TEXAMETER T TAXYET CO	
(3) TYPE OF WELL: (4) PROPOSED USE (check):	(11) WATER LEVEL: Completed well. Depth at which water was first found 35	
Rotary Driven	37/0	ft.
Cable Jetted 🗆 Domestic 🗀 industrial 🚨 Municipal 📑	Static level 28 ft. below land surface. Date 11/2	- 17 (0
Dug Bored Irrigation Test Well Other	Artesian pressure lbs. per square inch. Date	
8 "Diam from #1 ft to 16 ft Gage .250 "Diam from ft to ft Gage .250	(12) WELL LOG: Diameter of well below casing Depth drilled 75 78 ft. Depth of completed well 78 7	8# 75 _{ft.}
"Diam, from ft. to ft. Gage ft. Gage	Formation: Describe color, texture, grain size and structure of mat	erials;
	and show thickness and nature of each stratum and aquifer pene with at least one entry for each change of formation. Report each cha	
(b) PERFORATIONS: Perforated? Yes No.	position of Static Water Level and indicate principal water-bearing	strata.
Type of perforator used	· · · · · · · · · · · · · · · · · · ·	swl
Size of perforations in. by in.	Top Soil Brown Sandy Loam 0 6	
perforations from	Brown Clay / Sand & Gravel 6 25	
perforations from ft. to ft.	Brown Clay 25 35 Smal Cobbles & Gravel 35 53	~ 0
perforations from ft. to ft.		28 28
(7) SCREENS: Well screen installed? ▼ Yes □ No		<u>20 </u>
Manufacturer's Name Johnson	Black Sand 72 75 2	<u> </u>
Type Stainless Steel Model No. Telescope		
Diam. 8 Slot size 50 Set from 47 ft. to 67 ft.		
Diam. Slot size Set from ft. to ft.		
(8) WELL TESTS: Drawdown is amount water level is		
lowered below static level		
Was a pump test made? Yes No If yes, by whom?		
d: gal./min. with ft. drawdown after hrs.		
" " "		
<i>"</i> " " "		
Bailer test 45 gal./min. with 1 ft. drawdown after 2 hrs.		
Artesian flow g.p.m.		
mperature of water 51 Depth artesian flow encountered ft.	Work started 10/24/ 1978 Completed 11/27/	19 78
(9) CONSTRUCTION:	Date well drilling machine moved off of well 11/27/	¹⁹ 78
Well seal-Material used Portland Cement Type III	Drilling Machine Operator's Certification:	
Well sealed from land surface toft.	This well was constructed under my direct supervi	
Diameter of well bore to bottom of sealin.	Materials used and information reported above are true to best knowledge and belief.	o my
Diameter of well bore below seal	[Signed] January Date 11/27/, 1	19. 78
Number of sacks of cement used in well sealsacks	Drilling Machine Operator's License No. 1009	
How was cement grout placed? Pumped From Bottom Up to Top Land Surface	Drining Machine Operator's License No.	
	Water Well Contractor's Certification:	
· · · · · · · · · · · · · · · · · · ·	This well was drilled under my jurisdiction and this rep- true to the best of my knowledge and belief.	ort is
Was a drive shoe used? 🕱 Yes 🗌 No Plugs Size: location ft.	Name Carter's Drilling & Pump Service	
Did any strata contain unusable water? 🗌 Yes 🐔 No	(Person, firm or corporation) (Type or print)	
Type of water? depth of strata	Address P.O. Box 16-Springfield, Oregon 9747	1
Method of sealing strata off	[Signed] (ames of arke)	
Was well gravel packed? Yes Y No Size of gravel:	(Water Well Contractor)	
Gravel placed from ft. to ft.	Contractor's License No. 126 Date 11/27/	1978