## WATER WELL REPORT STATE OF OREGON

RECEIVED LANE
SEP 16 1981 973 L

State Well No. 65	15E-20bb
-------------------	----------

State Permit No.

WATER RESOURCES DEPT SALEM, OREGON

State Well No. 165 5	-9099
----------------------	-------

(1) OWNER:	(10) LOCATION OF WELL:
Name ROB ROBERTSON (VIN WRIGHT)	County LANE Driller's well number
Address 794 CREST DIRIVE	NW 4 NW 4 Section 20 T. 165 R. 5E W.M.
City EUGENE State OR	Tax Lot # Lot Blk Subdivision
(2) TYPE OF WORK (check):	Address at well location: HOLIDAY FARM
New Well	BLUE KIVER OR.
If abandonment, describe material and procedure in Item 12.	(11) WATER LEVEL: Completed well.
(3) TYPE OF WELL: (4) PROPOSED USE (check):	Depth at which water was first found 12 ft.
Paterns Air Mr. Driver B. D. et al.	Static level ft. below land surface. Date 11 SEP7
Rotary Air Driven Domestic Mandatrial Municipal Rotary Mud Dug Dug Totary Mud Dug Totary Mud Dug Totary Mud Dug	Artesian pressure lbs. per square inch. Date
☐ Bored ☐ Thermal: Withdrawal ☐ Reinjection ☐	(12) WELL LOG: Diameter of well below casing
(5) CASING INSTALLED: Steel Mr Plastic	Depth drilled 4 ft. Depth of completed well 40 ft.
Threadel D William	Formation: Describe color, texture, grain size and structure of materials; and show
6" Diam. from +1/2. ft. to .39ft. Gauge	thickness and nature of each stratum and aquifer penetrated, with at least one entry for each change of formation. Report each change in position of Static Water Level
"Diam. from	and indicate principal water-bearing strata.
LINER INSTALLED:	MATERIAL From To SWL
	FOREST SOIL, GRAVEL, BOULDERS 0 2 -
(6) PERFORATIONS: Perforated?   Yes No	SANDY GRAVEL, BUILDERS 2 17 -
Type of perforator used	SAND & GRAVEL IN CLAY 17 35 9
Size of perforations in. by in.	SMALL GRAVEL IN BLACK SAND 35 41 9
ft. to ft.	
perforations from ft. to ft.	
perforations from ft. to ft.	
(7) SCREENS: Well screen installed?   Yes Man	
Manufacturer's Name	
Type Model No.	
Diam. Slot Size Set from ft. to ft.	
Diam Slot Size Set from ft. to ft.	
(8) WELL TESTS: Drawdown is amount water level is lowered below static level	
We a pump test made? ☐ Yes ເNo If yes, by whom?	
d: gal/min. with ft, drawdown after brs.	
<i>n</i> , , , , , , , , , , , , , , , , , , ,	
Air test 50 gal./min. with drill stem at 4 ft. hrs.	
Bailer test gal./min. with ft. drawdown after hrs.	
Amesian flow g.p.m.	
Depth artesian flow encountered ft.	Work started 10 SEPT 1981 Completed 14 SEPT 1981
(9) CONSTRUCTION: Special standards: Yes \( \text{No} \) No \( \text{No} \)	Work started 5EPT 19 8 Completed 4 SEPT 19 8 Date well drilling machine moved off of well 16 SEPT 19 8
Well seal—Material used CEMENT + 5% BENTONITE	Drilling Machine Operator's Certification:
Well sealed from land surface to	This well was constructed under my direct supervision. Materials used
Diameter of well bore to bottom of sealin.	and information reparted above are true on y best knowledge and belief.
Diameter of well bore below sealin.	[Signed] Walles
Number of sacks of cement used in well seal sacks	Drilling Machine Operator's License No
How was cement grout placed? PRESSVIRE GROUT	
**************************************	Water Well Contractor's Certification:
Was pump installed?	This well was drilled under my jurisdiction and this report is true to the best of my knowledge and belief.
	Name W. N. WHITE, DRILLING
Was a drive shoe used?	(Person, firm or corporation) (Type or print)
Type of Water? depth of strata	Address 91769 PRAIRIE 13D Junction City
Method of sealing strata off	[Signed] Walles 7/ While
Was well gravel packed? ☐ Yes KNo Size of gravel:	Contractor's License No. 6.3.8. Date 15.5021. , 19.81.
ravel placed from ft. to ft.	Contractor's License No. D. D. Date