NOTICE TO WATER WELL CONTRACTOR
The original and first copy of this report are to be filed with the
WATER RESOURCES DEPARTMENT, SALEM, OREGON 97310 within 30 days from the date of well completion.

WATER WELL REPORT
STATE OF OREGON
(Please type or print)
(Do not write above this line)

LANE
9795

State Well No. 16S/8E-16
State Permit No.

(1) OWNER:
Name Willamette National Forest
Address P.O. Box 10607
Eugene, Oregon

(2) TYPE OF WORK (check):
New Well ☑ Deepening ☐ Reconditioning ☐ Abandon ☐
If abandonment, describe material and procedure in Item 12.

(3) TYPE OF WELL:
Rotary ☑ Driven ☐
[redacted] ☐ Jetted ☐
Dug ☐ Bored ☐

(4) PROPOSED USE (check):
Domestic ☑ Industrial ☐ Municipal ☐
Irrigation ☐ Test Well ☐ Other ☐

(5) CASING INSTALLED: Threaded ☐ Welded ☑
6" Diam. from +2 ft. to 150 ft. Gage .250
[redacted]" Diam. from ft. to ft. Gage
" Diam. from ft. to ft. Gage

(6) PERFORATIONS: Perforated? ☑ Yes ☐ No.
Type of perforator used MILLS KNIFE
Size of perforations 1/4 in. by 3 in.
15 perforations from 140 ft. to 145 ft.
perforations from ft. to ft.
perforations from ft. to ft.

(7) SCREENS: Well screen installed? ☐ Yes ☑ No
Manufacturer's Name
Type Model No.
Diam. Slot size Set from ft. to ft.
Diam. Slot size Set from ft. to ft.

(8) WELL TESTS: Drawdown is amount water level is lowered below static level
[redacted] a pump test made? ☑ Yes ☐ No If yes, by whom? M-H Well Drilling
Yield: 40 gal./min. with 10 ft. drawdown after 7 hrs.
" " " "
" " " "
[redacted]er test gal./min. with ft. drawdown after hrs.
Artesian flow g.p.m.
Temperature of water 47 Depth artesian flow encountered ft.

(9) CONSTRUCTION:
Well seal—Material used Cement Grout
Well sealed from land surface to 25 ft.
Diameter of well bore to bottom of seal 10 in.
Diameter of well bore below seal 6 in.
Number of sacks of cement used in well seal 52 sacks
How was cement grout placed? Pressure grouted

Was a drive shoe used? ☒ Yes ☐ No Plugs Size: location ft.
Did any strata contain unusable water? ☐ Yes ☒ No
Type of water? depth of strata
Method of sealing strata off
Was well gravel packed? ☐ Yes ☒ No Size of gravel:
Gravel placed from ft. to ft.

(10) LOCATION OF WELL:
County Lane Driller's well number 980
¼ ¼ Section 16 T. 16S R. 8E W.M.
Bearing and distance from section or subdivision corner
McKenzie Bridge Airport

(11) WATER LEVEL: Completed well.
Depth at which water was first found 38 ft.
Static level 42 ft. below land surface. Date 5/9/80
Artesian pressure lbs. per square inch. Date

(12) WELL LOG: Diameter of well below casing Six
Depth drilled 148 ft. Depth of completed well 148 ft.
Formation: Describe color, texture, grain size and structure of materials; and show thickness and nature of each stratum and aquifer penetrated, with at least one entry for each change of formation. Report each change in position of Static Water Level and indicate principal water-bearing strata.

MATERIAL	From	To	SWL
Soil	0	3	
Clay, brown silt	3	8	
Boulders, gravel med	8	38	
Gravel, med	38	41	
Gravel, med, sand	41	140	
Gravel, med	140	148	42

RECEIVED
MAY 29 1980
WATER RESOURCES DEPT
SALEM, OREGON

Work started April 21 1980 Completed May 9 1980
Date well drilling machine moved off of well May 9 1980

Drilling Machine Operator's Certification:
This well was constructed under my direct supervision. Materials used and information reported above are true to my best knowledge and belief.
[Signed] Leroy W. Mutschler Date 5/26, 1980
(Drilling Machine Operator)
Drilling Machine Operator's License No. 80

Water Well Contractor's Certification:
This well was drilled under my jurisdiction and this report is true to the best of my knowledge and belief.
Name M-H Well Drilling Inc.
(Person, firm or corporation) (Type or print)
Address 4051 N.E. Holly Acres Cor. Ore
[Signed] Leroy W. Mutschler
(Water Well Contractor)
Contractor's License No. 237 Date May 26, 1980

(USE ADDITIONAL SHEETS IF NECESSARY)

SP*45656-119