NOTICE TO WATER WELL CONTRACTOR
The original and first copy of this report are to be filed with the
STATE ENGINEER, SALEM, OREGON 97310
within 30 days from the date of well completion.

LMW

LINC 1231

WATER WELL REPORT
STATE OF OREGON
(Please type or print)
(Do not write above this line)

RECEIVED DEC 2 1976 WATER RESOURCES DEPT. SALEM, OREGON

State Well No. 11S/11W-9ab
State Permit No.

(1) OWNER:
Name Mike KASPER
Address P.O. Box 112
Newport, Oregon

(2) TYPE OF WORK (check):
New Well ☑ Deepening ☐ Reconditioning ☐ Abandon ☐
If abandonment, describe material and procedure in Item 12.

(3) TYPE OF WELL:
Rotary ☑ Driven ☐
Cable ☐ Jetted ☐
Dug ☐ Bored ☐

(4) PROPOSED USE (check):
Domestic ☑ Industrial ☐ Municipal ☐
Irrigation ☐ Test Well ☐ Other ☐

CASING INSTALLED: Threaded ☐ Welded ☑
6" Diam. from 0 ft. to 32 ft. Gage 250
4" Diam. from 0 ft. to 155 ft. Gage P.V.C.
" Diam. from ft. to ft. Gage

PERFORATIONS: Perforated? ☑ Yes ☐ No.
Type of perforator used drill
Size of perforations 1/8 in. by 1/8 in.
50 perforations from 75 ft. to 115 ft.
perforations from ft. to ft.
perforations from ft. to ft.

(7) SCREENS: Well screen installed? ☐ Yes ☑ No
Manufacturer's Name
Type Model No.
Diam. Slot size Set from ft. to ft.
Diam. Slot size Set from ft. to ft.

(8) WELL TESTS: Drawdown is amount water level is lowered below static level
Was a pump test made? ☐ Yes ☑ No If yes, by whom?
Yield: gal./min. with ft. drawdown after hrs.
" " " "
" " " "
Bailer test 3 gal./min. with 32 ft. drawdown after 1 hrs.
Artesian flow g.p.m.
Temperature of water Depth artesian flow encountered ft.

(9) CONSTRUCTION:
Well seal—Material used Cement
Well sealed from land surface to 18 ft.
Diameter of well bore to bottom of seal 10 in.
Diameter of well bore below seal 6 in.
Number of sacks of cement used in well seal 4 sacks
Number of sacks of bentonite used in well seal sacks
Brand name of bentonite
Number of pounds of bentonite per 100 gallons of water lbs./100 gals.
Was a drive shoe used? ☐ Yes ☑ No Plugs Size: location ft.
Did any strata contain unusable water? ☐ Yes ☑ No
Type of water? depth of strata
Method of sealing strata off
Was well gravel packed? ☐ Yes ☑ No Size of gravel:
Gravel placed from ft. to ft.

(10) LOCATION OF WELL:
County Lincoln Driller's well number
NW ¼ NE ¼ Section 9 T. 11S R. 11 W.M.
Bearing and distance from section or subdivision corner

(11) WATER LEVEL: Completed well.
Depth at which water was first found 90 ft.
Static level 60 ft. below land surface. Date 11/3/76
Artesian pressure lbs. per square inch. Date

(12) WELL LOG: Diameter of well below casing Six
Depth drilled 155 ft. Depth of completed well 155 ft.
Formation: Describe color, texture, grain size and structure of materials; and show thickness and nature of each stratum and aquifer penetrated, with at least one entry for each change of formation. *Report each change in position of Static Water Level and indicate principal water-bearing strata.*

MATERIAL	From	To	SWL
Soil	0	2	
Clay. yellow	2	16	
Clay, grey	16	32	
Claystone, grey	32	90	
Claystone, grey, hard broken water stratum	90	92	60
Claystone, grey	92	155	

Work started Nov 3 1976 Completed Nov 3 1976
Date well drilling machine moved off of well Nov 3 1976

Drilling Machine Operator's Certification:
This well was constructed under my direct supervision. Materials used and information reported above are true to my best knowledge and belief.
[Signed] Leroy W Mutschler (Drilling Machine Operator) Date 11/12, 1976
Drilling Machine Operator's License No. 80

Water Well Contractor's Certification:
This well was drilled under my jurisdiction and this report is true to the best of my knowledge and belief.
Name Mutschler Well Drilling (Person, firm or corporation) (Type or print)
Address 2555 N.W. Oak Creek Dr. Corv. Ore
[Signed] Leroy W Mutschler (Water Well Contractor)
Contractor's License No. 237 Date Nov 12, 1976

(USE ADDITIONAL SHEETS IF NECESSARY)

SP*45656-119