NOTILE TO WATER WELL CONTRACTOR
The original and first copy of this report are to be filed with the

STATE ENGINEER, SALEM, OREGON 9730 N 1 1 5 3 (Please type of print)

(Please type of print)

STATE ENGINEER, SALEM, OREGON 97310 (within 30 days from the date of well completion.

(Please type or print) TE ENGINEER Permit No.

(Do not write above this line) EM QREGON

(1) OWNER:	(10) LOCATION OF WELL:			
Name FRLING GRIMSTAD	County LINCOLN Driller's well number			
Address Room 2 Dodd Bld	½ ¼ Section 32 т.13s	R. 10w W.M.		
Newport, Oregon	Bearing and distance from section or subdivisi	on corner		
(2) TYPE OF WORK (check):				
New Well ☐ Deepening ☐ Reconditioning ☐ Abandon ☐	.2			
III abandonment, describe material and procedure in Item 12.	(11) WATER LEVEL: Completed w	ell.		
(3) TYPE OF WELL: (4) PROPOSED USE (check):	Depth at which water was first found	58 _{ft.}		
Rotary Driven Domestic IX Industrial Municipal	40	(10/07		
Cable		surface. Date 6/1/13		
Bolett B. Milgation B Test Well B Guiter	Artesian pressurelbs. per squar	e inch. Date		
(5) CASING INSTALLED: Threaded □ Welded ☑	(12) WELL LOG: Diameter of well to	halaw anging 6"		
6 "Diam. from 0 ft. to 100 ft. Gage 250	105			
ft. Gage				
" Diam. from ft. to ft, Gage	Formation: Describe color, texture, grain size a and show thickness and nature of each strature.			
(A) DEDECORATEVONO	with at least one entry for each change of forma	tion. Report each change in		
(6) PERFORATIONS: Perforated? X Yes - 1-No.	position of Static Water Level and indicate prin	cipal water-bearing strata.		
Type of perforator used torch	MATERIAL	From To SWL		
Size of perforations 1/8 in. by 8 in.	tan sandy clay	0' 1'		
80 perforations from 58 ft. to 98 ft.	broken sandstone	1 13		
perforations from ft. toft.	brown clay	13 24		
perforations from ft. to ft.	bolders	24 27		
(m) Comments	blue sticky clay	27 43		
(7) SCREENS: Well screen installed? Yes No	brown sandy clay@silty)	43 58		
Manufacturer's Name	brown & gray sandstone	52 87		
Type Model No.	gray sandstone	87 105		
Diam. Slot size Set from ft. to ft.				
Diam Slot size Set from ft. to ft.				
(8) WELL TESTS: Drawdown is amount water level is				
lowered below static level				
Was a pump test made? Yes No If yes, by whom?				
gal./min. with ft. drawdown after hrs.	The transfer was the same to the same that the same to the same that the			
" " "				
tested with air; estmate could fluctuate "		-		
Parity test 75 gal./min. with 57ft. drawdown after 1 hrs.				
sian flow g.p.m.				
Temperature of water Depth artesian flow encountered		16/17/177		
Temperature of water Deput attestan now encountered	Work started 6/6/73 19 Complete	(17/77		
(9) CONSTRUCTION:	Date well drilling machine moved off of well	6/ 1/ 15 19		
Well seal-Material used cement grout	Drilling Machine Operator's Certification:			
Well sealed from land surface toft.	This well was constructed under my	direct supervision.		
Diameter of well bore to bottom of sealin.	Materials used and information reported best knowledge and belief.	above are true to my		
Diameter of well bore below seal	resigned Robert W. Clanson	Tota 6/15/73 10		
Number of sacks of cement used in well seal9_ sacks	(Drilling Machine Operator)			
Number of sacks of bentonite used in well sealsacks	Drilling Machine Operator's License No.	658		
Brand name of bentonite		•		
Number of pounds of bentonite per 100 gallons	Water Well Contractor's Certification:			
of waterlbs./100 gals.	This well was drilled under my jurisdi			
Was a drive shoe used? Yes No Plugs Size: location ft.	true to the best of my knowledge and bel	CO INC		
Did any strata contain unusable water? Yes No	I Name			
Type of water? depth of strata	(Person, firm or corporation) 3440 sw 3rd; Corval	lis, Oregon		
Method of sealing strata off	I was	<i>A</i>		
Was well gravel packed? Yes No Size of gravel: pes	[Signed] Marche (Water Well Contr	'states		
Gravel placed from 54 tt. to 98 tt.	Contractor's License No560 Date 6/	/		
The second secon	Contractor a Difference No. 1300 Date 104	-45445		

NOT IT TO WATER WELL CONTRACTOR
The original and first copy of this report are to be filed with the

STATE OF OREGON JUN 261973 State Well No. 35/10W-32

(Please type or GNT) ATE ENGINE TO Permit No.

(Do not write above this PALEM 25 EON

STATE ENGINEER, SALEM, OREGON 9731 within 30 days from the date of well completion.

(1) OWNER:	(10) LOCATION OF WELL:			
Name ERLING CRIMSTAD -	County LINCOLN Driller's well number			
Address Room 2 Dodd Blvd	14 14 Section 32 T. 138	R. 101	W.	W.M.
Newport, Oregon	Bearing and distance from section or subdivisi	on corne	r	
(2) TYPE OF WORK (check)				-
New Well ☐ Deepening ☐ Reconditioning ☐ Abandon ☐				
If abandonment, describe material and procedure in Item 12.	(11) WATER LEVEL: Completed w	 		
(3) TYPE OF WELL: (4) PROPOSED USE (check):		58		
Potony FBr Duivon IT	Depth at which water was first found	<u> </u>	···	<u>ft.</u>
Cable Jetted Domestic 2 Industrial Municipal	Static level 48 ft. below land a	urface.	Date 6/	7/73_
□ Bored □ □ Irrigation □ Test Well □ Other □	Artesian pressure lbs. per squar	e inch.	Date	
CASING INSTALLED: Threaded Welded	(19) WEIT LOC.			6"
6 " Diam. from 0 ft. to 100 ft. Gage 250	(12) WELL LOG: Diameter of well below casing			
"Diam. from ft. to ft. Gage	Depth drilled 105 ft. Depth of completed well 105 ft.			
"Diam. fromft. toft. Gage	Formation: Describe color, texture, grain size and structure of materials; and show thickness and nature of each stratum and aquifer penetrated, with at least one entry for each change of formation. Report each change in			
PERFORATIONS: Perforated? Yes No.	position of Static Water Level and indicate prin	cipal wat	ter-beari	ng strata.
Type of perforator used torch	MATERIAL	From	То	swL
Size of perforations 1/8 in. by 8 in.	tan sandy clay	0'	71	
80 perforations from 58 ft. to 98 ft.	broken sandstone	1	13	
perforations fromft. toft.	brown clay	13	24	
perforations fromft. toft.	bolders	24	27	
			43 52	
(7) SCREENS: Well screen installed? Yes No	blue sticky clay brown sandy silty clay	43	52	
Manufacturer's Name	brown & gray sandstone	52	87	
Type Model No	gray sandstone	87	105	
Diam. Slot size Set from ft. to ft.				
Diam Slot size Set from ft. to ft.				
(O) YYYYY T PRYSCHIC Providence is amount wroten level in				
(8) WELL TESTS: Drawdown is amount water level is lowered below static level				
Was a pump test made? ☐ Yes ♣ No If yes, by whom?				
l: gal./min. with ft. drawdown after hrs.				
n was a second of the second o				
" tested with air; estimate could fluctuate "				
ZEALER test 75 gal./min. with 57 ft. drawdown after 1 hrs.				
sian flow g.p.m.			<u> </u>	
perature of water Depth artesian flow encountered ft.	Work started 6/6/73 19 Complet	_{ed} 6/7/	73	19
(9) CONSTRUCTION:	Date well drilling machine moved off of well	6/7/	73	19
Well seal—Material used cement grout	Drilling Machine Operator's Certification:			
Well sealed from land surface to 98 tt.	This well was constructed under my			
Diameter of well bore to bottom of seal 10 in.	Materials used and information reported best knowledge and belief.	above	are uu	e to my
Diameter of well bore below seal	[Signed] Robert W. Claassen	Date 6/	15/73	.19
Number of sacks of cement used in well seal9sacks	(Drilling Machine Operator)			
Number of sacks of bentonite used in well sealsacks	Drilling Machine Operator's License No.	658		
Brand name of bentonite				
Number of pounds of bentonite per 100 gallons	Water Well Contractor's Certification:			•
of water lbs./100 gals.	This well was drilled under my jurisd		nd this	report is
Was a drive shoe used? ★ Yes No Plugs Size: location ft.	true to the best of my knowledge and be CORVALLIS DRILLING CO) INC		
Did any strata contain unusable water? ☐ Yes 🔁 No	Name		ype or pr	int)
Type of water? depth of strata	(Person, firm or corporation) 3440 sw 3rd; Corvall:	Ls, Or	egon	
Method of sealing strata off	[Signed] Lefslene A Kinge (Water Well Cont	ractor)		***************************************
Was well gravel packed? N Yes No Size of gravel: PEA	}	ractor) 6_15_7	77	10

The enclosed well log is a log milioshy submitted. STATE ENGINEER SALEM OREGON