

NOTICE TO WATER WELL CONTRACTOR
The original and first copy
of this report are to be
filed with the

STATE ENGINEER, SALEM, OREGON 97310
within 30 days from the date
of well completion.

WATER WELL REPORT

STATE OF OREGON

(Please type or print)

DEC 31 1976

State Well No.

13-11W-9CA

Permit No.

SALEM, OREGON

(1) OWNER:

Name Pete Yoncich
Address 12831 MALINA DR
SANTA ANA, CALIFORNIA 92705

(2) TYPE OF WORK (check):

New Well ☒ Deepening ☐ Reconditioning ☐ Abandon ☒
If abandonment, describe material and procedure in Item 12.

(3) TYPE OF WELL:

Rotary ☒ Driven ☐
Cable ☐ Jetted ☐
Dug ☐ Bored ☐

(4) PROPOSED USE (check):

Domestic ☒ Industrial ☐ Municipal ☐
Irrigation ☐ Test Well ☐ Other ☐

CASING INSTALLED:

Threaded ☐ Welded ☐

NO P.E. " Diam. from ft. to ft. Gage
" Diam. from ft. to ft. Gage
" Diam. from ft. to ft. Gage

PERFORATIONS:

Perforated? ☐ Yes ☒ No.

Type of perforator used

Size of perforations in. by in.
..... perforations from ft. to ft.
..... perforations from ft. to ft.
..... perforations from ft. to ft.

(7) SCREENS:

Well screen installed? ☐ Yes ☒ No

Manufacturer's Name
Type Model No.
Diam. Slot size Set from ft. to ft.
Diam. Slot size Set from ft. to ft.

(8) WELL TESTS:

Drawdown is amount water level is
lowered below static level

Was a pump test made? ☐ Yes ☒ No If yes, by whom?

Yield: gal./min. with ft. drawdown after hrs.
" " " "
" " " "

Bailer test 0 gal./min. with 0 ft. drawdown after 0 hrs.

Artesian flow g.p.m.

Temperature of water Depth artesian flow encountered ft.

(9) CONSTRUCTION:

Well seal—Material used Abandon

Well sealed from land surface to ft.

Diameter of well bore to bottom of seal in.

Diameter of well bore below seal in.

Number of sacks of cement used in well seal sacks

Number of sacks of bentonite used in well seal sacks

Brand name of bentonite

Number of pounds of bentonite per 100 gallons

of water lbs./100 gals.

Was a drive shoe used? ☐ Yes ☐ No Plugs Size: location ft.

Did any strata contain unusable water? ☐ Yes ☐ No

Type of water? depth of strata

Method of sealing strata off

Was well gravel packed? ☐ Yes ☐ No Size of gravel:

Gravel placed from ft. to ft.

(10) LOCATION OF WELL:

County LINCOLN Driller's well number
NE 1/4 SW 1/4 Section 9 T.13S R. 11 W.M.

Bearing and distance from section or subdivision corner

(11) WATER LEVEL: Completed well.

Depth at which water was first found NONE ft.

Static level NONE ft. below land surface. Date 10/29/76

Artesian pressure lbs. per square inch. Date

(12) WELL LOG:

Diameter of well below casing 5 1/2

Depth drilled 215 ft. Depth of completed well 215 ft.

Formation: Describe color, texture, grain size and structure of materials;
and show thickness and nature of each stratum and aquifer penetrated,
with at least one entry for each change of formation. Report each change in
position of Static Water Level and indicate principal water-bearing strata.

MATERIAL	From	To	SWL
CLAY, yellow	0	7	
CLAY, red	7	32	
CLAYSTONE, grey	32	120	
" blue	120	125	
" brown	125	180	
SANDSTONE, hard, blue	180	188	
CLAYSTONE, grey	188	215	
ABANDON: BACKFILLED w/ CLAY & Cement			

Work started OCT 29 1976 Completed OCT 29 1976

Date well drilling machine moved off of well OCT 29 1976

Drilling Machine Operator's Certification:

This well was constructed under my direct supervision.
Materials used and information reported above are true to my
best knowledge and belief.

[Signed] Froy W. Mutschler Date 11/11, 1976
(Drilling Machine Operator)

Drilling Machine Operator's License No. 80

Water Well Contractor's Certification:

This well was drilled under my jurisdiction and this report is
true to the best of my knowledge and belief.

Name Mutschler Well Drilling
(Person, firm or corporation) (Type or print)

Address 7555 NW OAK Creek Dr. Gresham, Ore

[Signed] Froy W. Mutschler
(Water Well Contractor)

Contractor's License No. 237 Date Nov 11, 1976