NOTICE TO WATER WELL CONTRACTOR The original and first copy of this report are to be filed with the

Size of gravel:

Method of sealing strata off

Was well gravel packed? ☐ YesXXNo

Gravel placed from ...... ft. to ......

LINC				1	35	1/	-21	)
A TAIC	State	Well	No.	!	ارر	$\mathbb{L}(\mathcal{L})$	<i>(</i> \	<i>I</i>
	/			- 1		(		•
7.	State					•		

are to be filed with the WATE	ER WELL REPORT
SALEM, OREGON 97310 within 30 days from the date  (I	ATE OF OREGON Please type or print) State Well No. 35 16 2 2
(1) OWNER:	(10) LOCATION OF WELL:
Name Oakland's Fish Camp	County Lincoln Driller's well number
Address 4000 Hwy 34	14 14 Section 27 T. 138 R. 11W W.M.
Waldport, Or.	Bearing and distance from section or subdivision corner
(2) TYPE OF WORK (check):	
	ıdon 🗆 🔝
If abandonment, describe material and procedure in Item 12.	(11) WATER LEVEL: Completed well.
(3) TYPE OF WELL: (4) PROPOSED USE (ch	neck): Depth at which water was first found 785 ft.
Rotary XX Driven Domestic KIX Industrial Mur	nicipal  Static level 32 ft. below land surface. Date 10/23/79
C Jetted   Irrigation   Test Well   Other	, , , , ,
(5) CASING INSTALLED: Threaded □ Welder	(12) WELL LOG: Diameter of well below casing
6	250 Depth drilled 205 ft. Depth of completed well 205 ft.
" Diam. from ft. to ft. Gage	Formation: Describe color, texture, grain size and structure of materials:
" Diam. from ft. to ft. Gage	and show thickness and nature of each stratum and aquifer penetrated,
(6) PERFORATIONS: Perforated? ☐ Yes ☐	with at least one entry for each change of formation. Report each change in position of Static Water Level and indicate principal water-bearing strata.
(6) PERFORATIONS: Perforated? ☐ Yes →	MATERIAL From To SWL
<u></u>	
perforations from	0 40
perforations from ft. to	12 1
perforations from ft. to	brown sand & gravel 14 15
(7) SCREENS: Well screen installed?   Yes   No.	
Manufacturer's Name	
Type Model No	
Diam Slot size Set from ft. to	
Diam. Slot size Set from ft. to	gray broken claystome
(8) WELL TESTS: Drawdown is amount water leve	baring 9 gpm 175 205
lowered below static level	
	W.S. L. C.
Yield: 9 gal./min. with \$50 ft. drawdown after	2 hrs. NOV 1 1979
" "	WATER RESOURCES DEPT
" "	SALEM, ORLGUN
Beier test gal./min. with ft. drawdown after	hrs.
Artesian flow g.p.m.	
Temperature of water 5] Depth artesian flow encountered	
	10/22/ 70
(9) CONSTRUCTION:	Date well drilling machine moved off of well 10/23/ 1917
Well seal—Material used Cement	Drilling Machine Operator's Certification:
Well sealed from land surface to 18	This well was constructed under my direct supervision.  Materials used and information reported above are true to my
Diameter of Well bore to bottom of seal	best knowledge and belief,
Diameter of well bore below seal	[Signed] (Drilling Machine Operator) Date11/12/, 1979.
Number of sacks of cement used in well seal	Drilling Machine Operator's License No. 503
How was cement grout placed? pressure	Dritting Machine Operator's License No.
The state of the s	Water Well Contractor's Certification:
The state of the s	This well was drilled under my jurisdiction and this report is
Was a drive shoe used? ☐ Yes 🗷 No Plugs Size: location	true to the best of my knowledge and belief.
Did any strata contain unusable water?   Yes You	Name Ray mond C. Gellatly & Ronald S. Witham (Person, firm or corporation) (Type or print)
Type of water? depth of strata	Address Philomath, Or. P.O. Box 1
depth of strata	A A COUR COST - 1/2- September Color