NOTICE TO WATER WELL CONTRACTOR

of well completion.

The original and first copy of this report are to be filed with the WATER RESOURCES DEPARTMENT, SALEM, OREGON 97310 WATER WELL REPORT CE VE STATE OF OREGON SEP 2 9 1978 State Well No. 65/10w-25 (Please type or print) SEP 2 9 1978

 		1
1/2		· \
13	115	1
14		1
10		b

(Do not write above the WHER RESOURCES DEPT.

(1) OWNER:	(10) LOCATION OF WELL:		
Name Lawrence Durette	County Lincoln Driller's well nur	nber Cy/67/A	
Address Rt.1 Box 59	25 69	10W W.M.	
Otis, Oregon 97368	Bearing and distance from section or subdivision		
(2) TYPE OF WORK (check):		200	
New Well ☐ Deepening ☐ Reconditioning ☐ Abandon ☐			
If abandonment, describe material and procedure in Item 12.	(11) WATER LEVEL: Completed we	II.	
(3) TYPE OF WELL: (4) PROPOSED USE (check):	Depth at which water was first found	90 ft.	
Rotary 🖟 Driven 🗆 Domestic 🛣 Industrial 🗆 Municipal 🗆	Static level 26 ft. below land su	rface. Date 9/1/78	
Dug ☐ Bored ☐ Irrigation ☐ Test Well ☐ Other ☐	Artesian pressure lbs. per square		
CASING INSTALLED: Threaded Welded 250 Moreover Diam. from ft. to ft. Gage 250 "Diam. from ft. to ft. Gage Ft.	(12) WELL LOG: Diameter of well be Depth drilled 160 ft. Depth of complete Formation: Describe color, texture, grain size an and show thickness and nature of each stratum with at least one entry for each change of formatic position of Static Water Level and indicate principal contents.	ed well 160 ft. d structure of materials; and aquifer penetrated, n. Report each change in	
Type of perforator used	MATERIAL	From To SWL	
Size of perforations in. by in.	Redish brown clay soil	0 4	
perforations fromft. toft.	Brown clay	4 14	
perforations fromft. toft.	River gravel&boulders Brown sandstone	14 23	
perforations from ft. to ft.		23 42	
(7) SCREENS: Well screen installed? Yes X No	Blue sandstone & quartz	42 74	
Manufacturer's Name	Blue basalt	74 86 86 160	
Type		00 100	
Diam. Slot size Set from ft. to ft.			
(8) WELL TESTS: Drawdown is amount water level is lowered below static level			
Was a pump test made? Yes No If yes, by whom?			
Yield: gal./min. with ft. drawdown after hrs.			
" " " " " " " " " " " " " " " " " " " "			
" Tested with air: could fluctuate "			
REMER test 20 gal./min. with /25 ft. drawdown after 4 hrs.	* * * * * * * * * * * * * * * * * * *		
Artesian flow g.p.m.			
perature of water Depth artesian flow encounteredft.	Work started 9/1/78 19 Completed	0/0/=0 10	
		9/2/78 19	
(9) CONSTRUCTION:	Date well drilling machine moved off of well	9/2/78 19	
Well seal—Material used Cement Well sealed from land surface to 46 ft. Diameter of well bore to bottom of seal 10 in. Diameter of well bore below seal 6 in. Number of sacks of cement used in well seal 8 sacks How was cement grout placed? Mixed and poured from top	Drilling Machine Operator's License No	oove are true to my ate	
A Real Property of the Control of th	Water Well Contractor's Certification:	y growing one made .	
	true to the best of my knowledge and helief		
Was a drive shoe used? LyYes No Plugs Size: location ft.	Name Corvallis Drilling Co. Inc	•	
Did any strata contain unusable water? Yes V No	(Person, firm or corporation)	(Type or print)	
Type of water? depth of strata	Address 3440 SW 3rd St. Corvallis	Oregon 97330	
Method of sealing strata off	[Signed] Columnic H Kin	xu y	
Was well gravel packed? Tyes No Size of gravel:	(Water Well Contract	or)	
Fravel placed from ft. to ft.	Contractor's License No. 560 Date	Q/5/78 10	