NOTICE TO WATER WELL CONTRACTOR
The original and first copy
of this report are to be filed with the

Gravel placed from 19 ft. to 24

## STATE OF OREGON 10 19 196 Please type or print) (Po not write above this line)

STATE ENGINEER, SALEM, OREGON 973102 within 30 days from the date



of well completion. STATE ENGINEER	G-407/		
1) OWNER:	(11) LOCATION OF WELL:		
tame Lawrence A. and Betty Du Rette, and	County Lincoln Driller's well nur	<sub>mber</sub> #300	
Address F. Ralph and Evelyn G. Du Rette, Rte. 1	, box 4 Section 33 T. 65.	R 10W WM	
hox 59.0tis.Oregon 97368	Bearing and distance from section or subdivision		
2) TYPE OF WORK (check):	1216.69 feet South and 12.	15.62 feet East	
Yew Well □ Deepening □ Reconditioning □ Abandon □	of the Northwest corner of		
f abandonment, describe material and procedure in Item 12.	of section 33, T6S., R10W		
(3) TYPE OF WELL: (4) PROPOSED USE (check):		8 inch -	
Rotary   Driven	(12) WELL LOG: Diameter of well be	elow casing	
Dable	Depth drilled 165 ft. Depth of comple	ted well 161 ft.	
CASING INSTALLED: Threaded Welded 3.  8. "Diam. from 1 ft. to 85\frac{1}{5} ft. Gage* 258	Formation: Describe color, texture, grain size and structure of materials; and show thickness and nature of each stratum and aquifer penetrated, with at least one entry for each change of formation. Report each change in position of Static Water Level as drilling proceeds. Note drilling rates.		
"Diam from 3bove ft. to ft. Gage ft. Gage			
" Diam. from Surf: ft. to ft. Gage	MATERIAL	From To SWL	
Diani, Hulli management It. Wage	brown clay	12 30	
PERFORATIONS: Perforated?  Yes  No.	crey clay and rock mixed	30 -	
Type of perforator used	(clayhard)	30 -36	
Size of perforations in. by in.	grey hard shale and rock		
perforations fromft. toft.	mixed	<u>36 61 60</u>	
perforations from ft. to ft.	grey hard shale and rock		
perforations fromft. toft.	mixed #	61. 132 130	
perforations fromft. toft.	grey shale	132 161 155	
perforations fromft. toft.	20,7 5110,10	2 ) 2 2 2 7 2	
(E) CONTINUE	-		
(7) SCREENS: Well screen installed? ☐ Yes ☐ No			
Manufacturer's Name			
Type Model No Diam Slot size Set from ft. to ft.			
Diam. Slot size Set from ft. to ft.			
Diain. Slot size Set from It. to It.		·	
(8) WATER LEVEL: Completed well.			
Static level 8 2/3 ft. below land surface Date 5/25/67			
ian pressure lbs. per square inch Date			
(9) WELL TESTS: Drawdown is amount water level is			
lowered below static level			
Was a pump test made? ☐Yes ☐ No If yes, by whom? ☐T1110T	Work started 5/19 1967 Complete	ed 6/1 - 1967-	
Yield: 26 gal./min. with 116 ft. drawdown after 3 hrs.		6/1 1967	
<u> </u>	Date well drilling machine moved off of well	19 ,	
" " " "	Drilling Machine Operator's Certification:		
Bailer test gal./min. with ft. drawdown after hrs.	This well was constructed under my dir rials used and information reported abov	rect supervision. Mate-	
Artesian flow g.p.m. Date	knowledge and belief.	e are wide to my best	
Temperature of water Was a chemical analysis made?  Yes No	[Signed Clark aushaw	Date 7/17 , 19 67	
Temperature of water was a chemical analysis made: 1 res 13.40	(Drilling Machine Operator)	·	
(10) CONSTRUCTION:	Drilling Machine Operator's License No.	163	
Well seal—Material used bentonite			
Depth of sealft.	t. Water Well Contractor's Certification:		
Diameter of well bore to bottom of seal	This well was drilled under my jurisdiction and this report is true to the best of my knowledge and belief.		
Were any loose strata cemented off?  Yes  No Depth			
Was a drive shoe used? ☐ Yes ☐ No	NAMECharies Panschow, Rt. 1, box 102 (Ferson, firm or corporation) (Type or print)		
Did any strata contain unusable water? 🗌 Yes 🛴 No	Address Florence, Oregon 97439		
Type of water? depth of strata	denth of strate		
Method of sealing strata off	[Signed] Matel Pansahow		
Was well gravel packed? - Yes No Size of gravel 171 minus	(Water Well Contrac	tor)	

ft.

Contractor's License No. ...87.... Date 7/17