NOTICE TO WATER WELL CONTRACTOR The original and first copy of this report are to be filed with the

WATER WELL REPORT

(LINC	State	Well	No.

o.	65	/11w	-24

STATE ENGINEER, SALEM, OREGON 97210 within 30 days from the date

(Please type or print) OCT 2 0 1975 write above this line)

State	Well No	. <u>.</u>	5	///	W	-24	/
State	Permit	No.					

(1) OWNER: Name TOM RAY % DALE WALTER RESOURCES DEPT	(10) LOCATION OF WELL:			
Name TOM RAY % DALE WALTER PRESOURCE Address 841 S.W. 65 th St. SALEM, EGREGON	County Lincoln Driller's well number 221			
Address 841 S.W. 65 th St. SALEM.	S. E. 4 N. W.4 Section 24 T. 6 S.R. 11 W. W.M.			
LINCOLN CITY, ORE. 97367	Bearing and distance from section or subdivision			
(2) TYPE OF WORK (check):				
New Well ▼ Deepening □ Reconditioning □ Abandon □				
If abandonment, describe material and procedure in Item 12.	(11) WATER LEVEL: Completed w	ell.		
(3) TYPE OF WELL: (4) PROPOSED USE (check):	Depth at which water was first found 35			
Rotary Driven Domestic L Industrial Municipal	Static level 25 ft. below land s	urface. Date 9/19/75		
Cable	Artesian pressure Ibs. per squar			
	Artesian pressure and per squar	e nicii. Date		
CASING INSTALLED: Threaded □ Welded X	(12) WELL LOG: Diameter of well h	elow casing 6!!		
6" Diam. from + 2 ft. to92 ft. Gage 250	Depth drilled 180 ft. Depth of completed well 180 ft.			
"Diam. from ft. to ft. Gage ft. Corre	Formation: Describe color, texture, grain size a			
ft. toft. Gage	and show thickness and nature of each stratur with at least one entry for each change of format			
PERFORATIONS: Perforated? Yes No.	position of Static Water Level and indicate prin			
Type of perforator used	MATERIAL	From To SWL		
Size of perforations in. by in,	Soil	0 6		
perforations from ft. to ft.	Brown Clay	6 14		
perforations from ft. to ft.	Gray Claystone	14 35		
perforations from ft. to ft.	Brown Claystone	35 65		
(7) SCREENS: Well screen installed? VIV Yes II No.	Black Sandstone	65 85		
Well screen installed? YN Yes I No Manufacturer's Name 4" PVC LIner 0-180"	Gray Claystone	85 100		
Type Model No	Black Sandstone	100 140		
Diam Slot size Set from ft. to ft.	Blue Claystone	140 180		
Diam. Slot size Set from ft. to ft.				
(8) WELL TESTS: Drawdown is amount water level is		-		
lowered below static level	- April			
Was a pump test made? W Yes \(\subseteq \text{No It yes, by whom Garland Cox} \)		-		
Yield: 30 gal./min. with 80 ft. drawdown after 24 hrs.				
" " "	=			
" "	r and in the second sec			
Bailer test gal./min. with ft. drawdown after hrs.				
Artesian flow g.p.m.				
perature of water 58° Depth artesian flow encountered ft.	Work started 9/12 19 75 Complete	ed 10/9 19 75		
(9) CONSTRUCTION:	Date well drilling machine moved off of well	10/9 19 75		
Well seal—Material used Cement Grout	Drilling Machine Operator's Certification:			
Well sealed from land surface to	This well was constructed under my			
Diameter of well bore to bottom of seal	Materials used and information reported best knowledge and belief.	above are true to my		
Diameter of well bore below seal in.	[Signed] alun offunklige!	Date 10/16, 1975		
Number of sacks of cement used in well sealsacks	(Drilling Machine Operator)	652		
Number of sacks of bentonite used in well seal \mathbf{Q} sacks	Drilling Machine Operator's License No.			
Brand name of bentonite	Water Well Contractor's Certification:			
Number of pounds of bentonite per 100 gallons	This well was drilled under my jurisdi	ction and this report is		
of waterlbs./100 gals. Was a drive shoe used? K Yes \(\subseteq \) No Plugs Size: location ft.	true to the best of my knowledge and belief.			
Did any strata contain unusable water? Yes No	NameGUS STORES LOGGING & WELL 1	ORILLING (Type or print)		
Type of water? depth of strata	Address 5555 West 11 b Ave. EUC			
Method of sealing strata off		•		
Was well gravel packed? ★ Yes □ No Size of gravel: 3/4 Pda	[Signed] Alan Water Well Ontr	actor)		
Gravel placed from 32 ft. to 90 ft.	Contractor's License No. 578 Date	10/17 1075		