STATE OF OREGON
WATER SUPPLY WELL REPORT
(as required by ORS 537.545 & 537.765 and OAR 690-205-0210)

LINC 54899
3/16/2026

WELL I.D. LABEL# L 113915
START CARD # 1081316
ORIGINAL LOG #

(1) LAND OWNER

Owner Well I.D.
First Name DION Last Name BLAKE
Company
Address 12319 LOGSDEN RD
City BLODGETT State OR Zip 97326

(2) TYPE OF WORK

[X] New Well [ ] Deepening [ ] Conversion
[ ] Alteration (complete 2a & 10) [ ] Abandonment(complete 5a)

(2a) PRE-ALTERATION

	Dia	+	From	To	Gauge	Stl	Plstc	Wld	Thrd
Casing:									

	Material	From	To	Amt	sacks/lbs
Seal:					

(3) DRILL METHOD

[X] Rotary Air [ ] Rotary Mud [ ] Cable [ ] Auger
[ ] Reverse Rotary [ ] Other

(4) PROPOSED USE

[X] Domestic [ ] Irrigation [ ] Community
[ ] Industrial/ Commercial [ ] Livestock [ ] Dewatering
[ ] Thermal [ ] Injection [ ] Other

(5) BORE HOLE CONSTRUCTION

Special Standard [ ] (Attach copy)
Depth of Completed Well 90.00 ft.

BORE HOLE Dia	From	To	SEAL Material	From	To	Amt	sacks/lbs
10	0	19	Bentonite Chips	0	19	10	S
6	19	90			Calculated	8.67	
					Calculated		

Seal placement method: [ ] A [ ] B [ ] C [ ] D [ ] E [X] Other: BENTONITE CHIPS
Backfill placed from ft. to ft. Material
Filter pack from ft. to ft. Material Size
Explosives used: [ ] Type Amount
Seal Placement Begin Date 3/5/2026 Begin Time 12 00

(5a) ABANDONMENT USING UNHYDRATED BENTONITE

Proposed Amount Actual Amount

(6) CASING/LINER

C/L	Dia	+	From	To	Gauge	Mat. Type	Wld	Thrd	Shoe	Shoe Location
C	6	X	1	19	0.250	ST	X			
L	4	X	0.5	55	Sch40	PL		X		

Temp casing [X] Yes Dia 10 From + [ ] 0 To 19

(7) PERFORATIONS/SCREENS

Perforations Method
Screens Type Pre-Slotted Material PVC Schd 40

Perf/ Screen	Casing/ Liner	Screen Dia	From	To	Scrn/slot width	Slot length	# of slots	Tele/ Pipe size
Screen	Liner	4	55	90	.01	6	118	Pipe Size

(8) WELL TESTS: Minimum testing time is 1 hour

Type of Test	Yield (gal/min)	Drawdown	Drill Stem/ Pump Depth	Duration (hr)
Air	10		85	1

Temperature 53 °F Lab analysis [ ] Yes By
Water quality concerns? [ ] Yes (describe below) TDS amount 300 ppm

From	To	Description	Amount	Units

(9) LOCATION OF WELL (legal description)

County LINCOLN Twp 10.00 S N/S Range 8.00 W E/W WM
Sec 6 NE 1/4 of the SW 1/4 Tax Lot 406
Tax Map Number Lot
Lat ° ' " or 44.72913679 DMS or DD
Long ° ' " or -123.71965724 DMS or DD
(•) Street address of well ( ) Nearest address
12319 LOGSDEN RD, BLODGETT, OR 97326

(10) STATIC WATER LEVEL

	Date	SWL(psi)	+	SWL(ft)
Existing Well / Pre-Alteration				
Completed Well	3/5/2026			8

Flowing Artesian? [ ] Dry Hole? [ ]

WATER BEARING ZONES Depth water was first found 45.00

SWL Date	From	To	Est Flow	SWL(psi)	+	SWL(ft)
3/5/2026	45	90	10			8

(11) WELL LOG

Ground Elevation 252.51 FT

Material	From	To
Top Soil	0	4
Silty Sand w/ some Gravels	4	13
Gray Sandstone	13	90

Construction
Begin Date 3/5/2026 Begin Time 08 00 End Date 3/5/2026

(unbonded) Water Well Constructor Certification

I certify that the work I performed on the construction, deepening, alteration, or abandonment of this well is in compliance with Oregon water supply well construction standards. Materials used and information reported above are true to the best of my knowledge and belief.

License Number Date

Signed

(bonded) Water Well Constructor Certification

I accept responsibility for the construction, deepening, alteration, or abandonment work performed on this well during the construction dates reported above. All work performed during this time is in compliance with Oregon water supply well construction standards. This report is true to the best of my knowledge and belief.

License Number 2108 Date 3/16/2026

Signed DUSTIN HUDDLESTON (E-filed)

Drilling Company: PLI Systems Inc (Dustin Huddleston)

WATER SUPPLY WELL REPORT - continuation page

LINC 54899

3/16/2026

WELL I.D. LABEL# L	113915
START CARD #	1081316
ORIGINAL LOG #	

(2a) PRE-ALTERATION

Dia	+	From	To	Gauge	Stl	Plstc	Wld	Thrd

Material	From	To	Amt	sacks/lbs

(5) BORE HOLE CONSTRUCTION

BORE HOLE

Dia	From	To

SEAL

Material	From	To	Amt	sacks/lbs
		Calculated		
		Calculated		
		Calculated		
		Calculated		

FILTER PACK

From	To	Material	Size

(6) CASING/LINER

C/L	Dia	+	From	To	Gauge	Mat. Type	Wld	Thrd	Shoe	Shoe Location

(7) PERFORATIONS/SCREENS

Perf/ Screen	Casing/ Liner	Screen Dia	From	To	Scrn/slot width	Slot length	# of slots	Tele/ Pipe size

(8) WELL TESTS: Minimum testing time is 1 hour

Type of Test	Yield (gal/min)	Drawdown	Drill Stem/ Pump Depth	Duration (hr)

Water Quality Concerns

From	To	Description	Amount	Units

(10) STATIC WATER LEVEL

SWL Date	From	To	Est Flow	SWL(psi)	+	SWL(ft)

(11) WELL LOG

Material	From	To

Name of person(s) who assisted with construction and Trainee License # / Helper #

Assistant Name	Type	#
STEVEN RIEGER	HELPER MONITORING	8888936
ARMANDO SOTO	MONITORING	10599
RODOLFO VILLAGOMEZ	HELPER MONITORING	8888999

Comments/Remarks

The 6-inch diameter x 20ft steel casing was set 6ft into Sandstone with a poured Bentonite Seal in the 10-inch annulus. A 4-inch diameter liner w/ screen runs 90ft BGS.

WATER SUPPLY WELL REPORT - Map with location identified must be attached and shall include an approximate scale and north arrow

LINC 54899

3/16/2026

Map of Hole

STATE OF OREGON
WELL LOCATION MAP

This map is supplemental to the WATER SUPPLY WELL REPORT

Oregon Water Resources Department
725 Summer St NE, Salem OR 97301
(503)986-0900

LOCATION OF WELL

Latitude: 44.72913679 Datum: WGS84
Longitude: -123.71965724
Township/Range/Section/Quarter-Quarter Section:
WM10.00S8.00W6NESW
Address of Well:
12319 LOGSDEN RD, BLODGETT, OR 97326

Well Label: 113915

Printed: March 16, 2026

DISCLAIMER: This map is intended to represent the approximate location the well. It is not intended to be construed as survey accurate in any manner.

Provided by well constructor