NOTICE TO WATER WELL CONTRACTOR
The original and first copy
of this report are to be
filed with the
STATE ENGINEER, SALEM, OREGON 97310

within 30 days from the date of well completion.

VATER WELL REPORT RECEIVED

STATE OF OREGON DEC 1 & 1973 State Well No. 95 9W-19
(Please type or print) STATE ENGINEER
(Do not write above this line) SALEM, OREGON

		-	
(1) OWNER:	(10) LOCATION OF WELL:		
Name LINCOLN COUNTY PARKS	County LINCOLN Driller's well number		
Address Lincoln Co Courst Hs	14 14 Section 19 T. 9S R. 9W W.M.		
Newport, Ore	Bearing and distance from section or subdivision corner		
(2) TYPE ÖF WORK (check):	Boundary and distance from Section of Subdivision Comer		
New Well □ Deepening □ Reconditioning □ Abandon □	2		
If abandonment, describe material and procedure in Item 12.	(11) WATER LEVEL: Completed well.		
(3) TYPE OF WELL: (4) PROPOSED USE (check):	Depth at which water was first found 85 ft.		
Rotary X Driven Domestic X Industrial Municipal	Static level 30 ft. below land s		10/29/7
Cable	Artesian pressure lbs. per square inch. Date		
CASING INSTALLED: Threaded Welded 5 250	(12) WELL LOG: Diameter of well below casing 6"		
4" Diam. from0ft. to140ft. GageDVC			
ft. Gage	Formation: Describe color, texture, grain size and structure of materials; and show thickness and nature of each stratum and aquifer penetrated,		
PERFORATIONS: Perforated? IX Yes I No.	with at least one entry for each change of format position of Static Water Level and indicate prin	ion. Report e	ach change in
		cipai water-o	earing strata.
Type of perforator used drill	MATERIAL		o SWL
Size of perforations 4 in. by round in.	brown top soil	<u>'</u>	
200 perforations from 60 ft. to 140 ft.	brown clay & gravel	8 2	<del></del>
perforations from	brown clay & bolders		
perforations from ft. to ft.	dark gray shale	22 8	
(7) SCREENS: Well screen installed? ☐ Yes ☐ No	light blue sandstone		15
Manufacturer's Name	dark gray shale		32
Type Model No	light blue sandstone	124 1	40
Diam Slot size Set from ft. to ft.	<u>√</u> 2.		
Diam Slot size Set from ft. to ft.	n n	•	
(8) WELL TESTS: Drawdown is amount water level is			
lowered below static level			
Was a pump test made? ☐ Yes ☑ No If yes, by whom?			
Yield: gal./min. with ft. drawdown after hrs.			
n n	7 NF43		
"tested with air;" estimate could fluctuate "	- , A		
Beiler test 15 gal./min. with 81 ft. drawdown after 1 hrs.			
Artesian flow g.p.m.			
perature of water Depth artesian flow encountered ft.	Work started 11/24/73 19 Complete	a11/29/7	3 19
(9) CONSTRUCTION:	Date well drilling machine moved off of well	11/29/7	3 19
Well seal-Material used cement grout	Drilling Machine Operator's Certification:	•	
Well sealed from land surface to	This well was constructed under my direct supervision.  Materials used and information reported above are true to my best knowledge and belief.		
Diameter of well bore below seal6. in.	[Signed] Robert W. Claassew Date 11/26/7319		
Number of sacks of cement used in well seal	(Drilling Machine Operator)		
Number of sacks of bentonite used in well seal sacks	Drilling Machine Operator's License No658		
Brand name of bentonite	Water Wall Contractoris Contractoris		
Number of pounds of bentonite per 100 gallons	Water Well Contractor's Certification:		
of water	This well was drilled under my jurisdiction and this report is true to the best of my knowledge and belief.		
Was a drive shoe used? ☐ Yes ☐ No Plugs Size: location ft.	Name CORVALLIS DRILLING CO INC		
Did any strata contain unusable water?   Yes   No	(Person, firm or corporation) (Type or print) 3440 sw 3rd; Corvallis, Oregon		
Type of water? depth of strata	Address J440 SW Jrd; Corvatits, Oregon		
Method of sealing strata off	[Signed] Clarence A Kinney		
Was well gravel packed? ☐ Yes ☐ No Size of gravel:	(Water Well Contractor)		
Gravel placed from ft. to ft.	Contractor's License No. 560 Date 11/26/73 19		