WATER WELL REPORT
STATE OF OREGON

Run 1017

RECEIVED
FEB 7 1984
WATER RESOURCES DEPT.
SALEM, OREGON

State Well No. 13S/1E-34bb

State Permit No. deepening

PLEASE TYPE or PRINT IN INK

(1) OWNER:
Name Rod Andrews
Address 4614 Long St
City Sweet Home State Oregon

(2) TYPE OF WORK (check):
New Well ☐ Deepening ☑ Reconditioning ☐ Abandon ☐
If abandonment, describe material and procedure in Item 12.

(3) TYPE OF WELL:
Rotary Air ☐ Driven ☐
Rotary Mud ☐ Dug ☐
[illegible] ☐ Bored ☐

(4) PROPOSED USE (check):
Domestic ☐ Industrial ☐ Municipal ☐
Irrigation ☐ Test Well ☐ Other ☐
Thermal: Withdrawal ☐ Reinjection ☐

(5) CASING INSTALLED:
Steel ☐ Plastic ☐
Threaded ☐ Welded ☐
6" Diam. from ft. to ft. Gauge
" Diam. from ft. to ft. Gauge

LINER INSTALLED:
" Diam. from ft. to ft. Gauge

(6) PERFORATIONS:
Perforated? ☐ Yes ☐ No
Type of perforator used
Size of perforations in. by in.
perforations from ft. to ft.
perforations from ft. to ft.
perforations from ft. to ft.

(7) SCREENS:
Well screen installed? ☐ Yes ☐ No
Manufacturer's Name
Type Model No.
Diam. Slot Size Set from ft. to ft.
Diam. Slot Size Set from ft. to ft.

(8) WELL TESTS:
Drawdown is amount water level is lowered below static level

[illegible] a pump test made? ☐ Yes ☐ No If yes, by whom?
Yield: gal./min. with ft. drawdown after hrs.
" " " "
Air test 1 gal./min. with drill stem at 400 ft. 1 hrs.
Bailer test gal./min. with ft. drawdown after hrs.
[illegible]esian flow g.p.m.
Temperature of water Depth artesian flow encountered ft.

(9) CONSTRUCTION:
Special standards: Yes ☐ No ☐
Well seal—Material used
Well sealed from land surface to ft.
Diameter of well bore to bottom of seal in.
Diameter of well bore below seal in.
Number of sacks of cement used in well seal sacks
How was cement grout placed?
Was pump installed? Type HP Depth ft.
Was a drive shoe used? ☐ Yes ☐ No Plugs Size: location ft.
Did any strata contain unusable water? ☐ Yes ☐ No
Type of Water? depth of strata
Method of sealing strata off
Was well gravel packed? ☐ Yes ☐ No Size of gravel:
Gravel placed from ft. to ft.

(10) LOCATION OF WELL:
County Linn Driller's well number
NW ¼ NW ¼ Section 34 T. 13S R. 1E W.M.
Tax Lot # Lot Blk Subdivision
Address at well location: Approx 90 East on long St Between 4th and 5th st

(11) WATER LEVEL: Completed well.
Depth at which water was first found 390 ft.
Static level 31 ft. below land surface. Date 2-3-84
Artesian pressure lbs. per square inch. Date

(12) WELL LOG:
Diameter of well below casing 6
Depth drilled 460 ft. Depth of completed well 460 ft.

Formation: Describe color, texture, grain size and structure of materials; and show thickness and nature of each stratum and aquifer penetrated, with at least one entry for each change of formation. Report each change in position of Static Water Level and indicate principal water-bearing strata.

MATERIAL	From	To	SWL
Blue Sandstone/Hard	45	460	

Work started Feb 1 1984 Completed Feb 3 1984
Date well drilling machine moved off of well Feb 3 1984

(unbonded) Water Well Constructor Certification (if applicable):
This well was constructed under my direct supervision. Materials used and information reported above are true to my best knowledge and belief.
[Signed] Howard Ross Date Feb 3, 1984

Bonded Water Well Constructor Certification:
Bond U30 50 (number) Issued by: United Pacific Surety Company Name
This well was drilled under my jurisdiction and this report is true to the best of my knowledge and belief.
Name ABMS & Schilling WELL DRILLING (Person, firm or corporation) (Type or print)
Address 29030 SAINT MARY Hwy SWEET HOME
[Signed] Howard Ross Water Well Constructor
Date Feb 3, 1984

NOTICE TO WATER WELL CONSTRUCTOR
The original and first copy of this report are to be filed with the WATER RESOURCES DEPARTMENT, SALEM, OREGON 97310 within 30 days from the date of well completion.

SP*45292-690