NOTICE TO WATER WELL CONTRACTOR

The original and first copy
of this report are to be
filed with the

## WATER WELL REPORT ULIVEU

STATE OF OREGON JUN 2 1 1976 State Well No. .....

STATE ENGINEER, SALEM, OREGON 97310 N Within 30 days from the date of well completion.

(Please type or print)
WATER RESOURCES STEP Permit No. 125/3W 7db
(Do not write above this line)
SALEM, OREGON

**		
1) OWNER:	(10) LOCATION OF WELL:	
Glen White	County Linn Driller's well number 45676D	
ddress 1803 N. W. Park Terrace	$\overline{NW}$ SE $_{\frac{1}{2}}$ Section $\overline{4}$ T. 12S R.	3 <b>W</b> w.м.
Albany, Oregon 97321	Bearing and distance from section or subdivision	corner
2) TYPE OF WORK (check):	Douring date described and the second	
New Well X Deepening ☐ Reconditioning ☐ Abandon ☐		
f abandonment, describe material and procedure in Item 12.	(11) THAMED I EXTEL Completed well	
	(11) WATER LEVEL: Completed well.	
3) TYPE OF WELL: (4) PROPOSED USE (check):	Depth at which water was first found	ft.
totary Driven Domestic Dindustrial Municipal A	Static level 10 ft. below land surfa	ace. Date 6/4/76
oug	Artesian pressure Ibs. per square in	ich. Date
CACYNIC YNCHAILED		/••
CASING INSTALLED: Threaded Welded W	(12) WELL LOG: Diameter of well below	
6" "Diam. from	Depth drilled 140 ft. Depth of completed	well 140 ft.
"Diam. fromft. toft. Gage	Formation: Describe color, texture, grain size and structure of materials;	
" Diam. fromft. toft. Gage	and show thickness and nature of each stratum and aquifer penetrated, with at least one entry for each change of formation. Report each change in	
PERFORATIONS: Perforated?   □ Yes □ No.	position of Static Water Level and indicate principal	
tomah	MATERIAL F	rom To SWL
type of periorator about		
Size of perforations 1/1 in. by 8 in.		0 1 1
120 perforations from 120 ft. to XXX 1/40 ft.		$\frac{1}{13}$ $\frac{11}{10}$ $\frac{10}{10}$
perforations from ft. toft.	gravel & clay & sand	11 18
perforations from ft. to ft.		18 20
(7) SCREENS: Well screen installed?   Yes  No		20 23
Manufacturer's Name		23 52 52 58
rype Model No.	blue clay	
Diam. Slot size Set from ft. to ft. to ft.		58 97 97 107
Diam. Slot size Set from ft. to ft.	brown gravel & sand	107 110
	brown sand & clay	110 111
(8) WELL TESTS: Drawdown is amount water level is lowered below static level	gravel & sand	111 112
Was a pump test made? 图 Yes 口 No If yes, by whom? Schoen g	brown sand & clay	12013170
	gray clay	131 140
"		
n " " "		
Baller test XX. gal./min. with ft. drawdown after hrs.		
Artesian flow g.p.m.		
of water 53 Depth artesian flow encountered ft.	Work started 4/15 19 6 Completed	6/4 1976
(0) CONSTRUCTION. Cement & Bentonite clay	Date well drilling machine moved off of well	6/4 1976
(9) CONSTRUCTION: Cement & Bentonitie Clay		
Well seal—Material used	Drilling Machine Operator's Certification:  This well was constructed under my di	irect sunervision.
Well sealed from land surface toft.	Materials used and information reported ab	ove are true to my
Diameter of well bore to bottom of seal105/8 in.	best knowledge and belief.	1100 71
Diameter of well bore below seal	[Signed] Wale Heowit Date 6/18, 19.76	
Number of sacks of cement used in well seal	Drilling Machine Operator's License No. 594	
Number of sacks of bentonite used in well seal sacks		
Brand name of bentonite Bentonite	Water Well Contractor's Certification:	
Number of pounds of bentonite per 100 gallons of water 58 lbs./100 gals.	This well was drilled under my jurisdiction and this report is	
	true to the best of my knowledge and belief. Schoen Electric & Pump	
Was a drive shoe used? He yes No Plugs Size: location ft.	Name Schoon Electric & Pund (Type or print)	
Did any strata contain unusable water?   Yes   No	Address 626 W. Queen Avenue - Mbany, Or. 97321	
Type of water? depth of strata	Address	
Method of sealing strata off	[Signed] amy E Hewa	
Was well gravel packed? 🗌 Yes 💾 No Size of gravel:	(Water Well Contract	F/10 71
Gravel placed from ft. to ft.	Contractor's License No. 513 Date	9// 0 , 18/ C