The original and first copy of this remember LULI WARED VLIN	IN 10557 //Y N State Well No	125/	3w-29
WATER RESOURCES DEPARTMENT. NOV 2 1978 TATE OF SALEM, OREGON 97310 Within 30 days from the date of well completion. WATER RESOURCES DEPT SALEM, OREGON	or print) /0557	No	
(1) OWNER:	(10) LOCATION OF WELL:		
Name Cala Farms Inc.	County Linn Driller's well		
Address 31144 Wirth Rd.	34 14 Section 29 T. 12	$2S_{R.}$ 3W	W.M.
Tengent, Oregon 97389	Bearing and distance from section or subdivi	sion corner	
(2) TYPE OF WORK (check):	Dearing and about		
New Well of Deepening Reconditioning Abandon			
If abandonment, describe material and procedure in Item 12.	(11) WATER LEVEL: Completed well.		
(3) TYPE OF WELL: (4) PROPOSED USE (check):	Depth at which water was first found 22 ft.		
D. A. C. Deimon C.		l surface. Date	
Cable 10 Jetted Domestic Industrial Municipal		are inch. Date	
Dug Bored Irrigation Test well Other	Artesian pressure lbs. per squ	are men. Date	;
(CASING INSTALLED: Threaded Welded 12 12 Diam from 0 ft to 108 ft Gage 250	(12) WELL LOG: Diameter of well Depth drilled 115 ft. Depth of com		12
"Diam. from ft. to ft. Gage	Formation: Describe color, texture, grain size		
PERFORATIONS: Perforated? X Yes No.	and show thickness and nature of each stra with at least one entry for each change of forn position of Static Water Level and indicate pr	tum and aquif nation. Report e	er penetrated, each change in
manah and	MATERIAL	From	To SWL
1 1	topsoil	0 2	
800 perforations from 22 ft. to 104 ft.	topsoilsamdy loam	2 1	5
perforations from	sand & gravel	1 1	6
perforations from the to the perforations from the to the perforations from the total fit.	blue clay & pea gravel	46 7	7
periorations from 11. to	dark blue sticky clay	77 8	2
(7) SCREENS: Well screen installed? Yes No	- cemented gravel		6
Manufacturer's Name	blue sandy clay	86 1	00
Tope Model No.	- black sand & pea gravel	100 1	07
Diam Slot size Set from ft. to ft.	- blue sticky clay	107 1	15
Diam. Slot size Set from ft. to ft.		_	
(8) WELL TESTS: Drawdown is amount water level is lowered below static level			
Was a pump test made? Yes The No If yes, by whom?			
Yield: gal./min. with ft. drawdown after hrs.			
tested with air could fluctuate "			
, " " " " "			
ailer test 300+ gal./min. with 58 ft. drawdown after 4 hrs.			
Artesian flow g.p.m.			
perature of water Depth artesian flow encountered ft.	Work started 9/7/78 19 Completed 10/13/78 19 Date well drilling machine moved off of well 10/13/78 19		
) CONSTRUCTION:	Date well drilling machine moved off of well	10/15//	0 19
Well seal—Material used cement	Drilling Machine Operator's Certification		
Well zealed from land surface toft.	This well was constructed under n Materials used and information reporte	ny direct su ed above are	pervision, true to my
Diameter of well bore to bottom of sealin.	best knowledge and belief.		
Diameter of well bore below seal in.	[Signed] Corilling Machine Operator)	4 Date 10/2	: 3/78 19
Number of realize of coment used in well coal 24 sacks	prilling Machine Operator's License No	160	
How was cement grout placed? IIIXed & Poured Irom	Water Well Contractor's Certification:		
	This well was drilled under my jurisdiction and this report is true to the best of my knowledge and belief.		
Was a drive shoe used? Tyes [] No Plugs Size: location ft.	Name Corvallis Drilling Co.	Inc.	
Did any strata contain unusable water? 🗌 Yes 🅇 No	(Person, firm or corporation) Address 3440 SW 3rd St. Corve	(Turne	eon 97330
	Address 544U SW STO St. COLVE		J / 1//-

Size of gravel: ..

Method of sealing strata off

Was well gravel packed?
Yes No

Contractor's License No.560... Date10/23/78........, 19......