The original and first copy of this report are to be filed with the STATE ENGINEER, SALEM 10, OREGON within 30 days from the date of well completion.

State Well No.

State Permit No. ...

(1) OWNER: Name Floyd Bulman	(11) WELL TESTS: Drawdown is amount water level is lowered below static level Was a pump test made? Yes No If yes, by whom?	
Address 3726 Peoria Road, Corvallis, Ores	Yield: 300 gal./min. with / ft. drawdown after 2	hrs.
	430 " 1 " 2	"
(2) LOCATION OF WELL, Well No 5 of 5	" "	,,
(2) DOCATION OF WEALE:	Bailer test gal./min. with ft. drawdown after	hrs.
County Linn Driller's well number	Artesian flow g.p,m. Date	
1/4 1/4 Section T. R. W.M.	Temperature of water Was a chemical analysis made? ☐ Yes	II No
Bearing and distance from section or subdivision corner		
	(12) WELL LOG: Cased to bottom Diameter of well below casing	
	Depth drilled 31 ft. Depth of completed well 31	£t.
	Formation: Describe by color, character, size of material and structur	e, and
	Formation: Describe by color, character, size of material and structur show thickness of aquifiers and the kind and nature of the material is stratum penetrated, with at least one entry for each change of form	n eacn nation.
(3) TYPE OF WORK (check):		TO
New Well∑ Deepening Reconditioning Abandon □	1	LO
bandonment, describe material and procedure in Item 12.		4
	sand, clay and boulders 14 2	31
(4) PROPOSED USE (check): (5) TYPE OF WELL:	4" diameter	
Domestic Industrial Municipal Rotary Driven Cable Jetted	coarse gravel $2\frac{1}{8}-3^{11}$ 21 3	31
Irrigation A Test Well Other Dug Bored		
(6) CASING INSTALLED: Threaded Welded To Sun		
10 "Diam. from +3 ft. to 31 ft. Gage STD		
ft. Gage		
(7) PERFORATIONS: Perforated? Yes No		
Type of perforator used acetylene torch		
Size of perforations 6 in. by 5/8 in.		 =
100 perforations from 21 ft. to 31 ft.		
perforations fromft. toft.	The second secon	
perforations fromft. toft.		
perforations fromft_ toft_		
perforations fromft. toft.		
periorations from		
(8) SCREENS: Well screen installed? ☐ Yes ☑ No		
Manufacturer's Name		
Two: Model No	<u> </u>	<u>-</u>
1	Work started 12-10-63 19 . Completed 12-13-63	, 7
Diam Slot size Set from ft. to ft.	79 14 67	· 124
	Date well drilling machine moved off of well 12-14-63	19
(9) CONSTRUCTION:	(13) PUMP:	
Well seal—Material used in sealbentonite	Manufacturer's Name	
Depth of seal8 ft. Was a packer used?	Type:	
Diameter of well bore to bottom of sealin.		
Were any loose strata cemented off? Yes No Depth	Water Well Contractor's Certification:	
Was a drive shoe used? ☐ Yes Ҳ No	This well was drilled under my jurisdiction and this repo	ort is
Was well gravel packed? ☐ Yes 🏿 No Size of gravel:	true to the best of my knowledge and belief.	010 15
Gravel placed from ft. to ft.	NAME Parmond C Colleti	
Did any strata contain unusable water? Yes No	NAME Raymond C. Gellatly (Person, firm or corporation) (Type or print)	
Type of water? Depth of strata	Address Box 1 Philomath, Oregon	,
Method of sealing strata off	The state of the s	-
	Drilling Machine Operator's License No76	-
(10) WATER LEVELS: Static level 14 ft. below land surface Date 12-7%	reigned Player and C. He Walter	
Static level 14 ft, below land surface Date 12-77	[Signed] Myny M (Water Well Contractor)	
Artesian pressure lbs. per square inch Date	Contractor's License No. 77 Date 1-13-64	9