NOTICE TO WATER WELL CONTRACTOR
The original and first copy
of this report are to be filed with the

STATE ENGINEER, SALEM OREGON 97310 within 30 days from the date of well completion.

WATER WELL REPORTS E STATE OF OREGON AND (Please type STATE OF OREGON AUG 15 1973 State Well No.

(Please type or print) ATE ENGINES Remit No.
(Do not write above this line) EM. OREGON

(1) OWNER:	(10) LOCATION OF WELL:	
Name Oakvilla Trailer Court	County Linn Driller's well num	ber
Address Rt. 3, Albany, Ore. 97321	14 14 Section 10 T. 12S R	4W W.M.
	Bearing and distance from section or subdivision	
(2) TYPE OF WORK (check):		
New Wel∭ Deepening ☐ Reconditioning ☐ Abandon ☐	77 - 77 - 77 - 47 -	
If abandonment, describe material and procedure in Item 12.	(11) WATER LEVEL: Completed wel	
(3) TYPE OF WELL: (4) PROPOSED USE (check):		To 34 ft.
Rotary □ Driven □ □ Domestic 🎦 Industrial □ Municipal □	- Branch	face. Date 7-24-73
Cable M Jetted	y a data of the second	
		nen. Date
CASING INSTALLED: Threaded Welded	(40) THEFT TOO	ow casing6ii
6." Diam. from +08!! ft. to 40.05! ft. Gage 1.7#	Depth drilled 48 ft. Depth of complete	
"Diam. from	Formation: Describe color, texture, grain size and	
ft. to ft. Gage	and show thickness and nature of each stratum and aquifer penetrated, with at least one entry for each change of formation. Report each change in	
PERFORATIONS: Perforated? Ty Yes No.	position of Static Water Level and indicate princip	 Report each change in al water-bearing strata.
Type of perforator used Acetylene Torch Size of perforations 3/8 in. by 12 in.		
Size of perforations 3/8 in by 12 in	m - n - 13	From To SWL
36 perforations from 31 tt. to 40 ft.	Brown Clay	2 20
perforations from ft. to ft.		20 26
perforations fromft. toft.		26 34
	Brown Clay	34 40
(7) SCREENS: Well screen installed? ☐ Yes 🙀 No	Blue Clay	40 48
Manufacturer's Name		
Type		
Diam. Slot size Set from ft. to ft.	я	
Diam. Slot size Set from ft. to ft.	##	
(8) WELL TESTS: Drawdown is amount water level is lowered below static level		
Was a pump test made? ☐ Yes ∑ No If yes, by whom?		
Yild: gal./min. with ft. drawdown after hrs.		
" " "		
" " " " "		
Bailer test 24 gal./min. with 13 ft. drawdown after 1 hrs.	and the second s	
Artesian flow g.p.m.		
perature of water Depth artesian flow encountered	7 37	
	Work started 7-23 19 73 Completed	7-24 19 73
(9) CONSTRUCTION:	Date well drilling machine moved off of well	7-25 ¹⁹ 73
Well seal—Material used Bentonite	Drilling Machine Operator's Certification:	e i e i e e e e e e e e e e e e e e e e
Well sealed from land surface toft.	This well was constructed under my direct supervision. Materials used and information reported above are true to my	
Diameter of well bore to bottom of sealin.	best knowledge and belief.	
Diameter of well bore below sealin.	[Signed] Machine Operator) Date //26, 19.7.3	
Number of sacks of cement used in well seal sacks	Drilling Machine Operator's License No. 436	
Number of sacks of bentonite used in well seatsacks	Diffing Machine Operator's Incense No.	
Brand name of bentonite Oregon Bentonite	Water Well Contractor's Certification:	
Number of pounds of bentonite per 100 gallons	This well was drilled under my jurisdiction and this report is	
of water lbs./100 gals. Was a drive shoe used? Y Yes No Plugs Size: location ft.	true to the best of my knowledge and belief.	
Did any strata contain unusable water? Yes No	Name Merle Warren Well Drilling (Person, firm or corporation) (Type or print)	
	Part Part Part Part Part Part Part Part	(Type or print)
	Address Rt. Box 84, Tangent, Ore. 97321	
Method of sealing strata off	Signed	
Was well gravel packed? ☐ Yes X☐ No Size of gravel:		
Gravel placed from ft. toft.	Contractor's License No182 Date	120 , 19 / 3