App # 30460

LINN
10719

NOTICE TO WATER WELL CONTRACTOR
The original and first copy of this report are to be filed with the STATE ENGINEER, SALEM, OREGON 97310 within 30 days from the date of well completion.

RECEIVED
MAR 15 1965
STATE ENGINEER
SALEM OREGON

WATER WELL REPORT
STATE OF OREGON
(Please type or print)

State Well No. 12/4W-14 R

State Permit No. App. #G-3046

(1) OWNER:
Name S.R. Phillips
Address RH 1 Box 130
TANGENT ORE.

(2) LOCATION OF WELL:
County LINN Driller's well number
SE ¼ SE ¼ Section 14 T. 12 S. R. 4 W. W.M.
Bearing and distance from section or subdivision corner
N. 37° E. 10 CHAINS FROM SE
CORNER OF JOHN H. EDMONDSON
D.L.C. 58

(3) TYPE OF WORK (check):
New Well ☑ Deepening ☐ Reconditioning ☐ Abandon ☐
If abandonment, describe material and procedure in Item 12.

(4) PROPOSED USE (check):
Domestic ☐ Industrial ☐ Municipal ☐
Irrigation ☑ Test Well ☐ Other ☐

(5) TYPE OF WELL:
Rotary ☐ Driven ☐
Cable ☑ Jetted ☐
Dug ☐ Bored ☐

(6) CASING INSTALLED:
Threaded ☐ Welded ☑
6 " Diam. from 0 ft. to 71 ft. Gage ¼ wall
" Diam. from ft. to ft. Gage
" Diam. from ft. to ft. Gage

(7) PERFORATIONS:
Perforated? ☑ Yes ☐ No
Type of perforator used GAS TORCH
Size of perforations ¼ in. by 12 in.
4 Rows of 6 perforations from 59 ft. to 70 ft.
perforations from ft. to ft.
perforations from ft. to ft.
perforations from ft. to ft.
perforations from ft. to ft.

(8) SCREENS:
Well screen installed? ☐ Yes ☑ No
Manufacturer's Name
Type Model No.
Diam. Slot size Set from ft. to ft.
Diam. Slot size Set from ft. to ft.

(9) CONSTRUCTION:
Well seal—Material used in seal Bentonite
Depth of seal 20 ft. Was a packer used?
Diameter of well bore to bottom of seal 10 in.
Were any loose strata cemented off? ☐ Yes ☑ No Depth
Was a drive shoe used? ☐ Yes ☑ No
Was well gravel packed? ☐ Yes ☑ No Size of gravel:
Gravel placed from ft. to ft.
Did any strata contain unusable water? ☐ Yes ☐ No
Type of water? depth of strata
Method of sealing strata off

(10) WATER LEVELS:
Static level 10 ft. below land surface Date March 65
Artesian pressure lbs. per square inch Date

(11) WELL TESTS:
Drawdown is amount water level is lowered below static level
Was a pump test made? ☐ Yes ☑ No If yes, by whom?
Yield: gal./min. with ft. drawdown after hrs.
" " " "
" " " "
Bailer test 50 gal./min. with 9 ft. drawdown after 1 hrs.
Artesian flow g.p.m. Date
Temperature of water Was a chemical analysis made? ☐ Yes ☐ No

(12) WELL LOG:
Diameter of well below casing 6
Depth drilled 80 ft. Depth of completed well 75 ft.
Formation: *Describe by color, character, size of material and structure, and show thickness of aquifers and the kind and nature of the material in each stratum penetrated, with at least one entry for each change of formation.*

MATERIAL	FROM	TO
Top Soil	0	5
BROWN CLAY	5	18
BROWN SAND & GRAVEL	18	29
Blueish BLACK SAND & GRAVEL	29	71
BLUE CLAY	71	80

Work started Feb 1965 Completed MARCH 1965
Date well drilling machine moved off of well MARCH 4 1965

(13) PUMP:
Manufacturer's Name
Type: H.P.

Water Well Contractor's Certification:

This well was drilled under my jurisdiction and this report is true to the best of my knowledge and belief.

NAME Bill Howell
(Person, firm or corporation) (Type or print)
Address RH 2 CORVALLIS ORE.
Drilling Machine Operator's License No. 79
[Signed] Bill Howell
(Water Well Contractor)
Contractor's License No. 50 Date MARCH 4, 1965

(USE ADDITIONAL SHEETS IF NECESSARY)