WATER WELL REPORT STATE OF OREGON

MAY 0 4 1981 WATER RESOURCES DEPT SALEM, OREGON

nc/0724

State Well No. 1294W-16

	And the second s	
(1) OWNER:	(10) LOCATION OF WELL:	···
Name Allen Conley	County Linn Driller's well number C/5/81	
Address 32483 Oak ville Rd.	¼ % Section 1.6 T. 12S R. 4W	W.M.
City Albany, Oregon 97321 State	Tax Lot # 392890 Lot Blk Subdivision	- 1
(2) TYPE OF WORK (check):	Address at well location:	^ -
New Well □ Deepening □ Reconditioning □ Abandon □	(44) 11/1/10/10 1 11/10/10	,
If abandonment, describe material and procedure in Item 12.	(11) WATER LEVEL: Completed well.	
(3) TYPE OF WELL: (4) PROPOSED USE (check):	Depth at which water was first found	ft.
Rotary Air 🗆 Driven 🗆 Domestic 🖫 Industrial 🗆 Municipal 🗅	10 Selow land Sarrace. Bate 15/	12481
Rotery Mud	(40)	
Bored □ Thermal: Withdrawal □ Reinjection □	(12) WELL LOG: Diameter of well below casing6	**********
(5) CASING INSTALLED: Steel	Depth drilled 49 ft. Depth of completed well 49	
Threaded Welded T	Formation: Describe color, texture, grain size and structure of materials; a thickness and nature of each stratum and aquifer penetrated, with at least o	and show
6	for each change of formation. Report each change in position of Static Wat	ter Level
"Diam fromft. toft. Gauge	and indicate principal water-bearing strata.	
LINER INSTALLED:	MATERIAL From To	SWL
ft. to ft. Gauge	Topsoil 0 3	-
(6) PERFORATIONS: Perforated? ▼ Yes □ No	Dark brown clay 3 9	
T	Light brown clay 9 22	
Type of perforation used Torch cut. Size of perforations $\frac{1}{h}$ in. by μ in.	Cemented sand&gravel 22 29	
80 perforations from29 ft. to38 ft.	Sand&gravel 29 39	
perforations fromft. toft.	Blue clay 39 49	
perforations fromft. toft.	<u>.</u>	
(7) SCREENS: Well screen installed? Yes No	ь	
Manufacturer's Name		
Type		
Diam. Slot Size Set from ft. to ft.		
Diam. Slot Size Set from ft. to ft. Drawdown is amount water level is lowered		
(8) WELL TESTS: below static level below static level		
a pump test made? Yes No If yes, by whom?		
red: gal/min. with ft. drawdown after hrs.		
11 11 11 11 11 11 11 11 11 11 11 11 11	· · · · · · · · · · · · · · · · · · ·	 -
Air test gal./min. with drill stem at ft. hrs.		
Bailer test 50 gal./min. with 49 ft. drawdown after 1 hrs.		
eian flow g.p.m.		
Depth artesian flow encounteredft.	Work started 4/21/81 19 Completed 4/22/81	19
(9) CONSTRUCTION: Special standards: Yes \(\subseteq \) No \(\subseteq \)	Date well drilling machine moved off of well 4/23/8/	19
Well seal—Material used	Drilling Machine Operator's Certification:	
Well sealed from land surface to	This well was constructed under my direct supervision. Materia	la rigad
Diameter of well bore to bottom of seal 10 in.	and information reported above are true to my best knowledge and	belief.
Diameter of well bore below seal	[Signed] / Manual Summus Date 4/23/	81
Number of sacks of cement used in well seal sacks		
low was cement grout placed?	Drilling Machine Operator's License No. 1480	
Pumped through tremie	Water Well Contractor's Certification:	
Was assessed to the 11.30	This well was drilled under my jurisdiction and this report is the best of my knowledge and belief.	
Was pump installed?	Name Corvallis Drilling Co. Inc. (Type or print)	
Was a drive shoe used? ⊉ Yes □ No Plugs Size: locationft. Did any strata contain unusable water? □ Yes ↓□ No	(Person, firm or corporation) (Type or pri	nt)
Type of Water? depth of strata	Address 3440. St. 3rd &t. Corvallie, Oregon 97	ବ ବନ…
Method of sealing strata off	[Signed]	ノノ マ
Was well gravel packed? ☐ Yes ☐ No Size of gravel:	(Water Well Contractor)	COLUMN TO SERVICE SERV
Fravel placed from	Contractor's License No721 Date4/23/81	19