ORIGINAL File Original, and Duplicate with the STATE ENGINEER, OBSERVATION SALEM, OREGON	WATER WELL DRILL WELL STATE OF OR	
(1) OWNER: ASSIGNED TO ROST		(10) WELL TESTS: Moore's Irrigation
111 1 3 1470 5		Was a pump test made? X Yes  No If yes, by whom?
Address PHI, SHEDD, ORE		Yield: 95 gal./min. with 51 ft. draw down after 4 hrs.
(2) LOCATION OF WELL:		. 27 29 29
		Artesian flowg.p.m.
R. F. D. or Street No.		Shut-in pressure lbs, per square inch.
Bearing and distance from section or subdivision	on corner	Bailer test NONE g.p.m. with ft. drawdown
2376'S AND 2046' B FROM THE		Temperature of water Was a chemical analysis made? Yes No
SW CORNER S. 21, T. 128, R. 4W.		Was electric log made of well?   Yes No
		(11) WELL LOG:
(9) MYDE OF MODIZ (-1-).		Diameter of well, inches.
(3) TYPE OF WORK (check):  New well Ty Deepening Ty Reconditioning Ty Abandon Ty		Total depth 146 ft. Depth of completed well 75 ft.
New well Deepening Reconditioning Abandon 2000 Abandon 20		Formation: Describe by color, character, size of material and structure, and show thickness of aquifers and the kind and nature of the material in each stratum penetrated, with at least one entry for each change of formation.
(4) PROPOSED USE (check): (5) EQUIPMENT:		O ft. to 21 ft. clay, brown
Domestic   Industrial   Municipal	Rotary	21 " 39 " clay & gravel, brown
Irrigation X Test Well ☐ Other	Cable	39 " 60 " clay, blue
	Dug Well	60 " 74 " sand, black
CASING INSTALLED:	If gravel packed	74 " 146 " clay, blue
Threaded ☐ Welded 🏝 Gage		11 11
FROM 0 ft. to 75 ft.6" Diam. • 280 Wall	Diameter from to of Bore ft. ft.	11
" " " " " " " "	" "	" "
yy yy yy yy yy		11 11
37 37 33 33	" "	)) ))
y yy yy yy yy	); );	" "
15 27 27 27	"	_ n _ n
Type and size of shoe or well ring	Size of gravel:	,, ,,
Describe joint		1) ))
(7) PERFORATIONS:		11 11
Type of perforator used torch		11 11
SIZE of perforations 3/8 in., length, by 7 in.		23 33
FROM 60 ft. to 75 ft. 6 perf per foot 15 No. of rows		" "
n n n		"
" " "	)) )) )) )) )) )) )) )) )) )) )) )) ))	1) ))
1) 1) 2) 21	,, ,, ,, ,, ,, ,, ,, ,, ,, ,, ,, ,, ,,	11 39
		" "
SCREENS: Give Manufacturer's Name, Model No. and Size		" "
Give Manufacturer's Name, Model No.	and size	n n
CONCERNICATION		11 12
(o) CONSTRUCTION: Was a surface sanitary seal provided? ☐ Yes ☐	XNo To what depth ft.	" "
Were any strata sealed against pollution?   Y	<del></del>	Ground elevation at well sitefeet above mean sea level.
If yes, note depth of strata		Work started July 15 1955, Completed July 29, 1955
FROM ft. to	ft.	Well Driller's Statement:
"	"	This well was drilled under my jurisdiction and this report is
METHOD OF SEALING		true to the best of my knowledge and belief.
(9) WATER LEVELS:		NAME William M. Slate
Depth at which water was first found 26	ft.	(Person, firm, or corporation) (Typed or printed)
Standing level before perforating 21	ft.	Address 1115 S. Geary St. Albany, Ore.
Standing level after perforating 21	ft.	Driller's well number
Log Accepted by:	1	- Milli Ma Sa-a
Fair THAMAS I Aloum	[Signed] // (Well Driller)	
[Signed] Date Owner	d 7/2 5, 19.38	License No. 106 Dated July 15, 1958