

NOTICE TO WATER WELL CONTRACTOR

The original and first copy of this report are to be filed with the

STATE ENGINEER, SALEM, OREGON 97310

within 30 days from the date of well completion.

RECEIVED JUL 10 1968 STATE ENGINEER SALEM OREGON

WATER WELL REPORT

(Please type or print) Write above this line

RECEIVED AUG 14 1968 STATE ENGINEER SALEM OREGON

LINN 10930

State Well No. 12/2-36aa

State Permit No. G5205

(1) OWNER:

Name Portland District-Corps of Engineers Address 628 Pittock Block-Portland, Oregon 97205

(2) TYPE OF WORK (check):

New Well [X] Deepening [] Reconditioning [] Abandon []

If abandonment, describe material and procedure in Item 12.

(3) TYPE OF WELL:

Rotary [X] Cable [] Dug [] Driven [] Jetted [] Bored []

(4) PROPOSED USE (check):

Domestic [X] Industrial [] Irrigation [] Municipal [] Test Well [] Other []

CASING INSTALLED:

6" Diam. from 0 ft. to 77 ft. Gage 29.05 FT

PERFORATIONS:

Perforated? [] Yes [X] No

Type of perforator used

Size of perforations in. by in. perforations from ft. to ft.

(7) SCREENS:

Well screen installed? [] Yes [X] No

Manufacturer's Name Type Model No. Diam. Slot size Set from ft. to ft.

(8) WATER LEVEL: Completed well.

Static level 20 ft. below land surface Date 5/7/68

(9) WELL TESTS:

Drawdown is amount water level is lowered below static level

Was a pump test made? [X] Yes [] No If yes, by whom Valley Well Drillers

Yield: 38 gal./min. with 40 ft. drawdown after 2 hrs.

Bailer test gal./min. with ft. drawdown after hrs.

Artesian flow g.p.m. Date

Temperature of water Was a chemical analysis made? [] Yes [X] No

(10) CONSTRUCTION:

Well seal-Material used CEMENT

Depth of seal 23 ft.

Diameter of well bore to bottom of seal 10.74 in.

Were any loose strata cemented off? [] Yes [X] No Depth

Was a drive shoe used? [X] Yes [] No

Did any strata contain unusable water? [] Yes [X] No

Type of water? depth of strata

Method of sealing strata off

Was well gravel packed? [] Yes [X] No Size of gravel:

Gravel placed from ft. to ft.

(11) LOCATION OF WELL:

County Linn Driller's well number 1/4 Section 36 T. 12S R. 2E W.M. Bearing and distance from section or subdivision corner

(12) WELL LOG:

Diameter of well below casing 6

Depth drilled 100 ft. Depth of completed well 100 ft.

Formation: Describe color, texture, grain size and structure of materials; and show thickness and nature of each stratum and aquifer penetrated, with at least one entry for each change of formation. Report each change in position of Static Water Level as drilling proceeds. Note drilling rates.

Table with columns: MATERIAL, From, To, SWL. Rows include: Redish Brown clay with BOULDERS (0-49), Gray Brown clay with BOULDERS (49-65), Brown shale (65-75), Brown rock (75-85), Brown shale (85-90), Brown gray shale (90-95), Gray shale (95-100)

Work started 4/29/68 1968 Completed 5/7/1968

Date well drilling machine moved off of well 5/7/1968

Drilling Machine Operator's Certification:

This well was constructed under my direct supervision. Materials used and information reported above are true to my best knowledge and belief.

[Signed] W.D. Parkella (Drilling Machine Operator) Date 6/20/1968

Drilling Machine Operator's License No. 491

Water Well Contractor's Certification:

This well was drilled under my jurisdiction and this report is true to the best of my knowledge and belief.

NAME Valley Well Drillers (Person, firm or corporation) (Type or print)

Address P.O. Box 885 - Albany, Oregon 97321

[Signed] Edward Butts (Water Well Contractor)

Contractor's License No. 253 Date July 18, 1968