NOTICE TO WATER WELL CONTRACTOR

The original and first copy
of this report are to be
filed with the

STATE ENGINEER, SALEM, OREGON 97310 within 30 days from the date of well completion.

## WATER WELL REPORT

STATE OF OREGON

(Please type or print) 1999

State Well	No. 135)	1W-4
•	•	
State Pern	nit No	

(1) OWNER:	(10) LOCATION OF WELL:
Name LEBANON School DISTRICT #16C	County LINN Driller's well number
Address 845 S. 546 LEBANON ORE	1/4 Section 4/ T. /3S R. /W W.M.
	Bearing and distance from section or subdivision corner
New Well □ Deepening X Reconditioning Abandon □	
If abandonment, describe material and procedure in Item 12.	(11) WATER LEVEL: Completed well.
(3) TYPE OF WELL: (4) PROPOSED USE (check):	Depth at which water was first found 13 ft.
Rotary Driven Domestic Industrial Municipal	Static level 25 ft. below land surface. Date 7-29-75
Cable	Artesian pressure lbs. per square inch. Date
CASING INSTALLED:  "Diam. from Do ft. to Sage 250  "Diam. from ft. to ft. Gage 550	(12) WELL LOG: Diameter of well below casing
"Diam. fromft. toft. Gage	Formation: Describe color, texture, grain size and structure of materials; and show thickness and nature of each stratum and aquifer penetrated,
PERFORATIONS: Perforated?   Yes No.	with at least one entry for each change of formation. Report each change in position of Static Water Level and indicate principal water-bearing strata.
Type of perforator used	MATERIAL From To SWL
Size of perforations in. by in.	BROWN GRAVEL 60 64
perforations from ft. to ft.	Brown Clay 64 72
perforations from	SAND & GRAVIR 12 75
perforations from ft. to ft.	
(7) SCREENS: Well screen installed? \(\sigma\) Yes \(\forall \text{No.}\)	
(7) SCREENS: Well screen installed?  Yes No	
Type Model No.	
Diam Slot size Set from ft. to ft.	
Diam Slot size Set from ft. to ft.	
(8) WELL TESTS: Drawdown is amount water level is lowered below static level	RECEIVED
Was a pump test made?  Yes V No If yes, by whom?	1100 01075
Yield: gal./min. with ft. drawdown after hrs.	AUG2 01975
<i>n n n</i>	WATER RESOURCES DEPT.
Tested W/AIR est 25 gpm "	SALEM, OREGON
Bailer test gal./min. with ft. drawdown after hrs.	
Artesian flow g.p.m.	
perature of water Depth artesian flow encountered ft.	Work started 7-29 1975 Completed 7-29 1975
(9) CONSTRUCTION:	Date well drilling machine moved off of well 7-29 19 75
Well seal—Material used UNDISTURBED	Drilling Machine Operator's Certification:
Well sealed from land surface to ft.	This well was constructed under my direct supervision.  Materials used and information reported above are true to my
Diameter of well bore to bottom of seal in.	best knowledge and belief.
Diameter of well bore below seal in.	[Signed] Kahertw Lestrin Date 8-4 19
Number of sacks of cement used in well seal sacks	(Drilling Machine Operator)  Drilling Machine Operator's License No. /58
Number of sacks of bentonite used in well seal sacks	Drilling Machine Operator's License No.
Brand name of bentonite	Water Well Contractor's Certification:
Number of pounds of bentonite per 100 gallons	This well was drilled under my jurisdiction and this report is
of waterlbs./100 gals.	true to the best of my knowledge and belief.
Was a drive shoe used?  Yes No Plugs Size: location ft.	Name JONESES DRIVING CO INC
Did any strata contain unusable water?  Yes No	(Person, firm or corporation) (Type or print)  Address St At 2 Den 120 LEBANON OKE
Type of water? depth of strata	Address St 172 Den 720 LEBANON Che
Method of sealing strata off	[Signed] Be defined
Was well gravel packed?  Yes No Size of gravel:	(Water Well Contractor)
Gravel placed from ft. to ft.	Contractor's License No. 3/4 Date 8-4 , 1975