NOTICE TO WATER WELL CONTRACTOR The original and first copy of this report	
are to be filed with the PFORT (17520RT (17520RT (1752)	
WATER RESOURCES DEPARTMENT, C	
within 30 days from the date of well completion.	bove this line)
	H1100
(1) OWNER: Name City of Brownsvilles	(10) LOCATION OF WELL:
Address And An II	County LINN Driller's well number
Brownsulle Ore	<u>14 14 Section 3/ T./33 R.210 W.M.</u>
(2) TYPE OF WORK (check):	Bearing and distance from section or subdivision corner
New Well 🎲 Deepening 🗌 Reconditioning 🗋 Abandon 🗋	
If abandonment, describe material and procedure in Item 12.	(11) WATER LEVEL: Completed well.
(3) TYPE OF WELL: (4) PROPOSED USE (check):	Depth at which water was first found /O ft.
Rotary 🖌 Driven 🗆 Domestic 🗆 Industrial 🗆 Municipal 🖌	
Dur Dored D Irrigation D Test Well Cother	Artesian pressure lbs. per square inch. Date
CASING INSTALLED: Threaded	ibs. per square men. Date
CASING INSTALLED: Threaded □ Welded ↓ "Diam. fromft. toGageSO	(12) WELL LOG: Diameter of well below casing
"Diam. from	Depth drilled 30 ft. Depth of completed well 30 ft.
Diam. from ft. to ft. Gage	Formation: Describe color, texture, grain size and structure of materials; and show thickness and nature of each stratum and aquifer penetrated,
PERFORATIONS: Perforated? Ves UNO	with at least one entry for each change of formation. Report each change in
Type of perforator used Orch Cut	position of Static Water Level and indicate principal water-bearing strata.
Size of perforations 4 in. by 5 in.	MATERIAL From To SWL
75 perforations from 12 ft. to 21 ft.	Sand & Omul
12 perforations from 21 ft. to 29 ft.	Brown broken basalt 18 30
perforations from ft. to ft.	
(7) SCREENS: Well screen installed? Yes Y No	
Manufacturer's Name	
Type	
Diam Slot size Set from ft. to ft.	
Diam	
(8) WELL TESTS: Drawdown is amount water level is lowered below static level	· · · · · · · · · · · · · · · · · · ·
Was a pump test made? X Yes D No If yes, by whom?	
d: 13.3 gal./min. with 8 ft. drawdown after 4 hrs.	
" <u>"</u> "	
И И И И И И И И И И И И И И И И И И И	
Bailer test gal./min. with ft. drawdown after hrs.	
sian flow g.p.m.	
perature of water Depth artesian flow encountered ft.	Work started 4-3-78 19 Completed 4-10-78 19
(9) CONSTRUCTION:	Date well drilling machine moved off of well 4-10-78 19
Well seal-Material used Coment	Drilling Machine Operator's Certification:
Well sealed from land surface toft.	This well was constructed under my direct supervision. Materials used and information reported above are true to my
Diameter of well bore to bottom of seal in.	best knowledge and belief.
Diameter of well bore below seal	[Signed] Claude Jrby Date 5-15, 1978
Number of sacks of cement used in well seal 33 sacks How was cement grout placed? POUNIA	(Drilling Machine Operator) Drilling Machine Operator's License No. 1133
Brout pieces in a state left	
and a second	Water Well Contractor's Certification:
Maria a la companya a secondaria a secondaria a secondaria a secondaria de la companya de	This well was drilled under my jurisdiction and this report is true to the best of my knowledge and belief.
Was a drive shoe used? Did any strate contain unusely material Did any strate contain unusely be any strate contain unusely	Name Ourt Jones
Did any strata contain unusable water? Yes No Type of water? depth of strata	(Person, firm or corporation) (Type or print)
Type of water? depth of strata Method of sealing strata off	Address \$1400 SUMMAN WUY KUNANON ON
Was well gravel packed? St Yes 🗆 No Size of gravel: 12	[Signed] Berl HOND (Water Well Contractor)
Gravel placed from 12 ft. to 30 ft.	Contractor's License No. 514 Date 5-15-78
(USE ADDITIONAL SH	

3P*45656-119