NOTICE TO WATER WELL CONTRACTOR
The original and first copy
of this report are to be
filed with the

STATE ENGINEER, SALEM, OREGON 97870 within 30 days from the date of well completion.

WATER WELL REPORT CEIVED

STATE OF OREGON

JUL 1 0 1975 tate Well No. 445,

No. 145/3W-31

(Please type or print) ATER RESOURCES TREPTIMIT No.

(Do not write above this line) SALEM, OREGON

Concert

(1) OWNER:	(10) LOCATION OF WELL:		
Name Ray Hancock	County Linn Driller's well number		
Address PO Box 228, Halsey, Ore.	1/ 1/ Continue and many		
The state of the s	Bearing and distance from section or subdivision corner		
(2) TYPE OF WORK (check):	Highway 228	on corner	
New Well 💹 Deepening 🗌 Reconditioning 🗌 Abandon 🖂	ALL BALWOON CO.		
If abandonment, describe material and procedure in Item 12.	(11) WATER LEVEL: Completed well.		
(3) TYPE OF WELL: (4) PROPOSED USE (check):	Double of which was		
Rotary Driven Domestic X Industrial Municipal Domestic X			
Dug ☐ Bored ☐ Irrigation ☐ Test Well ☐ Other ☐		surface. Date 6-13-75	
	Artesian pressurelbs. per square inch. Date		
CASING INSTALLED: Threaded Welded	(12) WELL LOG: Diameter of well below casing8.11		
8	Depth drilled 49 ft. Depth of completed well 49 ft.		
"Diam. fromft. to 491051/21ft. Gage	1 1427		
ft. toft. Gage	Formation: Describe color, texture, grain size and structure of materials; and show thickness and nature of each stratum and aquifer penetrated,		
PERFORATIONS: Perforated? Yes No.	with at least one entry for each change of formation. Report each change in position of Static Water Level and indicate principal water-bearing strata.		
Type of perforator used Acetylene Torch	MATERIAL	From To SWL	
Size of perforations $3/8$ in. by 12 in.	Top SOil	0 2	
50 perforations from XXXXXII ft. to 40 02 ft.	Brown Clay	2 16	
perforations from 3.7 ft. to 4.9.1.0.51/211 ft.	Brown Clay & Gravel	16 25	
perforations from ft. to ft.	Dirty Gravel	25 29	
(7) SCREENS: Well screen installed? Yes No	Brown Sand & Gravel	29 46	
Manufacturer's Name	Brown Sandy Clay &	46 49	
Type Model No	Gravel		
Diam. Slot size Set from ft. to ft.	200		
Diam. Slot size Set from ft. to ft.			
(0) WITH I MECING Droudent to			
(8) WELL TESTS: Drawdown is amount water level is lowered below static level		-	
Was a pump test made? Yes No If yes, by whom?			
Yield: gal./min. with ft. drawdown after hrs.			
H H H H H H H H H H H H H H H H H H H		,	
" " " " " " " " " " " " " " " " " " "			
Bailer test 132 gal./min. with 2 ft, drawdown after 1 hrs.			
Artesian flow g.p.m.			
perature of water Depth artesian flow encountered ft.	Work started 6-9 19 75 Complete	d 6-13 19 75	
(9) CONSTRUCTION:	Date well drilling machine moved off of well	6-14 19 75	
Well seal—Material usedBentonite	Drilling Machine Operator's Certification:		
Well sealed from land surface to	This well was constructed under my	direct supervision.	
Diameter of well bore to bottom of seal 12 in.	Materials used and information reported best knowledge and belief.	above are true to my	
Diameter of well bore below seal in.	[Signed]	00106-14 1075	
Number of sacks of cement used in well sealsacks	(Drilling Machine Operator)		
Number of sacks of bentonite used in well seal 4 sacks	Drilling Machine Operator's License No. 436		
Brand name of bentonite Cent. Ore. Benton & Volclay	Woton Wall Control of the Control		
Number of pounds of bentonite per 100 gallons	Water Well Contractor's Certification:		
of waterlbs./100 gals.	This well was drilled under my jurisdiction and this report is true to the best of my knowledge and belief.		
Was a drive shoe used? Tyes \(\subseteq \text{No Plugs} \) Size: location ft.	Name Merle Warren Well Drilling		
Did any strata contain unusable water? Yes No	(Person, firm or corporation)	(Type or print)	
Type of water? depth of strata	Address Rf 1, Box 84 Tangent, Ore. 97389		
Method of sealing strata off	[Signed] Merly Carre	h	
Was well gravel packed? Yes Kno Size of gravel:	(Water Well Contra	A	
Gravel placed fromft. toft.	Contractor's License No. 182 Date	6-14 1075	