NOTICE TO WATER WELL CONTRACTOR  The original and first copy of this report are to be filed with the state of	tario domi	135 34	36aa )-25	
STATE ENGINEER, SALEM, OREGON 9731 (Please type	or print) STATE ENGINEER Permit No ove this line) SALEM, ORECON - \- \- \- \- \- \- \- \- \- \- \- \- \	6-62	56 e	
	(10) LOCATION OF WELL:		,	
(1) OWNER:	County Linn Driller's well number			
Name Gene Thornton	County			
Address Rt. 1, Box 287, Brownsville, Ore.				
(2) TYPE OF WORK (check):	Bearing and distance from section or subdivision	on corner		
New Well Deepening Reconditioning Abandon I If abandonment, describe material and procedure in Item 12.				
	(11) WATER LEVEL: Completed well.			
(3) TYPE OF WELL: (4) PROPOSED USE (check):	Depth at which water was first found 22 ft.			
Rotary Driven Domestic Mindustrial Municipal Domestic Mindustrial Municipal Domestic	Static level 8 ft. below land surface. Date 10-20-73			
Cable Y Jetted	Artesian pressure lbs. per squar	per square inch. Date		
CACTAGO TAYOMAT I ED.			0 **	
CASING INSTALLED: Threaded Welded X	(12) WELL LOG: Diameter of well k	elow casing	0''	
8 "Diam. from +1' ft. to 202 02/4! Gage 250Wall	Depth drilled 225 ft. Depth of compl	eted well	25 ft.	
"Diam. from	Formation: Describe color, texture, grain size	and structure of	materials;	
	and show thickness and nature of each strature with at least one entry for each change of formations.	tion. Report eac	h change in	
PERFORATIONS: Perforated? [X Yes ] No.	position of Static Water Level and indicate prin	cipal water-bea	ring strata.	
Type of perforator used XX Acetylene Torch	MATERIAL	From To	swL	
Size of perforations ½ in. by 12 in.	Top Soil	0 3		
66 perforations from 189 ft. to 200 ft.	Brown Clay	3 10		
	Silty Blue Clay	10 14		
perforations from ft. to ft.	Blue Clay & Gravel	14 19		
perforations from ft. to ft.	Brown Sand & Gravel	19 22		
(7) SCREENS: Well screen installed?   Yes X No	Blue Clay & Gravel	22 26		
Manufacturer's Name	Yellowish Brown Clay	26 45		
Type Model No	Reddish Brown Clay	45 55		
Diam. Slot size Set from ft. to ft.	Light Brown Clay	55 89		
Diam Slot size Set from ft. to ft.	Light Grey Clay	89 95		
(2) WELL TESTS. Drawdown is amount water level is	Brown Clay	95 133		
(8) WELL TESTS:  Drawdown is amount water level is lowered below static level	Dark Brown Clay	133 147		
Was a pump test made? X Yes No If yes, by whom? Self	Red Clay	147 178		
Yield: 60 gal./min. with 192 ft. drawdown after 1½ hrs.	Brown Clay & Brown Shale	<del>178 197</del>		
" " "	Hard Blue Shale	197 225	···	
" " "		<u> </u>		
50 88		<del>                                     </del>		
		<del>                                     </del>		
Artesian flow g.p.m.				
Depth artesian flow encountered ft.	Work started 10-8 19 73 Complet			
(9) CONSTRUCTION:	Date well drilling machine moved off of well	10-20	19 73	
	Drilling Machine Operator's Certification			
Well seal—Material usedBentonite	This well was constructed under my	direct sup	ervision.	
Well sealed from land surface toft.  Diameter of well bore to bottom of sealfi.	Materials used and information reported best knowledge and belief.		-	
Diameter of well bore below seal	[Signed] (Drilling Machine Operator)	Date-10-	3/1972	
Number of sacks of cement used in well sealsacks	(Drilling Machine Operator)	<b></b>	,	
Number of sacks of bentonite used in well sealsacks	Drilling Machine Operator's License No.	4-36		
Brand name of bentonite Oregon Bentonite				
Number of pounds of bentonite per 100 gallons	Water Well Contractor's Certification:			
of water	This well was drilled under my jurisd true to the best of my knowledge and be	liction and thi lief.	s report is	
Was a drive shoe used? ★ Yes No Plugs Size: location ft.	Name Merle Warren Well Drilling (Type or print)			
Did any strata contain unusable water?   Yes X No	(Person, firm or corporation)	(Type or	print)	
Type of water? depth of strata	Address Rt. 1 Box 84, Tangen	t, Ore. 9	7389	
	Mark. 11	11.		
Method of sealing strata off  Was well grovel posked? [7] Ves W. No. Size of gravel:	[Signed] (Water Well Conf			
Was well gravel packed? Tyes No Size of gravel:	Contractor's License No. 182 Date	10/3	1 19.7.3	
Gravel placed from ft. to ft.	1		<del></del>	


## NOTICE TO WATER WELL CONTRACTOR The original and first copy of this report are to be filed with the DEC 1 0 10 74 STATE OF OREGON

Gravel placed from ...

STATE OF OREGON (Please type or print)

STATE OF OREGON
STATE ENGINEER, SALEM, OREGON 97310 1 8 1974 STATE OF OREGON
(Please type or print) Conference of well completion.

STATE OF OREGON
(Please type or print) Conference of well completion.



SALEM, OREGON	tor loca	Wion 5	see m	ap 12
(1) OWNER:	(10) LOCATION OF WELL:			
Name Gene Thornton	County Linn Driller's well n	umber	•	_
Address Rt. 1, Box 287, Brownsville, Ore.	1/4 Section 25 T. 13S	R. 3W	Ÿ	W.M.
	Bearing and distance from section or subdivis			
(2) TYPE OF WORK (check):	Bearing and distance from Bearing of Subdivisi	1011 COLLICI	-	
New Well Deepening Reconditioning Abandon				
If abandonment, describe material and procedure in Item 12.	(11) THE A PRINT OF 1 1 1	17		
	(11) WATER LEVEL: Completed v	vell.		
(3) TYPE OF WELL: (4) PROPOSED USE (check):	Depth at which water was first found 22			ft.
Rotary Driven Domestic M Industrial Municipal Cable Description	Static level 8 ft. below land	surface. I	Date 10	)-20-7
Dug	Artesian pressure * lbs. per squa	re inch.	Date **	***
CASING INSTALLED: Threaded □ Welded	420)			
8 " Diam. from +1 ft. to 202 02 1 Gage 250 Wall				_
ft. to ft. Gage	Depth drilled 225 ft. Depth of comp	ieted well	225	) . ft.
	Formation: Describe color, texture, grain size and show thickness and nature of each stratu			
	with at least one entry for each change of form:	ation. Repo	ort each o	change in
PERFORATIONS: Perforated? K Yes I No.	position of Static Water Level and indicate pri	icipal wat	er-bearir	ıg strata.
Type of perforator used Acetylene Torch	MATERIAL	From	То	swL
Size of perforations ½ in. by 12 in.	Top Soil	0	3	
66	Brown Clay	3	10	
perforations from ft. to ft.	Silty Blue Clay	10	14	
perforations from ft. to ft.	Blue Clay & Gravel	14	19	
(E) CODEDIC	Brown Sand & Gravel	19	22	
(7) SCREENS: Well screen installed?   Yes X No	Blue Clay & Gravel	22	26	
Manufacturer's Name	Yellowish Brown Clay	26	45	
Type Model No.	Reddish Brown Clay	45	55	
Diam Slot size Set from ft. to ft.	Light Brown Clay	55	89	
Diam. Slot size Set from ft. to ft.	Light Gray Clay	89	95	
(8) WELL TESTS: Drawdown is amount water level is lowered below static level	Brown Clay	95	133	
the state of the s	Dark Brown Clay	133	147	<u> </u>
Was a pump test made? KYes \( \) No If yes, by whom? Self	Red Clay	147	178	
Yield: 60 gal./min. with 192 ft. drawdown after 1½ hrs.	Brown Clay & Br Shale	178	197	<u> </u>
n n	Hard Blue Shale	197	225	
" " "		-		<u> </u>
Bailer test 50 gal./min. with 88 ft. drawdown after 71/hrs.				
Artesian flow g.p.m.		+		<b></b>
erature of water Depth artesian flow encountered ft.	Work started 10-8 19 73 Complete	ted 10-	20 -	19 73
	Date well drilling machine moved off of well		)-20	<sup>19</sup> 73
(9) CONSTRUCTION: Well seel-Material used Bentonite	72 271 27 11 0 4 1 0 4 1		·	
Went Scar-Material used	Drilling Machine Operator's Certification This well was constructed under my			iaian
Well sealed from land surface to ff.	Materials used and information reported	above a	are true	to my
Diameter of well bore to bottom of seal in.	best knowledge and belief.			-
Diameter of well bore below seal8in.	[Signed] (Drilling Machine Operator)"	Date1	.0-31.	., 197 <i>5</i>
Number of sacks of cement used in well seal sacks	Drilling Machine Operator's License No.			
Number of sacks of bentonite used in well seal	Driming machine Operator & Literise 110.	ارودايد		
Brand name of bentonite Oregon Bentonite	Water Well Contractor's Certification:			
Number of pounds of bentonite per 100 gallons	This well was drilled under my jurisc	liction an	d this r	eport is
of water lbs./100 gals.	true to the best of my knowledge and be	lief.	VALAD L	-2-010 10
Was a drive shoe used? XYes No Plugs Size: location ft.	Name Merle Warren Well Dri			•••••
Did any strata contain unusable water?  Yes X No	(Person, firm or corporation)		pe or pri	_
Type of water? depth of strata	Address Rt. 1. Box 84, Tangen	t, Ore	973	389
Method of sealing strata off	[Signed]			
Was well gravel packed? ☐ Yes W No Size of gravel:	(Water Well Cont	ractor)		

Contractor's License No. 182 Date 10-31 , 19.73