NOTICE TO WATER WELL CONTRACTOR The original and first copy of this report are to be filed with the	L-BERORT NC	
WATER RESOURCES DEPARTMENT, STATE OF	OREGON LIMM ate Well No.	35/3W-36
within 30 days from the date of well completion. WATER DESCRIPTION (Do not write all	I E A A A A Z J State Ferring No.)
Of well completion. WATER RESOURCES DEPT SALEM, OSEGUES.	1	
	(10) LOCATION OF WELL:	
Name City of Brownsulle	County LINA Driller's well number	
proumerate Ore.	14 14 Section 36 T./35	R. 310 W.M.
(2) TYPE OF WORK (check):	Bearing and distance from section or subdivision	n corner
New Well		
If abandonment, describe material and procedure in Item 12.	(11) YUANDO FENYINK CI I I	11
(3) TYPE OF WELL: (4) PROPOSED USE (check):	(11) WATER LEVEL: Completed well. Depth at which water was first found ft.	
Rotary Driven D Domestic D Industrial Municipal M	(1)	
Cable Jetted Johnston Industrial Municipal Page Bored Irrigation Test Well Other	5	
	Artesian pressure lbs. per square	inch. Date
CASING INSTALLED: Threaded Welded Welded	(12) WELL LOG: Diameter of well b	elow casing 8"
8 "Diam from O ft. to Z6 ft. Gage 1250	Depth drilled 26 ft. Depth of comple	eted well 26 ft.
	Formation: Describe color, texture, grain size a	nd structure of materials;
DEDEODATIONS.	and show thickness and nature of each stratur with at least one entry for each change of format position of Static Water Level and indicate princ	ion. Report each change in
Type of perforator used Orch	MATERIAL	From To SWL
Size of perforations 14 in. by 5 in.	700501	0 1
130 perforations from 16 ft. to 26 ft.	sand & gravel	1 35/3
perforations from ft. to ft.	Comented gravel	1573 26
perforations from ft. to ft.	3	
(7) SCREENS: Well screen installed? Yes No		
Manufacturer's Name		
Type Model No.		
Diam Slot size Set from ft. to ft.		
Diam Slot size Set from ft. to ft.		
(8) WELL TESTS: Drawdown is amount water level is lowered below static level		
Was a pump test made? ✓ Yes ☐ No If yes, by whom?		
d: gal./min. with ft. drawdown after hrs.		
Pump test pending " "		
<u>" </u>		
Bailer test gal./min. with ft. drawdown after hrs.		
sian flow g.p.m.		
nperature of water Depth artesian flow encountered ft.	Work started 4/10/98 19 Complete	1 4/11/18 19
(9) CONSTRUCTION:	Date well drilling machine moved off of well	4-11/1819
Well seal—Material used	Drilling Machine Operator's Certification:	
Well sealed from land surface to 12 ft.	This well was constructed under my	
Diameter of well bore to bottom of seal in.	Materials used and information reported a best knowledge and belief.	above are true to my
Diameter of well bore below seal	[Signed] Cloude Siby I	Date 5/15, 1978
Number of sacks of cement used in well seal sacks	(Drilling Machine Operator) Drilling Machine Operator's License No	
How was cement grout placed?POULLA	- Driving Machine Operator's Intense 140	
	Water Well Contractor's Certification:	
	This well was drilled under my jurisdiction and this report is	
Was a drive shoe used? Yes No Plugs Size: location ft.	true to the best of my knowledge and belief.	
Did any strata contain unusable water? Yes No	Name (Person, firm or corporation) / (Type or print)	
Type of water? depth of strata	Address 24400 Santiam H	ury Ubanon Ch
Method of sealing strata off	[Signed] But Janes	•
Was well gravel packed? Yes No Size of gravel: 2 Dea	(Water Well Contra	ctor)
Gravel placed from	Contractor's License No. 5.14 Date	5/18/18 , 19
(HEE ADDITIONAL CO	THE THE STREET,	