

NOTICE TO WATER WELL CONTRACTOR
The original and first copy of this report are to be filed with the

RECEIVED

WATER WELL REPORT LINN

WATER RESOURCES DEPARTMENT
SALEM, OREGON 97310
within 30 days from date of well completion.

081 31 1978

STATE OF OREGON
(Please type or print)

12989

State Well No. 135/5E-32

State Permit No.

SALEM, OREGON

(1) OWNER:

Name Willamette National Forest
Address P.O. Box 10607
Eugene, Oregon

(2) TYPE OF WORK (check):

New Well Deepening Reconditioning Abandon
If abandonment, describe material and procedure in Item 12.

(3) TYPE OF WELL:

Rotary Driven
Cable Jetted
Dug Bored

(4) PROPOSED USE (check):

Domestic Industrial Municipal
Irrigation Test Well Other

CASING INSTALLED:

Threaded Welded
" Diam. from 7 1/2 ft. to 3 3/8 ft. Gage 250
" Diam. from ft. to ft. Gage
" Diam. from ft. to ft. Gage

PERFORATIONS:

Perforated? Yes No.

Type of perforator used
Size of perforations in. by in.
..... perforations from ft. to ft.
..... perforations from ft. to ft.
..... perforations from ft. to ft.

(7) SCREENS:

Well screen installed? Yes No

Manufacturer's Name
Type Model No.
Diam. Slot size Set from ft. to ft.
Diam. Slot size Set from ft. to ft.

(8) WELL TESTS:

Drawdown is amount water level is lowered below static level

Was a pump test made? Yes No If yes, by whom?
Yield: gal./min. with ft. drawdown after hrs.
" " " " "
" " " " "
Bailer test 20 gal./min. with 17 ft. drawdown after 2 hrs.
Artesian flow g.p.m.
Temperature of water Depth artesian flow encountered ft.

(9) CONSTRUCTION:

Well seal—Material used Cement
Well sealed from land surface to 18 ft.
Diameter of well bore to bottom of seal 10 in.
Diameter of well bore below seal 6 in.
Number of sacks of cement used in well seal 9 sacks
How was cement grout placed? MIXED & PRESS
grouted
Was a drive shoe used? Yes No Plugs Size: location ft.
Did any strata contain unusable water? Yes No
Type of water? depth of strata
Method of sealing strata off
Was well gravel packed? Yes No Size of gravel:
Gravel placed from ft. to ft.

(10) LOCATION OF WELL:

County LINN Driller's well number 5878
1/4 1/4 Section 32 T. 19S R. 5E W.M.

Bearing and distance from section or subdivision corner
HOUSE ROCK CAMP GROUND

(11) WATER LEVEL: Completed well.

Depth at which water was first found 36 ft.
Static level 21 ft. below land surface. Date 9/2/78
Artesian pressure lbs. per square inch. Date

(12) WELL LOG:

Diameter of well below casing Six
Depth drilled 53 ft. Depth of completed well 53 ft.

Formation: Describe color, texture, grain size and structure of materials; and show thickness and nature of each stratum and aquifer penetrated, with at least one entry for each change of formation. Report each change in position of Static Water Level and indicate principal water-bearing strata.

MATERIAL	From	To	SWL
SOIL	0	4	
GRAVEL & CLAY, yellow	4	15	
SAND & CLAY, blue	15	36	
BASALT, black, broken	36	38	21
WATER STRATUM			
BASALT, black	38	53	

Work started Aug 31 1978 Completed Sept 2 1978
Date well drilling machine moved off of well SEPT 2 1978

Drilling Machine Operator's Certification:

This well was constructed under my direct supervision. Materials used and information reported above are true to my best knowledge and belief.
[Signed] Froy W. Mutschler Date 9/20, 1978
(Drilling Machine Operator)
Drilling Machine Operator's License No. 80

Water Well Contractor's Certification:

This well was drilled under my jurisdiction and this report is true to the best of my knowledge and belief.
Name M-H Well Drilling Inc.
(Person, firm or corporation) (Type or print)
Address 4051 Holly Acres St. NE
Corvallis, Oregon
[Signed] Froy W. Mutschler
(Water Well Contractor)
Contractor's License No. 297 Date Sept 20, 1978