NOTICE TO WATER WELL CONTRACTOR The original and first copy of this report are to be filed with the RECEI WATER WELL REPORT are to be filed with the WATER RESOURCES DEPARTMENT,

SALEM, OREGON 97310 within 30 days from the date NOV 2.1978 (Please type or print)

ſo.	135/5E-32	

of well completion.

WATER RESOURCES DEFINE above this line)

State Well N State Permit No.

(1) OWNER: SALEM, UNEDO	(10) LOCATION OF WELL:	
Name WILL Amette NATIONAL FOREST	1-1-1-	18
Address P.O. Box 10607	24 2	<u> </u>
EUGENE, OREGON	4 14 Section 32 T. /35 R. 5E	W.M.
(2) TYPE OF WORK (check):	Bearing and distance from section or subdivision corner	
New Well ☑ Deepening ☐ Reconditioning ☐ Abandon ☐	House ROCK CAMP GrouND	'
If abandonment, describe material and procedure in Item 12.	(11) THAMPIN T THEFT OF THE	
(3) TYPE OF WELL: (4) PROPOSED USE (check):	(11) WATER LEVEL: Completed well.	
Potony Fin Dairen D	Depth at which water was first found	ft.
Cable	Static level ft. below land surface. Date	<u> 31/16</u>
Dug Bored Irrigation Test Well Other	Artesian pressure lbs. per square inch. Date	•
CASING INSTALLED: Threaded Welded For the Diam from +2 ft. to +6 ft. Gage 250	(12) WELL LOG: Diameter of well below casing S. Depth drilled 53 ft. Depth of completed well 25	71X ft.
" Diam. from ft. to ft. Gage	Formation: Describe color, texture, grain size and structure of r	
" Diam. from ft. to ft. Gage	and show thickness and nature of each stratum and aquifer ne	enetrated
PERFORATIONS: Perforated? Yes Yo.	with at least one entry for each change of formation. Report each position of Static Water Level and indicate principal water-bearing	change in ng strata.
Type of perforator used	MATERIAL From To	SWL
Size of perforations in. by in.	5016 . 0 4	SWL
perforations fromft. toft.	SANT GRAVEL & Boulders & 17	
perforations from ft. to ft.	GRAVEL SAND 17 37	
perforations from ft. to ft.	BASALT, black, broken 37 40	R
	WATER STRATUM	
(7) SCREENS: Well screen installed? Yes No	BASALT, BLACK, W/OTZ 10 53	
Manufacturer's Name		
Type Model No		
Diam. Slot size Set from ft. to ft.		
Diam Slot size Set from ft. to ft.		
(8) WELL TESTS: Drawdown is amount water level is lowered below static level		
Was a pump test made? Yes No If yes, by whom?		
Yield: gal./min. with ft. drawdown after hrs.		
" "		
Bailer test 25 gal./min. with 32 ft. drawdown after 2 hrs.		
Artesian flow g.p.m.		
perature of water Depth artesian flow encountered ft.	Work started H119 29 1978 Completed H11931	1973
(9) CONSTRUCTION:	Date well drilling machine moved off of well Ang 31	1978
Well seal—Material used	Drilling Machine Operator's Certification:	
Well sealed from land surface toft.	This well was constructed under my direct super	vision.
Diameter of well bore to bottom of sealin.	Materials used and information reported above are true best knowledge and belief	to my
Diameter of well bore below seal in.	[Signed] Myll Machine Operator) Date 120	19/3
Number of sacks of cement used in well sealsacks		, 20.2
Now was cement group placed? /// XED 7 7855	Drilling Machine Operator's License No	
GROUTED	Water Well Contractor's Certification:	
	This well was drilled under my jurisdiction and this re	enont in
Vas a drive shoe used? ☑ Yes ☐ No Plugs Size: location ft.	true to the best of my knowledge and belief.	
oid any strata contain unusable water? Yes No No Plugs Size: location	Name // H WELL Drilling INC	
	4051 Holly ACRES 34 NE Type or prin	ıt)
	Address CORVALLIS Oregon	
Method of sealing strata off	[Signed] Loroy W Mulochler	<i>;</i>
Vas well gravel packed? ☐ Yes ☑ No Size of gravel:	(Water Well Contractor)	4049.40
ravel placed from ft. to ft.	Contractor's License No. 35 Date Date	10/8