NOTICE TO WATER WELL CONTRACTOR

The cricinal and first copy
of this report are to be
filed with the

STATE ENGINEER, SALEM 10, OREGON
within 30 days from the date

MAR 28 1963 STATE OF OREGON (Please type or print)

State Well No. 14/3w-4

of well completion.	State Permit No.	*******
(1) OWNER:	(11) WELL TESTS: Drawdown is amount water lev	
Name Harold Pugh		ei is
Address	Was a pump test made? ☐ Yes ☐ No If yes, by whom? Yield: gal./min. with ft. drawdown after	
Halsey, Oregon	yield: gal./min. with ft. drawdown after	hrs.
	" " "	,,
(2) LOCATION OF WELL:	Bailer test 80 gal./min. with 10 ft. drawdown after	l hrs.
County Linn Driller's well number	Artesian flow g.p.m. Date	<u> </u>
Received and distance of the T. 14S R. 3W W.M.	Temperature of water Was a chemical analysis made?	Ves Fl No
Bearing and distance from section or subdivision corner Halsey-Brownsville Market Road		TCD TEL INO
marboy -Drownsville market hoad	(12) WELL LOG: Diameter of well below casing	8u
The state of the s	Depth drilled 72 ft. Depth of completed well	72 ft.
The state of the s	Formation: Describe by color, character, size of material and str show thickness of aquifers and the kind and nature of the mate stratum penetrated, with at least one entry for each change of	ucture, and
- 1 - 1 - 1 - 1 - 1 - 1 - 1 - 1 - 1 - 1	stratum penetrated, with at least one entry for each change of	formation.
	MATERIAL FROM	TO
TYPE OF WORK (check):	Clay	9
Well		28
If abandonment, describe material and procedure in Item 12.	Water Gravel 28	45
(4) PROPOSED USE (check): (5) TYPE OF WELL		55
2	Black Sand 55	60
Irrigation Test Well Other Cable Jetted	Sand & Gravel 60	66
Dug Bored	Blue Clay 66	72
(6) CASING INSTALLED: Threaded □ Welded □		12
8 "Diam. from 0 ft. to 71 ft. Gage 22#		
"Diam. fromft. toft. Gage		
"Diam. fromft. toft. Gage		
(7) PERFORATIONS: Perforated?X□ Yes □ No		
Type of perforator used Acetylene Torch		
Size of perforations 1/4 in. by 12 in.		
20 perforations from 58 ft. to 68 ft.		
perforations from ft. to ft.		
perforations fromft. toft.		
perforations from ft. to ft.		
perforations from ft. to ft.		
(8) SCREENS: Well screen installed ☐ Yes ☐ No		 -
nufacturer's Name		
Model No.		
Diam ft. to ft.	Work storted 3-14 1963. Completed 7 20	
Diam Slot size Set from ft. to ft.	Date well drilling machine moved off of well 3-27	$\frac{19.63}{10.63}$
(9) CONSTRUCTION:		¹⁹ _63
Well and Medical Control of the Cont	(13) PUMP: 7, , , , , , , , , , , , , , , , , , ,	N
Well seal—Material used in seal	Manufacturer's Name (Mullial 1144)	ري
Tt. Was a packer used?	Type 5 174-6 5 84 10/4-6/12 HP	5
Diameter of well bore to bottom of seal	Window Will Could be a second	
Were any loose strata cemented off? Yes Y No Depth	Water Well Contractor's Certification:	
Was a drive shoe used? Y Yes D No	This well was drilled under my jurisdiction and this true to the best of my knowledge and belief.	report is
Was well gravel packed? ☐ Yes ¶ No Size of gravel:		
Gravel placed fromft. toft.	NAME Merle E. Warren, Well Drillin	g
Did any strata contain unusable water? Yes XNo	(Person, firm or corporation) (Type or print)	
Type of water? Depth of strata Method of sealing strata off	Address Rt. 1, Box 85, Tangent, Ore	gon
	Drilling Machine Operator's License No	
(10) WATER LEVELS:		•••••••••••
tatic level 3 ft. below land surface Date 3 20 63	[Signed] (Water Well Contractor)	
artesian pressure lbs. per square inch Date	3/25	1.5
(USE ADDITIONAL SI		, 1912.5