NOTICE TO WATER WELL CONTRACTOR

The original and first copy of this report are to be filed with the

WATER WELL REPORT

LINN 13556 State Well No. 14/3 w - 4 D

STATE ENGINEER, SALEM, OREGON 9731 Within 30 days from the 100 of well completion.

(Please type or print)
not write above this line)

State	Permit	Nο	

SEP 23 1300	
(1) OWNER: STATE ENGINEER Name Dale PenSALEM CREGON	(11) LOCATION OF WELL:
	County Linn Driller's well number 1/1/3W-/1D
Dettil a Company	1/4 . 1/4 Section T. R. W.M.
(2) TYPE OF WORK (check):	Bearing and distance from section or subdivision corner
New Well XI	
Hew Well □ Deepening □ Reconditioning □ Abandon □ If abandonment, describe material and procedure in Item 12.	
Rotary Driven D	(12) WELL LOG: Diameter of well below casing 6
Rotary Driven Domestic Industrial Municipal Dug Bored IIII Test Well Other	Depth drilled 63 ft. Depth of completed well 63 ft.
	Formation: Describe color, texture, grain size and structure of materials;
CASING INSTALLED: Threaded Welded M 6 5/8, Diam. from 2/3+0 ft. to 63 ft. Gage . 250	and show thickness and nature of each stratum and asset as
"Diam. fromft. toft. Gage	MATERIAL From To SWL
" Diam. from ft. to ft. Gage	Yellow clay 0 7/1
PERFORATIONS: Perforated? Yes No.	Muddy gravel 14 36
Type of perforator used	Clean gravel 36 38
Size of perforations in. by in.	Blue clay 38 /17
perforations from ft. to ft.	Coarse sand 17 50
perforations from ft. to ft.	Sandy blue clay 50 62
perforations from ft. to ft.	Small gravel & sand 62 63
perforations from ft. to ft.	
perforations fromft. toft.	
(7) CODEENG	, , , , , , , , , , , , , , , , , , ,
(7) SCREENS: Well screen installed? ☐ Yes ♣ No	
Manufacturer's Name	
Type Model No. Diam. Slot size Set from ft. to ft.	
Diam. Slot size Set from ft. to ft. Diam. Slot size ft. to ft.	
(8) WATER LEVEL: Completed well.	
Static level 10 ft. below land surface Date 9/21/68	
A sian pressure _ lbs. per square inch Date	
lowered below static level	
Was a pump test made? ☐ Yes 🋣 No If yes, by whom?	Work started 9/18 19 68 Completed 9/00/49 19
Yield: gal./min. with ft. drawdown after hrs.	27 10 10 00 completed 9/20/88 19
" " "	Date well drilling machine moved off of well 9/21/68 19
	Drilling Machine Operator's Certification:
Bailer test 25 gal./min. with 20ft. drawdown after 1 hrs.	This well was constructed under my direct supervision. Materials used and information reported above are true to my best
Artesian flow g.p.m. Date	knowledge and belief.
Temperature of water Was a chemical analysis made? ☐ Yes ☐ No	[Signed] / Machine Operator) 19.68
(10) CONSTRUCTION:	1
Well seal-Material usedClay	Drilling Machine Operator's License No. 63
Depth of seal 18	Water Well Contractor's Certification:
Diameter of well bore to bottom of seal in.	This well was drilled under my jurisdiction and this report is
Were any loose strata cemented off? Yes No Depth	true to the best of my knowledge and belief.
Was a drive shoe used? X□ Yes □ No	NAME Harry A. Robinson (Person, firm or corporation) (Type or print)
Did any strata contain unusable water? Yes No	221/1 Front NE Golom Committee
Type of water? depth of strata	Address 2214 Front NE Salem, Ore.
Method of sealing strata off	[Signed] Alary of Notingen.
Was well gravel packed? ☐ Yes ¾ No Size of gravel:	(Water Well Contractor)
Gravel placed from ft. to ft.	Contractor's License No. 22 Date 9/22/68 19