

NOTICE TO WATER WELL CONTRACTOR

The original and first copy of this report are to be filed with the

WATER WELL REPORT

LYNN 13705

STATE ENGINEER, SALEM, OREGON 97301 within 30 days from the date of well completion.

STATE OF OREGON

(Please type or print)

Do not write above this line

State Well No. 444W-1

State Permit No.

RECEIVED SEP 5 1969 STATE ENGINEER SALEM OREGON

(1) OWNER:

Name City of Halsey Address Halsey, Oregon

(2) TYPE OF WORK (check):

New Well [x] Deepening [ ] Reconditioning [ ] Abandon [ ]

If abandonment, describe material and procedure in Item 12.

(3) TYPE OF WELL:

Rotary [ ] Driven [ ] Cable [x] Jetted [ ] Bored [ ]

(4) PROPOSED USE (check):

Domestic [ ] Industrial [ ] Municipal [x] Irrigation [ ] Test Well [ ] Other [ ]

(5) CASING INSTALLED:

12" Diam. from +1 ft. to 199 ft. Gage 250"

PERFORATIONS:

Perforated? [x] Yes [ ] No

Type of perforator used Miles knife Size of perforations 3/4 in. by 3 in. 300 perforations from 40 ft. to 70 ft. 100 perforations from 85 ft. to 95 ft.

(7) SCREENS:

Well screen installed? [ ] Yes [x] No

Manufacturer's Name Type Diam. Slot size Set from ft. to ft.

(8) WATER LEVEL: Completed well.

Static level 14 ft. below land surface Date 8/28/69 Artesian pressure lbs. per square inch Date

(9) WELL TESTS:

Drawdown is amount water level is lowered below static level

Was a pump test made? [x] Yes [ ] No If yes, by whom? W.W. 156 gal./min. with 32 ft. drawdown after 1 hrs. 200 " 58 " 5 " 200 " 66 " 8 "

(10) CONSTRUCTION:

Well seal—Material used Cement Depth of seal 20 ft. Diameter of well bore to bottom of seal 1.6 in. Were any loose strata cemented off? [ ] Yes [ ] No Depth Was a drive shoe used? [x] Yes [ ] No Did any strata contain unusable water? [ ] Yes [x] No Type of water depth of strata Method of sealing strata off Was well gravel packed? [ ] Yes [x] No Size of gravel: Gravel placed from ft. to ft.

(11) LOCATION OF WELL:

County LYNN Driller's well number 1/4 Section 1 T. 145 R. 4 W W.M. Bearing and distance from section or subdivision corner

(12) WELL LOG:

Diameter of well below casing 12"

Depth drilled 200 ft. Depth of completed well 200 ft.

Formation: Describe color, texture, grain size and structure of materials; and show thickness and nature of each stratum and aquifer penetrated, with at least one entry for each change of formation. Report each change in position of Static Water Level as drilling proceeds. Note drilling rates.

Table with columns: MATERIAL, From, To, SWL. Rows include Blue clay, Brown clay, Brown clay & small gravel, Fine large gravel, Brown cemented gravel, Fine sand & gravel - med., Brown cemented gravel, Blue sandy clay, Fine sandy clay & gravel, Blue sandy clay, Brown sandy clay, Gray sandy clay, Blue sandy clay, Brown sandy clay, Blue sand, Blue sandy clay.

Work started 8/4 1969 Completed 8/28 1969 Date well drilling machine moved off of well 8/28 1969

Drilling Machine Operator's Certification:

This well was constructed under my direct supervision. Materials used and information reported above are true to my best knowledge and belief.

[Signed] Frank Wilson Date 8/28 1969 (Drilling Machine Operator)

Drilling Machine Operator's License No. 404

Water Well Contractor's Certification:

This well was drilled under my jurisdiction and this report is true to the best of my knowledge and belief.

NAME W.W. Drilling & Pump Ser. (Person, firm or corporation) (Type or print)

Address 2320 MAIN - Springfield, OR

[Signed] Walt Wilson (Water Well Contractor)

Contractor's License No. 268 Date Aug. 28, 1969