NOTICE TO WATER WELL CONTRACTOR

The original and first copy of this report are to be filed with the

State Well No. 14/4w-6ad

STATE ENGINEER, SALEM, OREGON 97810 SALEM, OREGON Within 30 days from the date of well completion.

41 ft. Decp WEB

State Permit No.

(1) OWNER:	(11) WELL TESTS: Drawdown is amount to lowered below static le	water lev	el is
Name Elden Birky	Was a pump test made? Yes No If yes, by whom		
Address Rt. 1, Box 142			
Halsey, Oregon	" " "	TI GIOCI	<u>hrs.</u> .
(2) LOCATION OF WELL:	" " "		"
well !	Bailer test OO gal./min. with 7 1 ft. drawdo	wn after	η hrs.
County Linn Driller's well number	Artesian flow g.p.m. Date		
½ ½ Section 6 T. 14S R. 4W W.M.	Temperature of water Was a chemical analysis r	nade? 🔲 🖰	Yes 📝 No
Bearing and distance from section or subdivision corner	(12) WELL LOG: Diameter of well below car	sing	-
	Depth drilled 149 ft. Depth of completed well		
	Formation: Describe by color, character, size of material show thickness of aquifers and the kind and nature of t stratum penetrated, with at least one entry for each of	he materi hange of	al in each formation.
(3) TYPE OF WORK (check):	MATERIAL	FROM	то
T. T.	Top Soil	0	3
Well ② Deepening ☐ Reconditioning ☐ Abandon ☐ If abandonment, describe material and procedure in Item 12.	Brown Clay	3	18
	Gravel	18	35
(4) PROPOSED USE (check): (5) TYPE OF WELL:	Black Rock	35	42
Domestic 🔀 Industrial 🗌 Municipal 📋 Rotary 🔲 Driven 🗀	Broken Rock & Gravel	42	45,
Irrigation X Test Well □ Other □ Cable X Jetted □ - Dug □ Bored □	Blue Clay	45	65 Zm
(C) CACING INCOMALLED	Sand & Wood	. 65	75 %
(6) CASING INSTALLED: Threaded Welded W	Sand & Clay	75	127 8%
8 Diam. from ft. to130 ft. Gage 250Wall	Blue Clay	127	149 %
"Diam. fromft. toft. Gage			
"Diam. fromft. toft. Gage	Salt water		
(7) PERFORATIONS: Perforated? ★ Yes □ No	Sair water		
Type of perforator used Acetylene Torch			
Size of perforations 16 in. by 72 in.			,
		Γ	 .
perforations from ft. to ft.			· . ,
perforations fromft. toft.			
perforations from ft. to ft.			
perforations fromft. toft.			
(8) SCREENS: Well screen installed? ☐ Yes XNo			
Manufacturer's Name			
Model No.			<u> </u>
Diam Slot size Set from ft. to ft.	2.15 66	্বৰ্	
Diam. Slot size Set from ft. to ft.		<u>-26</u>	1966
(9) CONSTRUCTION:	Date well drilling machine moved off of well 2-26	<u> </u>	¹⁹ 66
(b) Constituention.	(13) PUMP:		
Well seal—Material used in seal Bentonite	Manufacturer's Name		
Depth of seal	Type:		
Diameter of well bore to bottom of seal			
Were any loose strata cemented off? 🗌 Yes 📉 No Depth	Water Well Contractor's Certification:		
Was a drive shoe used? 💯 Yes □ No	This well was drilled under my jurisdiction a	ind this	report is
Was well gravel packed? □XYes □ No Size of gravel:	true to the best of my knowledge and belief.		
Gravel placed from	NAME Merle Warren Well Drillin		
Did any strata contain unusable water? 🗖 Yes 🔲 No	(Person, firm or corporation) (Type or print)		
Type of water? depth of strata	Address Rt. 1, Box 85, Tangent.	, oreg	,on
Method of sealing strata off	Drilling Maching Operator's Ligense No	31 Z	
(10) WATER LEVELS:	Allahlas later		*************
Static level 70 ft. below land surface Date 2.25 66	[Signed] (Water Well Contractor)		
Static level 10 ft. below land surface Date 2-25-66 Artesian pressure lbs. per square inch Date	Contractor's License No. 192 Date 3	/	1/1
	A LODICHOTOPE LIGORES NO 3 VS TO45	-	10777