

NOTICE TO WATER WELL CONTRACTOR
The original and first copy
of this report are to be
filed with the

RECEIVED WATER WELL REPORT LINN
STATE OF OREGON JUN 23 1971
STATE ENGINEER SALEM, OREGON
(Please type or print)
(Do not write above this line)
14045

State Well No. 15/3W-17
State Permit No.

STATE ENGINEER, SALEM, OREGON 97310
within 30 days from the date
of well completion.

(1) OWNER:

Name ORVILLE PRALLE (R)
Address RTE # 1 BOX 62-E- HARRISBURG, OREGON

(2) TYPE OF WORK (check):

New Well Deepening Reconditioning Abandon
If abandonment, describe material and procedure in Item 12.

(3) TYPE OF WELL:

Rotary Driven
Cable Jetted
Dug Bored

(4) PROPOSED USE (check):

Domestic Industrial Municipal
Irrigation Test Well Other

CASING INSTALLED:

8" Diam. from 0 ft. to 35 ft. Gage .250
Threaded Welded

PERFORATIONS:

Perforated? Yes No.
Type of perforator used TORCH
Size of perforations 1/4 in. by 3 in.
36 perforations from 27 ft. to 35 ft.

(7) SCREENS:

Well screen installed? Yes No
Manufacturer's Name
Type Model No.
Diam. Slot size Set from ft. to ft.
Diam. Slot size Set from ft. to ft.

(8) WELL TESTS:

Drawdown is amount water level is lowered below static level
Was a pump test made? Yes No If yes, by whom?
Yield: gal./min. with ft. drawdown after hrs.
Bailer test 30 gal./min. with 0 ft. drawdown after 1 hrs.
Artesian flow g.p.m.
Temperature of water 51° Depth artesian flow encountered ft.

(9) CONSTRUCTION:

Well seal—Material used BENTONITE
Well sealed from land surface to 19 ft.
Diameter of well bore to bottom of seal 12 in.
Diameter of well bore below seal 8 in.
Number of sacks of cement used in well seal 002 sacks
Number of sacks of bentonite used in well seal 2 sacks
Brand name of bentonite YELLOWSTONE WESTERN
Number of pounds of bentonite per 100 gallons of water 133 lbs./100 gals.
Was a drive shoe used? Yes No Plugs Size: location ft.
Did any strata contain unusable water? Yes No
Type of water? depth of strata
Method of sealing strata off
Was well gravel packed? Yes No Size of gravel:
Gravel placed from ft. to ft.

(10) LOCATION OF WELL:

County LINN Driller's well number
1/4 Section 17 T. 15SR. 3W W.M.
Bearing and distance from section or subdivision corner

(11) WATER LEVEL: Completed well.

Depth at which water was first found 27 ft.
Static level 7 ft. below land surface. Date 5-12-71
Artesian pressure lbs. per square inch. Date

(12) WELL LOG:

Diameter of well below casing -0-
Depth drilled 35 ft. Depth of completed well 35 ft.

Formation: Describe color, texture, grain size and structure of materials; and show thickness and nature of each stratum and aquifer penetrated, with at least one entry for each change of formation. Report each change in position of Static Water Level and indicate principal water-bearing strata.

MATERIAL	From	To	SWL
BLACK SOIL	0	6	
SAND & GRAVEL	6	27	
COARSE GRAVEL	27	35	7 6

Work started 5-11-71 19 Completed 5-13-71 19
Date well drilling machine moved off of well 5-13-71 19

Drilling Machine Operator's Certification:

This well was constructed under my direct supervision. Materials used and information reported above are true to my best knowledge and belief.
[Signed] *John R. Budger* Date 5-16-71, 19...
(Drilling Machine Operator)
Drilling Machine Operator's License No. 747

Water Well Contractor's Certification:

This well was drilled under my jurisdiction and this report is true to the best of my knowledge and belief.
Name CARTER'S DRILLING & BIMP SERVICE
(Person, firm or corporation) (Type or print)
Address 325 So. 2ND ST., SPRINGFIELD, OREGON
[Signed] *James G. Carter*
(Water Well Contractor)
Contractor's License No. 126 Date 5-16-71, 19...