The original and first copy of this report are to be filed with the CER WELL REPORT 14186 State Well No. 15/4W-16 H of this report are to be filed with the STATE ENGINEER, SALEM, OREGON 97310 STATE OF OREGON within 30 days from the date of well completion. STATE ENGINEER type or print) G-3693 State Permit No. .. CLILVI Drawdown is amount water level is lowered below static level (11) WELL TESTS: (1) OWNER: City of Harrisburg Was a pump test made? Yes No If yes, by whom? WW Drilling Address Harrisburg, Oregon Yield: 300 gal./min. with 120ft. drawdown after 27 (2) LOCATION OF WELL: ft. drawdown after hrs. Bailer test gal./min. with County Lane LINA Driller's well number Artesian flow g.p.m. Date 1/4 Section /6 T. 185 Was a chemical analysis made? 🗌 Yes 👽 No Temperature of water Bearing and distance from section or subdivision corner (12) WELL LOG: Diameter of well below casing .... Depth drilled 400 ft. Depth of completed well 346 Formation: Describe by color, character, size of material and structure, and show thickness of aquifers and the kind and nature of the material in each stratum penetrated, with at least one entry for each change of formation. FROM MATERIAL (3) TYPE OF WORK (check): Gray white clay 10 0 Reconditioning [ Abandon [ New Well Deepening 🗌 Gray clay 10 ndonment, describe material and procedure in Item 12. Brown clay - pea gravel 14 Blue clay (4) PROPOSED USE (check): (5) TYPE OF WELL: Soft brown clay- very fine Rotary [ Driven □ Domestic | Industrial | Municipal 65 78 sand- water bearing Cable Jetted [ Irrigation [ Test Well [ Other Bored | 78 Dug 115 Soft blue clay 115 Black sand & gravel-(W B) 125 (6) CASING INSTALLED: Threaded | Welded \( \frac{350}{150} \) ft. Gage 3 Blue clay 125 135 Gray green clay 150 " Diam. from ...... ft. to ..... Blue clay 150 " Diam. from \_\_\_\_\_ft. to \_\_\_\_\_ft. Gage ... Black sand very fine some (7) PERFORATIONS: Perforated? Yes 🗌 No **178**. water - static head 25' 190 Mills knife 190 250 Type of perforator used Blue clay - very sticky Size of perforations in. by 2 Very fine sand, blue clay 250 some water, lots of wood 110 320 275 Dark gray cláy - fine sand 290 .. perforations from ... Blue clay very sticky perforations from .. ... perforations from .. Coarse black sand with buck shot gravel ... perforations from ...... Blue clay (8) SCREENS: Well screen installed? 🗌 Yes ⋤ No Manufacturer's Name ... ..... Slot size ...... Set from ..... ft. to ..... Work started 6/29/66 19 Completed 8/6/66 19 Date well drilling machine moved off of well (9) CONSTRUCTION: (13) PUMP: Well seal—Material used in seal \_\_\_\_Bentonite Manufacturer's Name Depth of seal \_\_\_\_\_ ft. Was a packer used? clay Diameter of well bore to bottom of seal ...18... Water Well Contractor's Certification: Were any loose strata cemented off? [ Yes XNo Depth This well was drilled under my jurisdiction and this report is Was a drive shoe used? XYes 🔲 No true to the best of my knowledge and belief. Was well gravel packed? ☐ Yes XNo Size of gravel: .. NAME W. W. Drilling and Pump Service
(Person, firm or corporation) (Type or print) Gravel placed from ..... ft. to ..... ft. Did any strata contain unusable water? 🔀 Yes 🛚 No Address 4157 Main St. depth of strata 400 Springfield, Ore. Type of water? sulfur Method of sealing strata off cement plug @ Drilling Machine Operator's License No. .. (10) WATER LEVELS: [Signed] Walt Wilson By Jelly (Water Well Contractor) ft. below land surface Date 8/5/66 Static level lbs. per square inch Date Contractor's License No. 268 \_\_\_\_ Date \_\_\_8/8/66 \_\_\_\_\_, 19...... Artesian pressure