WATER WELL REPORT

WATER RESOURCES DEPARTMENT CE VETTE OF OREGON SALEM, OREGON 97310 REGION (Plase type or print) within 30 days from the date of well completion.

Zinn

-		100	3 /	20
State	Well	No.105	$\langle \angle VV \rangle$	-25
				•

State Permit No. ..

pe or print)
above this line)
3108

(1) OWNER: WATER RESOURCES DEPT.	(10) LOCATION OF WELL:
Name John Hays SALEM, OREGON	County Linn Driller's well number
Address Rt. 2. Box 355. Albany, Ore. 97321	14 14 Se20on XXX T. 10S R. 2W W.M.
	Bearing and distance from section or subdivision corner
(2) TYPE OF WORK (check):	
New Well 🕍 Deepening 🗌 Reconditioning 🗍 Abandon 🗎	
If abandonment, describe material and procedure in Item 12.	(11) WATER LEVEL: Completed well.
(3) TYPE OF WELL: (4) PROPOSED USE (check):	Depth at which water was first found 26 ft.
Rotary Driven Domestic Industrial Municipal	Static level 10 ft. below land surface. Date 5-9-78
Cable K Jetted	
77	
CASING INSTALLED: Threaded Welded 17 27100 ft. Gage 250Wal	(12) WELL LOG: Diameter of well below casing10!!
" Diam, from ft. to 27 00 ft. Gage 200001	Depth drilled 28 ft. Depth of completed well 28 ft.
" Diam. from ft. to ft. Gage	Formation: Describe color, texture, grain size and structure of materials;
" Diam. fromft. toft. Gage	and show thickness and nature of each stratum and aquifer penetrated,
PERFORATIONS: Perforated? TXYes I No.	with at least one entry for each change of formation. Report each change in position of Static Water Level and indicate principal water-bearing strata.
Type of perforator used Acetylene Torch	MATERIAL From To SWL
Size of perforations ½ in. by 12 in.	
56 perforations from 2010811 ft. to 2610811 ft.	Top Soil 0 3
perforations fromft. toft.	Loam 3 12
perforations fromft. toft.	Sand & Large Gravel 12 17
	Brown Sand & Gravel 17 26
(7) SCREENS: Well screen installed? Yes No	Brown Sandy Clay & Grav. 26 28
Manufacturer's Name	
Type Model No	
Diam. Slot size Set from ft. to ft. Diam. Slot size Set from ft. to ft.	
Diam. Stot size Set from 1t. to 1t.	
(8) WELL TESTS: Drawdown is amount water level is lowered below static level	
Was a pump test made? ☐ Yes ♣ No If yes, by whom?	
gai./min. with ft. drawdown after hrs.	
" " " " " " " " " " " " " " " " " " "	n y
7.1	The state of the s
	The second secon
Artesian flow g.p.m.	
perature of water Depth artesian flow encountered ft.	Work started 5-8 19 78 Completed 5-9 19 78
(9) CONSTRUCTION:	Date well drilling machine moved off of well 5-9 19 78
Well seal-Material used Bentonite	Drilling Machine Operator's Certification:
Well sealed from land surface toft.	This well was constructed under my direct supervision.
Diameter of well bore to bottom of seal14in.	Materials used and information reported above are true to my best knowledge and belief.
Diameter of well bore below sealin.	[Signed] Date 9 5, 19 7
Number of sacks of **XXX used in well seal 400# sacks	(Drilling Machine Operator)
How was cement grout placed?	Drilling Machine Operator's License No. 436
The state of the s	Water Well Contractor's Certification:
	This well was drilled under my jurisdiction and this report is
Was a drive shee used? You Care The Things	true to the best of my knowledge and belief.
Was a drive shoe used? X Yes No Plugs	Name Merle Warren Well Drilling
	(Person, firm or corporation) (Type or print) Address RXXXXXXXX 34111 Hwy. 99E, Tangent, Or
Type of water? depth of strata	Address Angelia Fig. 1915 1 angent, or
Method of sealing strata off	[Signed] Iffile Marrin
Was well gravel packed? [] Yes 🔏 No Size of gravel:	(Water Well Contractor)
Gravel placed fromft. toft.	Contractor's License No. 182 Date 5-55, 1978