NOTICE TO WATER WELL CONTRACTOR The original and first copy of this report are to be filed with the

WATER RESOURCES DEPARTMENT, LIND SALEM, OREGON 97310 within 30 days from the date of well completion.

WATER WELL REPORT RECEIVED

STATE OF OREGON
(Please type or print)

DEC 2 197

(Do not write above this line) WATER RESOURCES DEPT.

(1) OWNER:	(10) LOCATION OF WELL:		
Name Rob Miller	County Linn Driller's well number 1401177G		
Address P.O. Box 496	SW 1/4 SW 1/4 Section 35 T. 9S R. 2W W.M.		
Stayton, Oregon 97383	Bearing and distance from section or subdivision corner		
(2) TYPE OF WORK (check):			
New Well Deepening Reconditioning Abandon			
If abandonment, describe material and procedure in Item 12.	(11) WATER LEVEL: Completed w	الم	
(3) TYPE OF WELL: (4) PROPOSED USE (check):			
Rotory / Driven []	244		
Cable		urface. Date 11/20/77	
Oug   Bored   Irrigation   Test Well   Other	Artesian pressure lbs. per square inch. Date		
CASING INSTALLED: Threaded Welded	(12) WELL LOG: Diameter of well below casing 10		
10 "Diam, from 0 ft. to 520 ft. Gage .250	5.04		
"Diam. from ft. to ft. Gage			
" Diam. from ft. to ft. Gage	Formation: Describe color, texture, grain size and structure of materials; and show thickness and nature of each stratum and aquifer penetrated,		
	with at least one entry for each change of formation. Report each change in position of Static Water Level and indicate principal water-hearing strats.		
PERFORATIONS: Perforated? A Yes I No.	position of Static Water Level and indicate prin	cipal water-bearing strata.	
Type of perforator used Torch	MATERIAL	From To SWL	
Size of perforations 3/16 in. by 6 in.	Rocky Top Soil	0 2	
400 perforations from414 ft. to520 ft.	Brown Clay & Gravel	2 10	
perforations from ft. to ft.	Brown Clay	10 21	
perforations from ft. to ft.	Sticky Gray Clay	21 46 25	
(7) SCREENS: Well screen installed?   Yes X No	Gray Claystone	46 53	
Manufacturer's Name	Claystone & Gravel	53 55	
Type Model No	Gray Claystone	55 62	
Diam. Slot size Set from ft. to ft.	Sticky Gray Clay	62 117	
Diam. Slot size Set from ft. to ft.	Green Clay	117 128	
	Gray Claystone Firm Gray Claystone	146 188	
(8) WELL TESTS: Drawdown is amount water level is lowered below static level	Fine Gray Sandstone	188 248	
Was a pump test made?   Yes Y  No If yes, by whom?	Sandy Gray Claystone	248 403	
gal./min. with ft. drawdown after hrs.	Brown Claystone	403 411	
" " "	Light Gray Claystone	411 429	
" " " " "	Light Gray Sand Rock	429 432	
ATR	Light Gray Sandstone	432 448	
gal./min. with 480 ft. drawdown after 4 hrs.	Gray Sandstone W/Streeks of	448	
Artesian flow g.p.m.	Brown Sandstone	561	
perature of water 53 Depth artesian flow encountered ft.	Work started 8/22 19 77 Complete		
(9) CONSTRUCTION:	Date well drilling machine moved off of well	11/23 1977	
Well seal—Material usedCement	Drilling Machine Operator's Certification:	, and a second	
Well sealed from land surface to25ft.	This well was constructed under my direct supervision.  Materials used and information reported above are true to my best knowledge and belief		
Diameter of well bore to bottom of seal14in.			
Diameter of well bore below sealin.	[Signed] Lingson	Data 11/29 1077	
Number of sacks of cement used in well seal	Orilling Machine Operatory		
How was cement grout placed?	Drilling Machine Operator's License No1072		
" aliand Managara (alabana alabana) ang	Woter Wall Control of Continue		
hand mixed and hand placed			
The second secon	This well was drilled under my jurisdiction and this report is true to the best of my knowledge and belief.		
Was a drive shoe used? 🗌 Yes 🛱 No Plugs Size: location ft.	Name Schoen Electric Inc.		
Did any strata contain unusable water?   Yes  No	(Parson firm or compression)! (Type or swint)		
Type of water? depth of strata	Address 626 W Queen Albany, Oregon 97321		
Method of sealing strata off			
Was well gravel packed? M Yes 🗆 No 💛 Size of gravel: 3/8Pea	[Signed] James Chole (Water Well Contractor)		
Gravel placed from25ft. to520ft.	Contractor's License No513 Date	1/30 19//	