NOTICE TO WATER WELL CONTRACTOR The original and first copy of this report are to be filed with the

WATER WELL REPORT EIVED

	95	/3418dc
•	***************************************	

	SALEM. OREGON
(1) OWNER:/	(10) LOCATION OF WELL:
Name DI CAPSTAG	County LINN Driller's well number 5/
Address 36307 SEA SCIO DRIVE	SW 14 SA 14 Section 8 T. 95 R. 3W W.M
(2) TYPE OF WORK (check):	Bearing and distance from section or subdivision corner
New Well ☐ Deepening ☐ Reconditioning ☐ Abandon ☐ If abandonment, describe material and procedure in Item 12.	
	(11) WATER LEVEL: Completed well.
(3) TYPE OF WELL: (4) PROPOSED USE (check):	Depth at which water was first found /8
Rotary Driven Domestic Industrial Municipal Domestic Municipal Domestic Driven Domestic Driven Domestic Driven Domestic Driven Domestic Driven Domestic Driven Driv	Static level 12 6 1 ft. below land surface. Date 10/28/78
Dug	Artesian pressure lbs. per square inch. Date
CASING INSTALLED: Threaded   Welded   Welded   250   ft. to 25   ft. Gage   250	(12) WELL LOG: Diameter of well below casing  Depth drilled 25 ft. Depth of completed well 25 ft.
" Diam. fromft. toft. Gage	Formation: Describe color, texture, grain size and structure of materials;
ft. Gage	and show thickness and nature of each stratum and aquifer penetrated.
PERFORATIONS: Perforated? Yes   No.	with at least one entry for each change of formation. Report each change in position of Static Water Level and indicate principal water-bearing strata.
Type of perforator used / Oukch	MATERIAL From To SWL
Size of perforations // in. by 5 in.	SANCY SOIL & SAG GRAVEL D 2
	BROWN SAND & GRAVE 2 25
perforations from ft. to ft.	
perforations fromft. toft.	
(7) SCREENS: Well screen installed?   Yes No	<u> </u>
Manufacturer's Name	
Type Model No.	
Diam. Slot size Set from ft. to ft.	
Diam. Slot size Set from ft. to ft.	
(0) WITH I MECING. Droudown to amount with the	
(8) WELL TESTS: Drawdown is amount water level is lowered below static level	
Was a pump test made? ✓ Yes □ No If yes, by whom?	
Yield: 30 6 gal./min. with / ft. drawdown after / hrs.	
" "	
<i>n n n n</i>	
Bailer test gal./min. with ft. drawdown after hrs.	
Artesian flow g.p.m.	4
perature of water Depth artesian flow encountered ft.	Work started /0/25/76 19 Completed 10/28/76 19
(9) CONSTRUCTION:	Work started / 0/25 / 76, 19 Completed / 0/38/76, 19  Date well drilling machine moved off of well / 0/28/26 19
& raid as lata	19/20/18
Well sealed from land numbers to 18	Drilling Machine Operator's Certification:  This well was constructed under my direct supervision.
Diameter of well bore to bottom of sealin.	Materials used and information reported above are true to my
Diameter of well bore below seal 10 in.	best knowledge and belief.
Number of sacks of cement used in well seal sacks_	[Signed] # AT KICLAUM Date 10/30 176
Number of sacks of bentonite used in well seal	Drilling Machine Operator's License No
Brand name of bentonite	
Number of pounds of bentonite per 100 gallons	Water Well Contractor's Certification:
of waterlbs./100 gals.	This well was drilled under my jurisdiction and this report is true to the best of my knowledge and belief
Was a drive shoe used? Yes D No Plugs Size: location ft.	Name KIONERS WELL RILLING
Did any strata contain unusable water?   Yes No	Person, firm or corporation) (Type or print)
Type of water? depth of strata	Address XTA BOX 256 A
Method of sealing strata off	[Signed] Homan & Kidden
Was well gravel packed?  Yes No Size of gravel:	(Water Well Contractor)
Gravel placed fromft. toft.	Contractor's License No. 6/5 Date 10/30/76
	, , , , , , , , , , , , , , , , , , , ,