NOTICE TO WATER WELL CONTRACTOR The original and first copy of this paper.	wmcc letter
are to be filed with the RELL VVALER WELL REPORT 9 9 9 9 9 9 9 9 9 9 9 9 9	
WATER RESOURCES DEPARTMENT OCT 31977 STATE OF OREGON SALEM, OREGON 97310 OCT 31977 (Please type or print)	
within 30 days from the date of well completion VATER RESOURCE SUBJECT Write al	
SOLEM OPECON	Linn 334/
(1) OWNER:	(10) LOCATION OF WELL:
Name Treeses Tumber Co	7
Address FO Box & Lyons 97358	10 00 01
Orlan.	14 14 Section 19 T. 95 R. 26 W.M.
(2) TYPE OF WORK (check):	Bearing and distance from section or subdivision corner
New Well Deepening □ Reconditioning □ Abandon □	
If abandonment, describe material and procedure in Item 12.	
	(11) WATER LEVEL: Completed well.
(3) TYPE OF WELL: (4) PROPOSED USE (check):	Depth at which water was first found 64 ft.
Rotary Driven Domestic Industrial Municipal Domestic	Static level 25 ft. below land surface. Date 9-26-7
Dug Bored Irrigation Test Well Other	Artesian pressure lbs. per square inch. Date
CASING INSTALLED: Threaded Co. Welded Et	
CASING INSTALLED: Threaded Welded 250	(12) WELL LOG: Diameter of well below casing
	Depth drilled 220 ft. Depth of completed well 220 ft.
	Formation: Describe color, texture, grain size and structure of materials:
Diant. 11011 1t. to	and show thickness and nature of each stratum and aquifer penetrated
PERFORATIONS: Perforated? Yes No.	with at least one entry for each change of formation. Report each change in position of Static Water Level and indicate principal water-bearing strata.
Type of perforator used	MATERIAL From To SWL
Size of perforations 38 in, by $2\frac{1}{2}$ in.	Clay & Granel 0 42
3/00 1/0	Brown Clay 42 64
perforations from ft. to ft.	Small Groull & Sand 104 108
perforations fromft. toft.	Grey Clay With Grand 108 74
	Busin clause staged nel 149
(7) SCREENS: Well screen installed? Yes No	Dysun 1 Cay 109 122
Manufacturer's Name	Gree Clay & Gravel 122 172
Type Model No	Small 4 Wed Grove la Sond 122 129
Diam. Slot size Set from ft. to ft.	Grey Clay & Granel 129 220
Diam. Slot size Set from ft. to ft.	
(8) WELL TESTS: Drawdown is amount water level is	
lowered below static level	
Was a pump test made? Wes I No If yes, by whom?	
yield: 310 gal./min. with 143 ft. drawdown after 4 hrs.	
" " " "	
и и и	
Bailer test gal./min. with ft. drawdown after hrs.	
Artesian flow g.p.m.	
perature of water Depth artesian flow encountered ft.	Work started 8-24 1977 Completed 9-20 197
10	
(9) CONSTRUCTION:	Date well drilling machine moved off of well $9-20$ 1977
Well seal-Material used Will Forms until	Drilling Machine Operator's Certification:
Well sealed from land surface toft.	This well was constructed under my direct supervision. Materials used and information reported above are true to my
Diameter of well bore to bottom of sealin.	best knowledge and belief
Diameter of well bore below seal in.	[Signed]//mon Sewell St. Date 7-23, 1977
Number of sacks of sacks in well sealsacks	(Drilling Machine Operator)
How was cement grout placed?	Drilling Machine Operator's License No
	Water Well Contractor's Certification:
The state of the s	This well was drilled under my jurisdiction and this report is
Was a drive shoe used? ☐ Yes ☐ No Plugs Size: location ft.	true to the best of my knowledge and belief.
Did any strata contain unusable water? Yes No Plugs Size: location ft.	Name
	Name 4510 DALLAS RD. N.W. (Type or print) SALEM, OR 97304
Type of water? depth of strata	Address
Method of sealing strata off	[Signed] and A Simulation
Was well gravel packed? Tes No Size of gravel:	(Water Well Contractor)
Gravel placed from ft. to ft.	Contractor's License No. Contractor's License No. Contractor's License No.
(USE ADDITIONAL SH	EETS IF NECESSARY) SP*45656-119