PESERVATION WELL

2/17
TER WELL REPORT 3403 The original and first off of this report are to be MAY 2 6 1966 WATER WELL REPORT 39

STATE ENGINEER, SALEM, OREGON 97310 Within 30 days from the date TE ENGINEE F(Please type or print) G-3891

ALEM GREGON	State Permit No	9	<u> </u>
(I) OWNER:	(11) WELL TESTS: Drawdown is amount water level is lowered below static level		
Name North Santiam Plywood Company	Was a pump test made? ☐ Yes ☐ No If yes, by whom? Stettler		
Address Lyons, Oregon	Yield: 500 gal./min. with 74 ft. drawd	own after	tier 10 hr
	" " "		# <del>************************************</del>
(2) LOCATION OF WELL:	" " "		· ·
County Marion Driller's well number	Bailer test gal./min, with ft. draw	down after	hr
Me Ton Bind's well number	Artesian flow g.p.m. Date	down ditte	
Hearing and distance from section or subdivision corner	Temperature of water Was a chemical analysis	made? [] "	Vec 1971 N
	(19) WELL LOC		
Well # 2	Diameter of well below (	casing1	
	Depth drilled 194 ft. Depth of completed w	rell .	192 ft
	Formation: Describe by color, character, size of mater show thickness of aquifers and the kind and nature of stratum penetrated, with at least one entry for each	ial and structure	cture, and
	stratum penetrated, with at least one entry for each	change of	formation
(3) TYPE OF WORK (check):	MATERIAL	FROM	то
37 777 11 6	Soil	0	3
Abandon	Medium Gravel and Glay	3	
bandonment, describe material and procedure in Item 12.	Medium Gravel	18	1.8
(4) PROPOSED USE (check): (5) TYPE OF WELL:	Sand and Gravel	32	32
Demostic C Traduction C Prince C	Medium Gravel	36	36
Irrigation Cable 17 Jetted C	Brown Clay		40
Dug	Course Gravel	40	42
(6) CASING INSTALLED: Threaded  Welded	Cemented Gravel	42	46
12 " Diam. from + 1 ft. to 189 ft. Gage 250	Medium Gravel and Sand	46	50
" Diam. fromft. toft. Gage	Brown Clay	50	80
" Diam. fromft. toft. Gage	Small Gravel and Course Sand	80	91
	Brown Clay	91	107
(7) PERFORATIONS: Perforated? ★ Yes □ No	Medium Gravel	107	109
Type of perforator used Mills Perforator	Brown Clay with Gravel	109	115
Size of perforations 3/8 in by 21 in	Grey Clay Stone	115	134
390 perforations from 36 ft. to 80 ft.	Brown Silt	134	145
220 perforations from 91 ft. to 115 ft	Medium Gravel	145	169
160 perforations from169 ft. to	Brown Course Sand	169	175
perforations from ft. to ft.	Cemented Gravel	175	182
perforations from ft. to ft.	- Jemerred Gravet	182	194
(8) SCREENS: Well screen installeds. [7] Year W. Y.		1	
Well screen installed?  Yes No Manufacturer's Name		<del>                                     </del>	
The state of the s		<del> </del>	<del></del>
Model No.		<del>                                     </del>	
Slot sizeSet fromft. toft.  DiamSlot sizeSet fromft. toft.	Work started 1-1-66 19 Completed 1	18-66	
	Date well drilling and Line	18-66	19
(9) CONSTRUCTION:	(13) PUMP:	LOWUU	
Well seal-Material used in seal Drill Cuttings & Bentonite			
Depth of seal25ft. Was a packer used?No	Manufacturer's Name	.4	
Diameter of well bore to bottom of seal	Type:		
Were any loose strata cemented off? \(\subseteq\) Yes \(\subseteq\) Depth	Water Well Contractor's Certification:		
Was a drive shoe used [M] Yes \( \subseteq No. \)			
Was well gravel packed? ☐ Yes ☐ No Size of gravel:	This well was drilled under my jurisdiction a true to the best of my knowledge and belief.	and this re	port is
Gravel placed fromft.			
Did any strata contain unusable water?   Yes  No	NAME MILLER - ROBINSON - WEST		
Type of western	(Person, firm or corporation) (Typ	e or print)	
Method of sealing strata off	Address 5545 Joseph St. S.E. Sale	m, Oreg	on
(10) WATER LEVELS:	Drilling Machine Operator's License No.	59	
(20) WILLER DEVELO:		·	•••••
Static level 46 ft. below land surface Date 4-18-66	[Signed] Harlan F. Milled		***********
Artesian pressure lbs. per square inch Date	(water well Contractor)	66	
/7/CP A P P P P P P P P P P P P P P P P P P	Contractor's License No	•00	19