

NOTICE TO WATER WELL CONTRACTOR
The original and first copy
of this report are to be
filed with the

WATER WELL REPORT

RECEIVED
JUN 11 1973

STATE OF OREGON
(Please type or print)

STATE ENGINEER
SALEM, OREGON

State Well No. 9S/3E-32
State Permit No. G 6332
well #2 G6843

STATE ENGINEER, SALEM, OREGON 97310
within 30 days from the date
of well completion.

Linn
3499

(1) OWNER:

Name Don Walker Ranch
Address M.I. City, Oe.

(2) TYPE OF WORK (check):

New Well Deepening Reconditioning Abandon
If abandonment, describe material and procedure in Item 12.

(3) TYPE OF WELL:

Rotary Driven
Cable Jetted
Dug Bored

(4) PROPOSED USE (check):

Domestic Industrial Municipal
Irrigation Test Well Other

(5) CASING INSTALLED:

Threaded Welded
10" Diam. from 0 ft. to 162 ft. Gage 1250
" Diam. from ft. to ft. Gage
" Diam. from ft. to ft. Gage

(6) PERFORATIONS:

Perforated? Yes No
Type of perforator used Oxy Acet.
Size of perforations 3/8 in. by 8 in.
65 perforations from 147 ft. to 162 ft.
perforations from ft. to ft.
perforations from ft. to ft.

(7) SCREENS:

Well screen installed? Yes No
Manufacturer's Name
Type Model No.
Diam. Slot size Set from ft. to ft.
Diam. Slot size Set from ft. to ft.

(8) WELL TESTS:

Drawdown is amount water level is lowered below static level
Was a pump test made? Yes No If yes, by whom?
Yield: gal./min. with ft. drawdown after hrs.
" " " " " "
" " " " " "
Bailer test 50 gal./min. with 47 ft. drawdown after 1 hrs.
Artesian flow g.p.m.
Temperature of water Depth artesian flow encountered ft.

(9) CONSTRUCTION:

Well seal—Material used Cement
Well sealed from land surface to 20 ft.
Diameter of well bore to bottom of seal 14 in.
Diameter of well bore below seal 10 in.
Number of sacks of cement used in well seal 4 sacks
Number of sacks of bentonite used in well seal sacks
Brand name of bentonite
Number of pounds of bentonite per 100 gallons
of water lbs./100 gals.
Was a drive shoe used? Yes No Plugs Size: location ft.
Did any strata contain unusable water? Yes No
Type of water? depth of strata
Method of sealing strata off
Was well gravel packed? Yes No Size of gravel:
Gravel placed from ft. to ft.

(10) LOCATION OF WELL:

County Linn Driller's well number 479-73
1/4 Section 32 T. 9S R. 3E W.M.
Bearing and distance from section or subdivision corner

(11) WATER LEVEL: Completed well.

Depth at which water was first found 55 ft.
Static level 53 ft. below land surface. Date June 9, 1973
Artesian pressure lbs. per square inch. Date

(12) WELL LOG:

Diameter of well below casing
Depth drilled 162 ft. Depth of completed well 162 ft.

Formation: Describe color, texture, grain size and structure of materials; and show thickness and nature of each stratum and aquifer penetrated, with at least one entry for each change of formation. Report each change in position of Static Water Level and indicate principal water-bearing strata.

MATERIAL	From	To	SWL
Soil	0	2	
Clay + Boulders	2	40	
Gravel Large	40	50	
Boulders	50	55	20
Gravel Small Sandy	55	75	
Boulders + Gravel	75	100	
Clay Sandy	100	140	
Small Gravel - Sandy	140	145	
Gravel Sandy - Med	145	159	
Sand	159	162	53

Work started June 2 1973 Completed June 9 1973
Date well drilling machine moved off of well June 9 1973

Drilling Machine Operator's Certification:

This well was constructed under my direct supervision. Materials used and information reported above are true to my best knowledge and belief.

[Signed] William C. Perry Date June 9, 1973
(Drilling Machine Operator)

Drilling Machine Operator's License No. 1174

Water Well Contractor's Certification:

This well was drilled under my jurisdiction and this report is true to the best of my knowledge and belief.

Name William C. Perry Drilling
(Person, firm or corporation) (Type or print)

Address 4190 Fletcher Rd N.E. Subm. Oe.

[Signed] William C. Perry
(Water Well Contractor)

Contractor's License No. 75 Date June 9, 1973