

RECEIVED

WATER WELL REPORT

WATER RESOURCES DEPARTMENT
SALEM, OREGON 97310
within 30 days from the date
of well completion.

JAN 4 1979

STATE OF OREGON
(Please type or print)

WATER RESOURCES DEPT.
SALEM, OREGON

State Well No. 105/30759C
State Permit No.

(1) OWNER:

Name Dennis Dickson
Address Albany, Ore.

(2) TYPE OF WORK (check):

New Well ☒ Deepening ☐ Reconditioning ☐ Abandon ☐

If abandonment, describe material and procedure in Item 12.

(3) TYPE OF WELL:

Rotary ☒ Driven ☐
Cable ☐ Jetted ☐
Dug ☐ Bored ☐

(4) PROPOSED USE (check):

Domestic ☒ Industrial ☐ Municipal ☐
Irrigation ☐ Test Well ☐ Other ☐

CASING INSTALLED:

Threaded ☐ Welded ☒

6" Diam. from 0 ft. to 55 ft. Gage 220
4" P.V.C. Diam. from 0 ft. to 415 ft. Gage 125
" Diam. from ft. to ft. Gage

PERFORATIONS:

Perforated? ☒ Yes ☒ No

Type of perforator used

Size of perforations in. by in.
perforations from ft. to ft.
perforations from ft. to ft.
perforations from ft. to ft.

(7) SCREENS:

Well screen installed? ☐ Yes ☒ No

Manufacturer's Name
Type Model No.
Diam. Slot size Set from ft. to ft.
Diam. Slot size Set from ft. to ft.

(8) WELL TESTS:

Drawdown is amount water level is lowered below static level

Was a pump test made? ☒ Yes ☐ No If yes, by whom?
Yield: 4 gal./min. with 220 ft. drawdown after 4 hrs.
" " " " " "

Bailer test gal./min. with ft. drawdown after hrs.

Artesian flow g.p.m.

Temperature of water Depth artesian flow encountered ft.

(9) CONSTRUCTION:

Well seal—Material used Cement
Well sealed from land surface to 20 ft.
Diameter of well bore to bottom of seal 9 in.
Diameter of well bore below seal 4 in.
Number of sacks of cement used in well seal 4 sacks
How was cement grout placed? Poured

Was a drive shoe used? ☐ Yes ☒ No Plugs Size: location ft.

Did any strata contain unusable water? ☐ Yes ☒ No

Type of water? depth of strata

Method of sealing strata off

Was well gravel packed? ☐ Yes ☒ No Size of gravel:

Gravel placed from ft. to ft.

(10) LOCATION OF WELL:

County Linn Driller's well number 662-78
S.W. 1/4 NE 1/4 Section 15 T. 10S R. 34E W.M.
Bearing and distance from section or subdivision corner

(11) WATER LEVEL: Completed well.

Depth at which water was first found 190 ft.

Static level 72 ft. below land surface. Date Sept 21/1978

Artesian pressure lbs. per square inch. Date

(12) WELL LOG:

Diameter of well below casing 4

Depth drilled 425 ft. Depth of completed well 415 ft.

Formation: Describe color, texture, grain size and structure of materials; and show thickness and nature of each stratum and aquifer penetrated, with at least one entry for each change of formation. Report each change in position of Static Water Level and indicate principal water-bearing strata.

MATERIAL	From	To	SWL
Soil	0	2	
Claystone Yellow	2	5	
Clay	5	28	
Claystone	28	25	
Sandstone Gray	25	110	
Sandstone Dark Gray	110	270	
Rock Med Hard	270	425	22
P.V.C. liner installed			
0-415'			
PCH 180-415-			
168-PCH 1/8 x 6"			

Work started Sept 11 1978 Completed Sept 21 1978

Date well drilling machine moved off of well Sept 22 1978

Drilling Machine Operator's Certification:

This well was constructed under my direct supervision. Materials used and information reported above are true to my best knowledge and belief.

[Signed] William C. Long Date Sept 22, 1978
(Drilling Machine Operator)

Drilling Machine Operator's License No. 117

Water Well Contractor's Certification:

This well was drilled under my jurisdiction and this report is true to the best of my knowledge and belief.

Name Long Drilling (Type or print)
(Person, firm or corporation)

Address 11401 Steinkamp Rd SE Anasville, Tex

[Signed] William C. Long (Water Well Contractor)

Contractor's License No. 75 Date Sept 22, 1978