The original and first copy of this report are to be filed with the	**************************************	1 105/	2w -	28
STATE ENGINEER, SALEM, OREGON 57310 4 1975 STATE OF within 30 days from the date TATE ENGINEER (Do not write ab SALEM, OREGON	or print) STATE ENGINEES ate Permit N			
of well completion.	ove this line SALEM OREGON			
				
(1) OWNER: OOO	(10) LOCATION OF WELL:			
Name Marvin Slaser	County L/N/ Driller's well number			
Address 72 Bay 85 Scanney	1/4 1/4 Section 2 8 T. 10 S R. 2 W.M.			
	Bearing and distance from section or subdivision corner			
(2) TYPE OF WORK (check):	north east corrose South 301			
New Well ☐ Deepening ☐ Reconditioning ☐ Abandon ☐ If abandonment, describe material and procedure in Item 12.	Tuest 240'			
(3) TYPE OF WELL: (4) PROPOSED USE (check):	(11) WATER LEVEL: Completed well. Depth at which water was first found ft.			
Rotary Driven Domestic Mindustrial Municipal Domestic	Static level 18 ft. below land surface. Date 9-10-74			
Cable Dug	Artesian pressure lbs. per square inch. Date			
CASING INSTALLED: Threaded [] Welded [2]	(40)			Offic
	(12) WELL LOG: Diameter of well b	elow cas	ing	<i>Y</i>
•	Depth drilled /// ft. Depth of compl	eted well	39	f t.
"Diam. from ft. to ft. Gage ft. Gage ft. To ft. Gage ft.	Formation: Describe color, texture, grain size a and show thickness and nature of each stratum	n and ac	juifer pe	netrated,
PERFORATIONS: Perforated?	with at least one entry for each change of format position of Static Water Level and indicate prin			
Type of perforator used lut with a Responden	MATERIAL	From	То	swl
Size of perforations in. by in.	Sanda Grovel	25	35	
100 perforations from 20 ft. to 35 ft.	Vellow Clay	35	37	
perforations from ft. to ft.	Sand+ Gravel loose yellow	37	39	
perforations from ft. to ft.			•	,
	-1			
(7) SCREENS: Well screen installed? ☐ Yes No			``	
Manufacturer's Name	i kan ka i			
Type Model No.				
Diam Slot size Set from ft. to ft.				
Diam Slot size Set from ft. to ft.	•			
(8) WELL TESTS: Drawdown is amount water level is lowered below static level				
Was a pump test made? The Yes No If yes, by whom?				
Yield: gal./min. with ft. drawdown after hrs.	ν.			
" " " "				
" " "	t was ever			
	·			
Bailer test 40 gal./min. with ft. drawdown after hrs.				
Artesian flow g.p.m.				
perature of water 54 Depth artesian flow encountered ft.	Work started 9 - 7 19 > 4 Complete	ed 9-	10	19 > 4
(9) CONSTRUCTION:	Date well drilling machine moved off of well	9-1	10	19 > 5
Well seal-Material used Itesting Seal	Drilling Machine Operator's Certification:	•		/
	This well was constructed under my	direct	super	vision.
Well sealed from land surface toft.	Materials used and information reported	above a	are tru	e to my
Diameter of well bore to bottom of seal in.	best knowledge and belief.		10	
Diameter of well bore below seal in.	[Signed]// (Drilling Machine Operator)	Date .//.	18	, 19.4
Number of sacks of cement used in well seal sacks	Drilling Machine Operator's License No.	23/	2	
Number of sacks of bentonite used in well sealsacks				
Brand name of bentonite	Water Well Contractor's Certification:			
Number of pounds of bentonite per 100 gallons	This well was drilled under my jurisdi	etion an	nd this	report is
of water lbs./100 gals.	true to the best of my knowledge and bel		v.iii 1	
Was a drive shoe used? \(\subseteq \text{Yes} - \subseteq \text{No Plugs} \) Size: location ft.	Name BOBS. ELELL DRILLING (Person, firm or corporation)	2 1N	Έ.	
Did any strata contain unusable water? Yes No				
Type of water? depth of strata	Address 465 Wagon Wheelds	Sel	anco	orlan
Method of sealing strata off	ISSUMMENT DE PRINTERS			0 3.
Was well gravel packed? Tyes No Size of gravel:	(Water Well Contr	actor)		
	Contractor's License No /T/ Data C	2-16	3	10 2/-
Gravel placed from ft. to ft.	Contractor's License No. / Z Date			, 18.29